

CU-2Z52VBR: Only Wall-Mounted Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
2 rooms	16 + 16	1.60	1.60	-	-	-	3.20 (1.5-4.0)	3.00	680 (250-990)	4.71	2.60	2.60	-	-	-	5.20 (1.1-7.0)	5.20	1210 (210-1910)	4.30
	16 + 20	1.60	2.00	-	-	-	3.60 (1.5-4.5)	3.50	780 (250-1150)	4.62	2.40	3.00	-	-	-	5.40 (1.1-7.0)	5.40	1260 (210-1890)	4.29
	16 + 25	1.60	2.50	-	-	-	4.10 (1.5-5.2)	4.00	900 (250-1370)	4.56	2.20	3.40	-	-	-	5.60 (1.1-7.0)	5.70	1310 (210-1890)	4.27
	16 + 35	1.65	3.55	-	-	-	5.20 (1.5-6.0)	5.90	1350 (250-1620)	3.85	1.90	4.20	-	-	-	6.10 (1.1-7.0)	6.20	1430 (210-1890)	4.27
	16 + 42	1.45	3.75	-	-	-	5.20 (1.5-6.0)	5.90	1350 (250-1620)	3.85	1.70	4.40	-	-	-	6.10 (1.1-7.2)	6.20	1430 (210-1900)	4.27
	16 + 50	1.25	3.95	-	-	-	5.20 (1.5-6.0)	5.90	1350 (250-1620)	3.85	1.50	4.60	-	-	-	6.10 (1.1-7.2)	6.20	1430 (210-1900)	4.27
	20 + 20	2.00	2.00	-	-	-	4.00 (1.5-5.0)	4.00	890 (250-1310)	4.49	2.80	2.80	-	-	-	5.60 (1.1-7.0)	5.70	1310 (210-1870)	4.27
	20 + 25	2.00	2.50	-	-	-	4.50 (1.5-5.2)	4.50	1030 (250-1370)	4.37	2.60	3.20	-	-	-	5.80 (1.1-7.0)	5.90	1360 (210-1870)	4.26
	20 + 35	1.90	3.30	-	-	-	5.20 (1.5-6.0)	5.90	1350 (250-1620)	3.85	2.20	3.90	-	-	-	6.10 (1.1-7.2)	6.20	1430 (210-1900)	4.27
	20 + 42	1.70	3.50	-	-	-	5.20 (1.5-6.0)	5.90	1350 (250-1620)	3.85	1.95	4.15	-	-	-	6.10 (1.1-7.2)	6.20	1430 (210-1900)	4.27
	20 + 50	1.50	3.70	-	-	-	5.20 (1.5-6.0)	5.90	1350 (250-1620)	3.85	1.75	4.35	-	-	-	6.10 (1.1-7.2)	6.20	1430 (210-1900)	4.27
	25 + 25	2.60	2.60	-	-	-	5.20 (1.5-6.0)	5.90	1350 (250-1620)	3.85	3.05	3.05	-	-	-	6.10 (1.1-7.2)	6.20	1430 (210-1900)	4.27
	25 + 35	2.15	3.05	-	-	-	5.20 (1.5-6.0)	5.90	1350 (250-1620)	3.85	2.55	3.55	-	-	-	6.10 (1.1-7.2)	6.20	1430 (210-1900)	4.27
	25 + 42	1.95	3.25	-	-	-	5.20 (1.5-6.0)	5.90	1350 (250-1620)	3.85	2.30	3.80	-	-	-	6.10 (1.1-7.2)	6.20	1430 (210-1900)	4.27
	25 + 50	1.75	3.45	-	-	-	5.20 (1.5-6.0)	5.90	1350 (250-1620)	3.85	2.05	4.05	-	-	-	6.10 (1.1-7.2)	6.20	1430 (210-1900)	4.27
	35 + 35	2.60	2.60	-	-	-	5.20 (1.5-6.0)	5.90	1350 (250-1620)	3.85	3.05	3.05	-	-	-	6.10 (1.1-7.2)	6.20	1430 (210-1900)	4.27
	35 + 42	2.35	2.85	-	-	-	5.20 (1.5-6.0)	5.90	1350 (250-1620)	3.85	2.75	3.35	-	-	-	6.10 (1.1-7.2)	6.20	1430 (210-1900)	4.27

CU-2Z52VBR: Free Multi Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
2 rooms	16 + 16	1.60	1.60	-	-	-	3.20 (1.5-4.0)	3.30	740 (250-1050)	4.32	2.60	2.60	-	-	-	5.20 (1.1-7.0)	5.50	1270 (210-1970)	4.09
	16 + 20	1.60	2.00	-	-	-	3.60 (1.5-4.5)	3.70	840 (250-1210)	4.29	2.40	3.00	-	-	-	5.40 (1.1-7.0)	5.70	1320 (210-1950)	4.09
	16 + 25	1.60	2.50	-	-	-	4.10 (1.5-5.2)	4.30	960 (250-1430)	4.27	2.20	3.40	-	-	-	5.60 (1.1-7.0)	5.90	1370 (210-1950)	4.09
	16 + 35	1.65	3.55	-	-	-	5.20 (1.5-6.0)	6.10	1410 (250-1680)	3.69	1.90	4.20	-	-	-	6.10 (1.1-7.0)	6.40	1490 (210-1950)	4.09
	16 + 42	1.45	3.75	-	-	-	5.20 (1.5-6.0)	6.10	1410 (250-1680)	3.69	1.70	4.40	-	-	-	6.10 (1.1-7.2)	6.40	1490 (210-1960)	4.09
	16 + 50	1.25	3.95	-	-	-	5.20 (1.5-6.0)	6.10	1410 (250-1680)	3.69	1.50	4.60	-	-	-	6.10 (1.1-7.2)	6.40	1490 (210-1960)	4.09
	20 + 20	2.00	2.00	-	-	-	4.00 (1.5-5.0)	4.20	950 (250-1370)	4.21	2.80	2.80	-	-	-	5.60 (1.1-7.0)	5.90	1370 (210-1930)	4.09
	20 + 25	2.00	2.50	-	-	-	4.50 (1.5-5.2)	3.50	810 (250-1430)	5.56	2.60	3.20	-	-	-	5.80 (1.1-7.0)	6.10	1420 (210-1930)	4.08
	20 + 35	1.90	3.30	-	-	-	5.20 (1.5-6.0)	6.10	1410 (250-1680)	3.69	2.20	3.90	-	-	-	6.10 (1.1-7.2)	6.40	1490 (210-1960)	4.09
	20 + 42	1.70	3.50	-	-	-	5.20 (1.5-6.0)	6.10	1410 (250-1680)	3.69	1.95	4.15	-	-	-	6.10 (1.1-7.2)	6.40	1490 (210-1960)	4.09
	20 + 50	1.50	3.70	-	-	-	5.20 (1.5-6.0)	6.10	1410 (250-1680)	3.69	1.75	4.35	-	-	-	6.10 (1.1-7.2)	6.40	1490 (210-1960)	4.09
	25 + 25	2.60	2.60	-	-	-	5.20 (1.5-6.0)	6.10	1410 (250-1680)	3.69	3.05	3.05	-	-	-	6.10 (1.1-7.2)	6.40	1490 (210-1960)	4.09
	25 + 35	2.15	3.05	-	-	-	5.20 (1.5-6.0)	6.10	1410 (250-1680)	3.69	2.55	3.55	-	-	-	6.10 (1.1-7.2)	6.40	1490 (210-1960)	4.09
	25 + 42	1.95	3.25	-	-	-	5.20 (1.5-6.0)	6.10	1410 (250-1680)	3.69	2.30	3.80	-	-	-	6.10 (1.1-7.2)	6.40	1490 (210-1960)	4.09
	25 + 50	1.75	3.45	-	-	-	5.20 (1.5-6.0)	6.10	1410 (250-1680)	3.69	2.05	4.05	-	-	-	6.10 (1.1-7.2)	6.40	1490 (210-1960)	4.09
	35 + 35	2.60	2.60	-	-	-	5.20 (1.5-6.0)	6.10	1410 (250-1680)	3.69	3.05	3.05	-	-	-	6.10 (1.1-7.2)	6.40	1490 (210-1960)	4.09
	35 + 42	2.35	2.85	-	-	-	5.20 (1.5-6.0)	6.10	1410 (250-1680)	3.69	2.75	3.35	-	-	-	6.10 (1.1-7.2)	6.40	1490 (210-1960)	4.09

CU-3Z54VBR: Only Wall-Mounted Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	Total
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
2 rooms	16 + 16	1.60	1.60	-	-	-	3.20 (1.8-6.2)	3.0	630 (330-2130)	5.08	2.60	2.60	-	-	-	5.20 (1.4-7.0)	5.9	1340 (340-2070)	3.88
	16 + 20	1.60	2.00	-	-	-	3.60 (1.8-6.2)	3.5	770 (330-2090)	4.68	2.58	3.22	-	-	-	5.80 (1.4-7.0)	6.7	1520 (330-2030)	3.82
	16 + 25	1.60	2.50	-	-	-	4.10 (1.8-6.2)	4.1	920 (330-2090)	4.46	2.42	3.78	-	-	-	6.20 (1.4-7.0)	7.2	1650 (330-2030)	3.76
	16 + 35	1.60	3.50	-	-	-	5.10 (1.8-6.3)	5.9	1350 (330-2100)	3.78	2.20	4.80	-	-	-	7.00 (1.4-7.3)	8.2	1900 (290-2130)	3.68
	16 + 42	1.49	3.91	-	-	-	5.40 (1.9-6.4)	6.6	1500 (350-2140)	3.60	1.93	5.07	-	-	-	7.00 (1.4-7.3)	8.2	1890 (310-2120)	3.70
	16 + 50	1.31	4.09	-	-	-	5.40 (1.9-6.8)	5.8	1320 (340-2080)	4.09	1.70	5.30	-	-	-	7.00 (1.4-8.0)	7.5	1710 (270-2230)	4.09
	20 + 20	2.00	2.00	-	-	-	4.00 (1.8-6.2)	4.0	890 (330-2050)	4.49	3.20	3.20	-	-	-	6.40 (1.4-7.0)	7.5	1710 (320-2030)	3.74
	20 + 25	2.00	2.50	-	-	-	4.50 (1.8-6.2)	4.8	1080 (330-2050)	4.17	3.02	3.78	-	-	-	6.80 (1.4-7.0)	8.0	1840 (290-2030)	3.70
	20 + 35	1.96	3.44	-	-	-	5.40 (1.8-6.3)	6.4	1470 (330-2060)	3.67	2.55	4.45	-	-	-	7.00 (1.4-7.3)	8.2	1890 (280-2120)	3.70
	20 + 42	1.74	3.66	-	-	-	5.40 (1.9-6.4)	6.4	1470 (350-2100)	3.67	2.26	4.74	-	-	-	7.00 (1.4-7.3)	8.0	1850 (300-2080)	3.78
	20 + 50	1.54	3.86	-	-	-	5.40 (1.9-6.8)	5.6	1280 (340-2080)	4.22	2.00	5.00	-	-	-	7.00 (1.4-8.0)	7.4	1700 (270-2230)	4.12
	25 + 25	2.50	2.50	-	-	-	5.00 (1.8-6.2)	5.8	1320 (330-2050)	3.79	3.50	3.50	-	-	-	7.00 (1.4-7.2)	8.2	1900 (290-2100)	3.68
	25 + 35	2.25	3.15	-	-	-	5.40 (1.9-6.3)	6.4	1470 (350-2060)	3.67	2.92	4.08	-	-	-	7.00 (1.4-7.3)	8.2	1890 (280-2120)	3.70
	25 + 42	2.01	3.39	-	-	-	5.40 (1.9-6.4)	6.4	1470 (350-2100)	3.67	2.61	4.39	-	-	-	7.00 (1.4-7.3)	8.0	1850 (280-2080)	3.78
	25 + 50	1.80	3.60	-	-	-	5.40 (1.9-6.8)	5.6	1280 (340-2080)	4.22	2.33	4.67	-	-	-	7.00 (1.4-8.0)	7.4	1700 (240-2230)	4.12
	35 + 35	2.70	2.70	-	-	-	5.40 (1.9-6.4)	6.3	1430 (350-2060)	3.78	3.50	3.50	-	-	-	7.00 (1.4-7.5)	8.0	1840 (270-2140)	3.80
	35 + 42	2.45	2.95	-	-	-	5.40 (1.9-6.5)	6.3	1430 (350-2110)	3.78	3.18	3.82	-	-	-	7.00 (1.4-7.5)	7.9	1830 (260-2140)	3.83
	35 + 50	2.22	3.18	-	-	-	5.40 (1.9-6.9)	5.6	1280 (360-2080)	4.22	2.88	4.12	-	-	-	7.00 (1.4-8.0)	7.4	1680 (240-2160)	4.17
42 + 42	2.70	2.70	-	-	-	5.40 (1.9-6.5)	6.3	1430 (350-2110)	3.78	3.50	3.50	-	-	-	7.00 (1.4-7.6)	7.8	1790 (260-2170)	3.91	
42 + 50	2.47	2.93	-	-	-	5.40 (1.9-6.9)	5.6	1280 (360-2080)	4.22	3.20	3.80	-	-	-	7.00 (1.4-8.0)	7.4	1680 (240-2160)	4.17	
3 rooms	16 + 16 + 16	1.60	1.60	1.60	-	-	4.80 (1.8-7.2)	4.2	930 (360-2140)	5.16	2.33	2.33	2.33	-	-	6.99 (1.5-8.1)	6.9	1550 (290-2270)	4.51
	16 + 16 + 20	1.66	1.66	2.08	-	-	5.40 (1.8-7.3)	5.1	1120 (360-2180)	4.82	2.15	2.15	2.70	-	-	7.00 (1.6-9.0)	6.8	1540 (320-2630)	4.55
	16 + 16 + 25	1.52	1.52	2.36	-	-	5.40 (1.9-7.2)	5.1	1120 (390-2090)	4.82	1.96	1.96	3.08	-	-	7.00 (1.6-9.0)	6.8	1540 (320-2630)	4.55
	16 + 16 + 35	1.29	1.29	2.82	-	-	5.40 (1.9-7.2)	5.1	1120 (390-2050)	4.82	1.67	1.67	3.66	-	-	7.00 (1.6-9.0)	6.7	1520 (340-2610)	4.61
	16 + 16 + 42	1.17	1.17	3.06	-	-	5.40 (1.8-7.3)	5.1	1120 (390-2090)	4.82	1.51	1.51	3.98	-	-	7.00 (1.6-9.0)	6.7	1510 (310-2560)	4.64
	16 + 16 + 50	1.05	1.05	3.30	-	-	5.40 (1.8-7.3)	4.7	1050 (420-1920)	5.14	1.37	1.37	4.26	-	-	7.00 (1.6-9.0)	6.2	1410 (330-2410)	4.96
	16 + 20 + 20	1.54	1.93	1.93	-	-	5.40 (1.9-7.2)	5.1	1120 (390-2090)	4.82	2.00	2.50	2.50	-	-	7.00 (1.6-9.0)	6.8	1530 (310-2620)	4.58
	16 + 20 + 25	1.42	1.77	2.21	-	-													

CU-3Z54VBR: Free Multi Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION								HEATING OPERATION									
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	Total
		kW	kW	kW	kW	kW				kW	kW	kW	kW	kW				kW	kW
2 rooms	16 + 16	1.60	1.60	-	-	-	3.20 (1.8-6.2)	3.2	690 (330-2190)	4.64	2.60	2.60	-	-	-	5.20 (1.4-7.0)	6.4	1460 (340-2190)	3.56
	16 + 20	1.60	2.00	-	-	-	3.60 (1.8-6.2)	3.7	830 (330-2150)	4.34	2.58	3.22	-	-	-	5.80 (1.4-7.0)	7.2	1640 (330-2150)	3.54
	16 + 25	1.60	2.50	-	-	-	4.10 (1.8-6.2)	4.4	980 (330-2150)	4.18	2.42	3.78	-	-	-	6.20 (1.4-7.0)	7.7	1770 (330-2150)	3.50
	16 + 35	1.60	3.50	-	-	-	5.10 (1.8-6.3)	6.2	1410 (330-2160)	3.62	2.20	4.80	-	-	-	7.00 (1.4-7.3)	8.8	2020 (290-2250)	3.47
	16 + 42	1.49	3.91	-	-	-	5.40 (1.9-6.4)	6.8	1560 (350-2200)	3.46	1.93	5.07	-	-	-	7.00 (1.4-7.3)	8.7	2010 (310-2240)	3.48
	16 + 50	1.31	4.09	-	-	-	5.40 (1.9-6.8)	6.0	1380 (340-2140)	3.91	1.70	5.30	-	-	-	7.00 (1.4-8.0)	7.9	1830 (270-2350)	3.83
	20 + 20	2.00	2.00	-	-	-	4.00 (1.8-6.2)	4.2	950 (330-2110)	4.21	3.20	3.20	-	-	-	6.40 (1.4-7.0)	7.9	1830 (320-2150)	3.50
	20 + 25	2.00	2.50	-	-	-	4.50 (1.8-6.2)	5.0	1140 (330-2110)	3.95	3.02	3.78	-	-	-	6.80 (1.4-7.0)	8.5	1960 (290-2150)	3.47
	20 + 35	1.96	3.44	-	-	-	5.40 (1.8-6.3)	6.7	1530 (330-2120)	3.53	2.55	4.45	-	-	-	7.00 (1.4-7.3)	8.7	2010 (280-2240)	3.48
	20 + 42	1.74	3.66	-	-	-	5.40 (1.9-6.4)	6.7	1530 (350-2160)	3.53	2.26	4.74	-	-	-	7.00 (1.4-7.3)	8.5	1970 (300-2200)	3.55
	20 + 50	1.54	3.86	-	-	-	5.40 (1.9-6.8)	5.9	1340 (340-2140)	4.03	2.00	5.00	-	-	-	7.00 (1.4-8.0)	7.9	1820 (270-2350)	3.85
	25 + 25	2.50	2.50	-	-	-	5.00 (1.8-6.2)	6.0	1380 (330-2110)	3.62	3.50	3.50	-	-	-	7.00 (1.4-7.2)	8.8	2020 (290-2220)	3.47
	25 + 35	2.25	3.15	-	-	-	5.40 (1.9-6.3)	6.7	1530 (350-2120)	3.53	2.92	4.08	-	-	-	7.00 (1.4-7.3)	8.7	2010 (280-2240)	3.48
	25 + 42	2.01	3.39	-	-	-	5.40 (1.9-6.4)	6.7	1530 (350-2160)	3.53	2.61	4.39	-	-	-	7.00 (1.4-7.3)	8.5	1970 (280-2200)	3.55
	25 + 50	1.80	3.60	-	-	-	5.40 (1.9-6.8)	5.9	1340 (340-2140)	4.03	2.33	4.67	-	-	-	7.00 (1.4-8.0)	7.9	1820 (240-2350)	3.85
	35 + 35	2.70	2.70	-	-	-	5.40 (1.9-6.4)	6.5	1490 (350-2120)	3.62	3.50	3.50	-	-	-	7.00 (1.4-7.5)	8.5	1960 (270-2260)	3.57
	35 + 42	2.45	2.95	-	-	-	5.40 (1.9-6.5)	6.5	1490 (350-2170)	3.62	3.18	3.82	-	-	-	7.00 (1.4-7.5)	8.5	1950 (260-2260)	3.59
	35 + 50	2.22	3.18	-	-	-	5.40 (1.9-6.9)	5.9	1340 (360-2140)	4.03	2.88	4.12	-	-	-	7.00 (1.4-8.0)	7.8	1800 (240-2280)	3.89
42 + 42	2.70	2.70	-	-	-	5.40 (1.9-6.5)	6.5	1490 (350-2170)	3.62	3.50	3.50	-	-	-	7.00 (1.4-7.6)	8.3	1910 (260-2290)	3.66	
42 + 50	2.47	2.93	-	-	-	5.40 (1.9-6.9)	5.9	1340 (360-2140)	4.03	3.20	3.80	-	-	-	7.00 (1.4-8.0)	7.8	1800 (240-2280)	3.89	
3 rooms	16 + 16 + 16	1.60	1.60	1.60	-	-	4.80 (1.8-7.2)	4.6	1020 (360-2230)	4.71	2.33	2.33	2.33	-	-	6.99 (1.5-8.1)	7.6	1730 (290-2450)	4.04
	16 + 16 + 20	1.66	1.66	2.08	-	-	5.40 (1.8-7.3)	5.5	1210 (360-2270)	4.46	2.15	2.15	2.70	-	-	7.00 (1.6-9.0)	7.6	1720 (320-2810)	4.07
	16 + 16 + 25	1.52	1.52	2.36	-	-	5.40 (1.9-7.2)	5.5	1210 (390-2180)	4.46	1.96	1.96	3.08	-	-	7.00 (1.6-9.0)	7.6	1720 (320-2810)	4.07
	16 + 16 + 35	1.29	1.29	2.82	-	-	5.40 (1.9-7.2)	5.5	1210 (390-2140)	4.46	1.67	1.67	3.66	-	-	7.00 (1.6-9.0)	7.5	1700 (340-2790)	4.12
	16 + 16 + 42	1.17	1.17	3.06	-	-	5.40 (1.8-7.3)	5.5	1210 (390-2180)	4.46	1.51	1.51	3.98	-	-	7.00 (1.6-9.0)	7.5	1690 (310-2740)	4.14
	16 + 16 + 50	1.05	1.05	3.30	-	-	5.40 (1.8-7.3)	5.1	1140 (420-2010)	4.74	1.37	1.37	4.26	-	-	7.00 (1.6-9.0)	7.0	1590 (330-2590)	4.40
	16 + 20 + 20	1.54	1.93	1.93	-	-	5.40 (1.9-7.2)	5.5	1210 (390-2180)	4.46	2.00	2.50	2.50	-	-	7.00 (1.6-9.0)	7.6	1710 (310-2800)	4.09
	16 + 20 + 25	1.42	1.77	2.21	-	-													

CU-4Z71VBR: Only Wall-Mounted Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION								HEATING OPERATION									
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	Total
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
2 rooms	16 + 16	1.60	1.60	-	-	-	3.20 (1.9-6.4)	2.9	600 (270-2160)	5.33	2.60	2.60	-	-	-	5.20 (2.7-9.8)	6.0	1380 (660-3090)	3.77
	16 + 20	1.60	2.00	-	-	-	3.60 (1.9-6.4)	3.4	730 (270-2120)	4.93	2.58	3.22	-	-	-	5.80 (2.7-9.8)	6.8	1560 (650-3100)	3.72
	16 + 25	1.60	2.50	-	-	-	4.10 (1.9-6.4)	3.9	870 (270-2120)	4.71	2.42	3.78	-	-	-	6.20 (2.7-9.8)	7.4	1690 (650-3100)	3.67
	16 + 35	1.60	3.50	-	-	-	5.10 (1.9-6.9)	5.6	1290 (270-2520)	3.95	2.23	4.87	-	-	-	7.10 (2.7-9.9)	8.6	1980 (630-3100)	3.59
	16 + 42	1.60	4.20	-	-	-	5.80 (1.9-6.9)	7.2	1650 (270-2480)	3.52	2.26	5.94	-	-	-	8.20 (2.7-9.9)	10.4	2410 (630-3100)	3.40
	16 + 50	1.60	5.00	-	-	-	6.60 (2.0-7.5)	8.1	1860 (280-2560)	3.55	2.06	6.44	-	-	-	8.50 (2.8-10.2)	10.1	2340 (560-3070)	3.63
	16 + 60	1.49	5.61	-	-	-	7.10 (2.0-7.5)	9.8	2260 (280-2560)	3.14	1.79	6.71	-	-	-	8.50 (2.8-10.2)	10.1	2340 (560-3070)	3.63
	20 + 20	2.00	2.00	-	-	-	4.00 (1.9-6.4)	3.8	840 (270-2080)	4.76	3.20	3.20	-	-	-	6.40 (2.7-9.8)	7.6	1750 (640-3100)	3.66
	20 + 25	2.00	2.50	-	-	-	4.50 (1.9-6.4)	4.6	1020 (270-2080)	4.41	3.02	3.78	-	-	-	6.80 (2.7-9.8)	8.1	1880 (640-3100)	3.62
	20 + 35	2.00	3.50	-	-	-	5.50 (1.9-6.9)	6.4	1470 (270-2480)	3.74	2.80	4.90	-	-	-	7.70 (2.7-9.9)	9.5	2190 (630-3100)	3.52
	20 + 42	2.00	4.20	-	-	-	6.20 (1.9-6.9)	8.2	1890 (270-2440)	3.28	2.74	5.76	-	-	-	8.50 (2.7-9.9)	10.9	2520 (620-3110)	3.37
	20 + 50	2.00	5.00	-	-	-	7.00 (2.0-7.5)	9.2	2120 (280-2520)	3.30	2.43	6.07	-	-	-	8.50 (2.8-10.2)	10.1	2340 (560-3070)	3.63
	20 + 60	1.78	5.32	-	-	-	7.10 (2.0-7.5)	9.6	2210 (280-2520)	3.21	2.12	6.38	-	-	-	8.50 (2.8-10.2)	10.1	2340 (560-3070)	3.63
	25 + 25	2.50	2.50	-	-	-	5.00 (1.9-6.8)	5.5	1250 (270-2470)	4.00	3.60	3.60	-	-	-	7.20 (2.7-9.8)	8.8	2020 (640-3100)	3.56
	25 + 35	2.50	3.50	-	-	-	6.00 (1.9-6.9)	7.7	1770 (270-2480)	3.39	3.37	4.73	-	-	-	8.10 (2.7-9.9)	10.1	2330 (630-3100)	3.48
	25 + 42	2.50	4.20	-	-	-	6.70 (1.9-6.9)	10.1	2320 (270-2440)	2.89	3.17	5.33	-	-	-	8.50 (2.7-9.9)	10.9	2520 (620-3110)	3.37
	25 + 50	2.37	4.73	-	-	-	7.10 (1.9-7.5)	9.6	2210 (260-2520)	3.21	2.83	5.67	-	-	-	8.50 (2.8-10.2)	10.1	2340 (560-3070)	3.63
	25 + 60	2.09	5.01	-	-	-	7.10 (1.9-7.5)	9.6	2210 (260-2520)	3.21	2.50	6.00	-	-	-	8.50 (2.8-10.2)	10.1	2340 (560-3070)	3.63
	35 + 35	3.50	3.50	-	-	-	7.00 (1.9-7.1)	10.9	2510 (270-2580)	2.79	4.25	4.25	-	-	-	8.50 (2.8-10.0)	10.7	2470 (640-3100)	3.44
	35 + 42	3.23	3.87	-	-	-	7.10 (1.9-7.2)	11.3	2610 (270-2630)	2.72	3.86	4.64	-	-	-	8.50 (2.8-10.0)	10.7	2470 (640-3100)	3.44
	35 + 50	2.92	4.18	-	-	-	7.10 (2.0-7.6)	9.2	2130 (280-2520)	3.33	3.50	5.00	-	-	-	8.50 (2.8-10.3)	9.9</		

CU-4Z71VBR: Only Wall-Mounted Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	Total
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
4 rooms	16 + 16 + 16 + 16	1.60	1.60	1.60	1.60	-	6.40 [1.9-8.7]	6.2	1390 [340-2370]	4.60	2.12	2.12	2.12	2.12	-	8.48 [3.0-10.7]	8.7	1960 [500-2770]	4.33
	16 + 16 + 16 + 20	1.67	1.67	1.67	2.09	-	7.10 [1.9-8.8]	7.4	1660 [340-2470]	4.28	2.00	2.00	2.00	2.50	-	8.50 [3.0-10.7]	8.6	1950 [500-2720]	4.36
	16 + 16 + 16 + 25	1.56	1.56	1.56	2.42	-	7.10 [1.9-8.8]	7.4	1660 [340-2470]	4.28	1.86	1.86	1.86	2.92	-	8.50 [3.0-10.7]	8.6	1950 [500-2720]	4.36
	16 + 16 + 16 + 35	1.37	1.37	1.37	2.99	-	7.10 [1.9-8.8]	7.4	1660 [340-2380]	4.28	1.64	1.64	1.64	3.58	-	8.50 [3.0-10.7]	8.5	1930 [500-2700]	4.40
	16 + 16 + 16 + 42	1.26	1.26	1.26	3.32	-	7.10 [1.9-8.8]	7.4	1660 [340-2380]	4.28	1.51	1.51	1.51	3.97	-	8.50 [3.0-10.7]	8.5	1930 [500-2690]	4.40
	16 + 16 + 16 + 50	1.16	1.16	1.16	3.62	-	7.10 [1.9-8.8]	7.1	1580 [400-2240]	4.49	1.39	1.39	1.39	4.33	-	8.50 [3.0-10.7]	8.4	1890 [560-2590]	4.50
	16 + 16 + 16 + 60	1.05	1.05	1.05	3.95	-	7.10 [1.9-8.8]	7.1	1580 [400-2240]	4.49	1.26	1.26	1.26	4.72	-	8.50 [3.0-10.7]	8.4	1890 [560-2590]	4.50
	16 + 16 + 20 + 20	1.58	1.58	1.97	1.97	-	7.10 [1.9-8.8]	7.4	1660 [340-2420]	4.28	1.89	1.89	2.36	2.36	-	8.50 [3.1-10.7]	8.6	1950 [520-2710]	4.36
	16 + 16 + 20 + 25	1.48	1.48	1.84	2.30	-	7.10 [1.9-8.8]	7.4	1660 [340-2420]	4.28	1.77	1.77	2.20	2.76	-	8.50 [3.1-10.7]	8.6	1950 [520-2710]	4.36
	16 + 16 + 20 + 35	1.31	1.31	1.63	2.85	-	7.10 [1.9-8.8]	7.4	1660 [340-2380]	4.28	1.56	1.56	1.95	3.43	-	8.50 [3.0-10.7]	8.5	1930 [500-2690]	4.40
	16 + 16 + 20 + 42	1.21	1.21	1.51	3.17	-	7.10 [1.9-8.8]	7.2	1620 [370-2380]	4.38	1.45	1.45	1.80	3.80	-	8.50 [3.0-10.7]	8.5	1920 [520-2680]	4.43
	16 + 16 + 20 + 50	1.11	1.11	1.39	3.49	-	7.10 [1.9-8.8]	7.1	1580 [400-2200]	4.49	1.33	1.33	1.67	4.17	-	8.50 [3.0-10.7]	8.3	1880 [570-2580]	4.52
	16 + 16 + 20 + 60	1.01	1.01	1.27	3.81	-	7.10 [1.9-8.8]	7.1	1580 [400-2200]	4.49	1.21	1.21	1.52	4.56	-	8.50 [3.0-10.7]	8.3	1880 [570-2580]	4.52
	16 + 16 + 25 + 25	1.39	1.39	2.16	2.16	-	7.10 [1.9-8.8]	7.4	1660 [340-2420]	4.28	1.66	1.66	2.59	2.59	-	8.50 [3.1-10.7]	8.6	1950 [520-2710]	4.36
	16 + 16 + 25 + 35	1.23	1.23	1.93	2.71	-	7.10 [1.9-8.8]	7.4	1660 [340-2380]	4.28	1.48	1.48	2.31	3.23	-	8.50 [3.0-10.7]	8.5	1930 [500-2690]	4.40
	16 + 16 + 25 + 42	1.15	1.15	1.79	3.01	-	7.10 [1.9-8.8]	7.2	1620 [370-2380]	4.38	1.37	1.37	2.15	3.61	-	8.50 [3.0-10.7]	8.5	1920 [520-2680]	4.43
	16 + 16 + 25 + 50	1.06	1.06	1.66	3.32	-	7.10 [1.9-8.8]	7.1	1580 [400-2200]										

CU-4Z71VBR: Free Multi Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION								HEATING OPERATION									
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	Total
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
2 rooms	16 + 16	1.60	1.60	-	-	-	3.20 (1.9-6.4)	3.1	660 (270-2220)	4.85	2.60	2.60	-	-	-	5.20 (2.7-9.8)	6.6	1500 (660-3210)	3.47
	16 + 20	1.60	2.00	-	-	-	3.60 (1.9-6.4)	3.6	790 (270-2180)	4.56	2.58	3.22	-	-	-	5.80 (2.7-9.8)	7.4	1680 (650-3220)	3.45
	16 + 25	1.60	2.50	-	-	-	4.10 (1.9-6.4)	4.2	930 (270-2180)	4.41	2.42	3.78	-	-	-	6.20 (2.7-9.8)	7.8	1810 (650-3220)	3.43
	16 + 35	1.60	3.50	-	-	-	5.10 (1.9-6.9)	5.9	1350 (270-2580)	3.78	2.23	4.87	-	-	-	7.10 (2.7-9.9)	9.1	2100 (630-3220)	3.38
	16 + 42	1.60	4.20	-	-	-	5.80 (1.9-6.9)	7.5	1710 (270-2540)	3.39	2.26	5.94	-	-	-	8.20 (2.7-9.9)	11.0	2530 (630-3220)	3.24
	16 + 50	1.60	5.00	-	-	-	6.60 (2.0-7.5)	8.3	1920 (280-2620)	3.44	2.06	6.44	-	-	-	8.50 (2.8-10.2)	10.7	2460 (560-3190)	3.46
	16 + 60	1.49	5.61	-	-	-	7.10 (2.0-7.5)	10.1	2320 (280-2620)	3.06	1.79	6.71	-	-	-	8.50 (2.8-10.2)	10.7	2460 (560-3190)	3.46
	20 + 20	2.00	2.00	-	-	-	4.00 (1.9-6.4)	4.1	900 (270-2140)	4.44	3.20	3.20	-	-	-	6.40 (2.7-9.8)	8.1	1870 (640-3220)	3.42
	20 + 25	2.00	2.50	-	-	-	4.50 (1.9-6.4)	4.8	1080 (270-2140)	4.17	3.02	3.78	-	-	-	6.80 (2.7-9.8)	8.7	2000 (640-3220)	3.40
	20 + 35	2.00	3.50	-	-	-	5.50 (1.9-6.9)	6.7	1530 (270-2540)	3.59	2.80	4.90	-	-	-	7.70 (2.7-9.9)	10.0	2310 (630-3220)	3.33
	20 + 42	2.00	4.20	-	-	-	6.20 (1.9-6.9)	8.5	1950 (270-2500)	3.18	2.74	5.76	-	-	-	8.50 (2.7-9.9)	11.4	2640 (620-3230)	3.22
	20 + 50	2.00	5.00	-	-	-	7.00 (2.0-7.5)	9.5	2180 (280-2580)	3.21	2.43	6.07	-	-	-	8.50 (2.8-10.2)	10.7	2460 (560-3190)	3.46
	20 + 60	1.78	5.32	-	-	-	7.10 (2.0-7.5)	9.8	2270 (280-2580)	3.13	2.12	6.38	-	-	-	8.50 (2.8-10.2)	10.7	2460 (560-3190)	3.46
	25 + 25	2.50	2.50	-	-	-	5.00 (1.9-6.8)	5.7	1310 (270-2530)	3.82	3.60	3.60	-	-	-	7.20 (2.7-9.8)	9.3	2140 (640-3220)	3.36
	25 + 35	2.50	3.50	-	-	-	6.00 (1.9-6.9)	7.9	1830 (270-2540)	3.28	3.37	4.73	-	-	-	8.10 (2.7-9.9)	10.6	2450 (630-3220)	3.31
	25 + 42	2.50	4.20	-	-	-	6.70 (1.9-6.9)	10.3	2380 (270-2500)										

CU-4Z71VBR: Free Multi Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	Total
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
4 rooms	16 + 16 + 16 + 16	1.60	1.60	1.60	1.60	-	6.40 [1.9-8.7]	6.7	1510 [340-2490]	4.24	2.12	2.12	2.12	2.12	-	8.48 [3.0-10.7]	9.7	2200 [500-3010]	3.85
	16 + 16 + 16 + 20	1.67	1.67	1.67	2.09	-	7.10 [1.9-8.8]	7.9	1780 [340-2590]	3.99	2.00	2.00	2.00	2.50	-	8.50 [3.0-10.7]	9.7	2190 [500-2960]	3.88
	16 + 16 + 16 + 25	1.56	1.56	1.56	2.42	-	7.10 [1.9-8.8]	7.9	1780 [340-2590]	3.99	1.86	1.86	1.86	2.92	-	8.50 [3.0-10.7]	9.7	2190 [500-2960]	3.88
	16 + 16 + 16 + 35	1.37	1.37	1.37	2.99	-	7.10 [1.9-8.8]	7.9	1780 [340-2500]	3.99	1.64	1.64	1.64	3.58	-	8.50 [3.0-10.7]	9.6	2170 [500-2940]	3.92
	16 + 16 + 16 + 42	1.26	1.26	1.26	3.32	-	7.10 [1.9-8.8]	7.9	1780 [340-2500]	3.99	1.51	1.51	1.51	3.97	-	8.50 [3.0-10.7]	9.6	2170 [500-2930]	3.92
	16 + 16 + 16 + 50	1.16	1.16	1.16	3.62	-	7.10 [1.9-8.8]	7.6	1700 [400-2360]	4.18	1.39	1.39	1.39	4.33	-	8.50 [3.0-10.7]	9.4	2130 [560-2830]	3.99
	16 + 16 + 16 + 60	1.05	1.05	1.05	3.95	-	7.10 [1.9-8.8]	7.6	1700 [400-2360]	4.18	1.26	1.26	1.26	4.72	-	8.50 [3.0-10.7]	9.4	2130 [560-2830]	3.99
	16 + 16 + 20 + 20	1.58	1.58	1.97	1.97	-	7.10 [1.9-8.8]	7.9	1780 [340-2540]	3.99	1.89	1.89	2.36	2.36	-	8.50 [3.1-10.7]	9.7	2190 [520-2950]	3.88
	16 + 16 + 20 + 25	1.48	1.48	1.84	2.30	-	7.10 [1.9-8.8]	7.9	1780 [340-2540]	3.99	1.77	1.77	2.20	2.76	-	8.50 [3.1-10.7]	9.7	2190 [520-2950]	3.88
	16 + 16 + 20 + 35	1.31	1.31	1.63	2.85	-	7.10 [1.9-8.8]	7.9	1780 [340-2500]	3.99	1.56	1.56	1.95	3.43	-	8.50 [3.0-10.7]	9.6	2170 [500-2930]	3.92
	16 + 16 + 20 + 42	1.21	1.21	1.51	3.17	-	7.10 [1.9-8.8]	7.8	1740 [370-2500]	4.08	1.45	1.45	1.80	3.80	-	8.50 [3.0-10.7]	9.5	2160 [520-2920]	3.94
	16 + 16 + 20 + 50	1.11	1.11	1.39	3.49	-	7.10 [1.9-8.8]	7.6	1700 [400-2320]	4.18	1.33	1.33	1.67	4.17	-	8.50 [3.0-10.7]	9.4	2120 [570-2820]	4.01
	16 + 16 + 20 + 60	1.01	1.01	1.27	3.81	-	7.10 [1.9-8.8]	7.6	1700 [400-2320]	4.18	1.21	1.21	1.52	4.56	-	8.50 [3.0-10.7]	9.4	2120 [570-2820]	4.01
	16 + 16 + 25 + 25	1.39	1.39	2.16	2.16	-	7.10 [1.9-8.8]	7.9	1780 [340-2540]	3.99	1.66	1.66	2.59	2.59	-	8.50 [3.1-10.7]	9.7	2190 [520-2950]	3.88
	16 + 16 + 25 + 35	1.23	1.23	1.93	2.71	-	7.10 [1.9-8.8]	7.9	1780 [340-2500]	3.99	1.48	1.48	2.31	3.23	-	8.50 [3.0-10.7]	9.6	2170 [500-2930]	3.92
	16 + 16 + 25 + 42	1.15	1.15	1.79	3.01	-	7.10 [1.9-8.8]	7.8	1740 [370-2500]	4.08	1.37	1.37	2.15	3.61	-	8.50 [3.0-10.7]	9.5	2160 [520-2920]	3.94
	16 + 16 + 25 + 50	1.06	1.06	1.66	3.32	-	7.10 [1.9-8.8]	7.6	1700 [400-23										

CU-4Z80VBR: Only Wall-Mounted Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	Total
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
2 rooms	16+16	1.60	1.60	-	-	-	3.20 [2.3-5.8]	3.7	770 [350-2030]	4.16	2.60	2.60	-	-	-	5.20 [2.2-8.2]	7.5	1640 [430-2920]	3.17
	16+20	1.60	2.00	-	-	-	3.60 [2.3-5.8]	4.3	910 [340-2030]	3.96	2.58	3.22	-	-	-	5.80 [2.2-8.2]	7.9	1760 [430-2910]	3.30
	16+25	1.60	2.50	-	-	-	4.10 [2.3-5.8]	5.2	1110 [340-2030]	3.69	2.42	3.78	-	-	-	6.20 [2.2-8.2]	8.6	1900 [430-2910]	3.26
	16+35	1.60	3.50	-	-	-	5.10 [2.3-5.8]	7.0	1520 [340-1960]	3.36	2.23	4.87	-	-	-	7.10 [2.2-8.6]	9.3	2070 [380-2990]	3.43
	16+42	1.60	4.20	-	-	-	5.80 [2.3-6.7]	8.5	1860 [340-2520]	3.12	2.26	5.94	-	-	-	8.20 [2.2-9.8]	11.0	2450 [370-3520]	3.35
	16+50	1.60	5.00	-	-	-	6.60 [2.3-7.2]	9.6	2100 [320-2520]	3.14	2.28	7.12	-	-	-	9.40 [2.2-10.0]	11.4	2540 [330-3330]	3.70
	16+60	1.60	6.00	-	-	-	7.60 [2.3-8.5]	12.5	2730 [320-3530]	2.78	1.98	7.42	-	-	-	9.40 [2.2-10.0]	11.4	2540 [330-3330]	3.70
	16+71	1.47	6.53	-	-	-	8.00 [2.3-8.5]	13.2	2880 [320-3380]	2.78	1.73	7.67	-	-	-	9.40 [2.2-10.3]	11.2	2480 [320-3500]	3.79
	20+20	2.00	2.00	-	-	-	4.00 [2.3-5.8]	4.9	1050 [340-1970]	3.81	3.20	3.20	-	-	-	6.40 [2.2-8.2]	8.7	1940 [390-2900]	3.30
	20+25	2.00	2.50	-	-	-	4.50 [2.3-5.8]	5.9	1280 [340-1970]	3.52	3.02	3.78	-	-	-	6.80 [2.2-8.2]	9.0	2000 [390-2900]	3.40
	20+35	2.00	3.50	-	-	-	5.50 [2.3-5.8]	7.8	1690 [340-1900]	3.25	2.80	4.90	-	-	-	7.70 [2.2-8.6]	10.1	2250 [370-2930]	3.42
	20+42	2.00	4.20	-	-	-	6.20 [2.3-7.2]	9.7	2110 [340-2940]	2.94	2.84	5.96	-	-	-	8.80 [2.2-10.0]	11.3	2500 [370-3630]	3.52
	20+50	2.00	5.00	-	-	-	7.00 [2.3-8.1]	10.3	2250 [320-3140]	3.11	2.69	6.71	-	-	-	9.40 [2.2-10.0]	11.4	2530 [320-3310]	3.72
	20+60	2.00	6.00	-	-	-	8.00 [2.3-8.5]	13.5	2950 [320-3530]	2.71	2.35	7.05	-	-	-	9.40 [2.2-10.0]	11.4	2530 [320-3310]	3.72
	20+71	1.76	6.24	-	-	-	8.00 [2.3-8.5]	12.9	2810 [350-3380]	2.85	2.07	7.33	-	-	-	9.40 [2.2-10.3]	11.1	2470 [320-3480]	3.81
	25+25	2.50	2.50	-	-	-	5.00 [2.3-5.8]	6.8	1470 [340-1970]	3.40	3.60	3.60	-	-	-	7.20 [2.2-8.6]	9.6	2130 [390-3010]	3.38
	25+35	2.50	3.50	-	-	-	6.00 [2.3-6.7]	9.1	1980 [340-2520]	3.03	3.37	4.73	-	-	-	8.10 [2.2-9.8]	10.8	2400 [370-3520]	3.38
	25+42	2.50	4.20	-	-	-	6.70 [2.3-7.2]	11.2	2450 [340-2940]	2.73	3.43	5.77	-	-	-	9.20 [2.2-10.0]	11.9	2650 [370-3630]	3.47
	25+50	2.50	5.00	-	-	-	7.50 [2.3-8.5]	11.9	2590 [320-3530]	2.90	3.13	6.27	-	-	-	9.40 [2.2-10.0]	11.4	2530 [320-3310]	3.72
	25+60	2.35	5.65	-	-	-	8.00 [2.3-8.5]	13.5	2950 [320-3530]	2.71	2.76	6.64	-	-	-	9.40 [2.2-10.0]	11.4	2530 [320-3310]	3.72
	25+71	2.08	5.92	-	-	-	8.00 [2.3-8.5]	12.9	2810 [350-3380]	2.85	2.45	6.95	-	-	-	9.40 [2.2-10.3]	11.1	2470 [320-3480]	3.81
	35+35	3.50	3.50	-	-	-	7.00 [2.3-8.1]	11.9	2590 [330-3670]	2.70	4.50	4.50	-	-	-	9.00 [2.2-10.0]	11.4	2530 [360-3550]	3.56
	35+42	3.50	4.20	-	-	-	7.70 [												

CU-4Z80VBR: Only Wall-Mounted Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
3 rooms	16+25+35	1.60	2.50	3.50	-	-	7.60 [2.3-8.5]	10.3	2250 [340-3010]	3.38	1.98	3.09	4.33	-	-	9.40 [3.0-10.4]	10.6	2360 [430-3330]	3.98
	16+25+42	1.54	2.41	4.05	-	-	8.00 [2.3-8.6]	10.8	2350 [340-3090]	3.40	1.81	2.83	4.76	-	-	9.40 [3.0-10.4]	10.6	2350 [430-3320]	4.00
	16+25+50	1.41	2.20	4.39	-	-	8.00 [2.3-8.6]	9.9	2160 [380-2790]	3.70	1.65	2.58	5.17	-	-	9.40 [3.0-10.5]	10.1	2240 [460-3170]	4.20
	16+25+60	1.27	1.98	4.75	-	-	8.00 [2.3-8.8]	9.9	2160 [380-2860]	3.70	1.49	2.33	5.58	-	-	9.40 [3.0-10.5]	10.1	2240 [460-3170]	4.20
	16+25+71	1.14	1.79	5.07	-	-	8.00 [2.3-8.8]	9.6	2100 [380-2860]	3.81	1.34	2.10	5.96	-	-	9.40 [3.0-10.6]	10.0	2230 [460-3210]	4.22
	16+35+35	1.48	3.26	3.26	-	-	8.00 [2.3-8.6]	10.5	2290 [340-3010]	3.49	1.74	3.83	3.83	-	-	9.40 [3.0-10.5]	10.5	2330 [460-3360]	4.03
	16+35+42	1.38	3.01	3.61	-	-	8.00 [2.3-8.6]	10.5	2290 [340-3010]	3.49	1.62	3.54	4.24	-	-	9.40 [3.0-10.5]	10.4	2320 [460-3280]	4.05
	16+35+50	1.27	2.77	3.96	-	-	8.00 [2.3-8.8]	9.6	2100 [380-2860]	3.81	1.49	3.26	4.65	-	-	9.40 [3.0-10.5]	10.0	2210 [490-3130]	4.25
	16+35+60	1.15	2.52	4.33	-	-	8.00 [2.3-8.8]	9.6	2100 [380-2860]	3.81	1.35	2.96	5.09	-	-	9.40 [3.0-10.6]	10.0	2210 [490-3190]	4.25
	16+35+71	1.05	2.30	4.65	-	-	8.00 [2.3-9.0]	9.6	2100 [380-2930]	3.81	1.23	2.70	5.47	-	-	9.40 [3.0-10.6]	9.9	2200 [490-3180]	4.27
	16+42+42	1.28	3.36	3.36	-	-	8.00 [2.3-8.8]	10.5	2290 [340-3160]	3.49	1.50	3.95	3.95	-	-	9.40 [3.0-10.5]	10.4	2310 [460-3270]	4.07
	16+42+50	1.19	3.11	3.70	-	-	8.00 [2.3-8.8]	9.6	2100 [380-2860]	3.81	1.39	3.66	4.35	-	-	9.40 [3.0-10.5]	10.0	2210 [490-3120]	4.25
	16+42+60	1.08	2.85	4.07	-	-	8.00 [2.3-9.0]	9.6	2100 [380-2930]	3.81	1.27	3.35	4.78	-	-	9.40 [3.0-10.6]	10.0	2210 [490-3180]	4.25
	16+42+71	0.99	2.60	4.41	-	-	8.00 [2.3-9.0]	9.4	2040 [380-2860]	3.92	1.17	3.06	5.17	-	-	9.40 [3.0-10.6]	9.9	2190 [490-3160]	4.29
	16+50+50	1.10	3.45	3.45	-	-	8.00 [2.3-8.8]	9.1	1980 [430-2640]	4.04	1.30	4.05	4.05	-	-	9.40 [3.0-10.6]	9.5	2120 [550-3050]	4.43
	16+50+60	1.02	3.17	3.81	-	-	8.00 [2.3-9.0]	9.1	1980 [430-2710]	4.04	1.19	3.73	4.48	-	-	9.40 [3.0-10.6]	9.5	2120 [550-3050]	4.43
	16+50+71	0.93	2.92	4.15	-	-	8.00 [2.3-9.0]	9.1	1980 [470-2710]	4.04	1.10	3.43	4.87	-	-	9.40 [3.0-10.6]	9.5	2110 [550-3040]	4.45
	16+60+60	0.94	3.53	3.53	-	-	8.00 [2.3-9.0]	9.1	1980 [430-2710]	4.04	1.10	4.15	4.15	-	-	9.40 [3.0-10.6]	9.5	2120 [550-3050]	4.43
	16+60+71	0.87	3.27	3.86	-	-	8.00 [2.3-9.0]	9.1	1980 [470-2710]	4.04	1.02	3.84	4.54	-	-	9.40 [3.0-10.6]	9.5	2110 [550-3040]	4.

CU-4Z80VBR: Only Wall-Mounted Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
3 rooms	25+35+42	1.96	2.75	3.29	-	-	8.00 [2.3-8.8]	10.5	2290 [340-3160]	3.49	2.30	3.23	3.87	-	-	9.40 [3.0-10.5]	10.4	2310 [460-3270]	4.07
	25+35+50	1.82	2.55	3.63	-	-	8.00 [2.3-8.8]	9.6	2100 [380-2860]	3.81	2.14	2.99	4.27	-	-	9.40 [3.0-10.5]	10.0	2210 [490-3120]	4.25
	25+35+60	1.67	2.33	4.00	-	-	8.00 [2.3-9.0]	9.6	2100 [380-2930]	3.81	1.96	2.74	4.70	-	-	9.40 [3.0-10.6]	10.0	2210 [490-3180]	4.25
	25+35+71	1.53	2.14	4.33	-	-	8.00 [2.3-9.0]	9.4	2040 [380-2860]	3.92	1.79	2.51	5.10	-	-	9.40 [3.0-10.6]	9.9	2190 [490-3160]	4.29
	25+42+42	1.84	3.08	3.08	-	-	8.00 [2.3-8.8]	10.5	2290 [340-3090]	3.49	2.16	3.62	3.62	-	-	9.40 [3.0-10.5]	10.4	2300 [460-3260]	4.09
	25+42+50	1.71	2.87	3.42	-	-	8.00 [2.3-8.8]	9.6	2100 [380-2780]	3.81	2.01	3.37	4.02	-	-	9.40 [3.0-10.6]	9.9	2200 [490-3170]	4.27
	25+42+60	1.57	2.65	3.78	-	-	8.00 [2.3-9.0]	9.6	2100 [380-2930]	3.81	1.85	3.11	4.44	-	-	9.40 [3.0-10.6]	9.9	2200 [490-3170]	4.27
	25+42+71	1.45	2.43	4.12	-	-	8.00 [2.3-9.0]	9.4	2040 [380-2860]	3.92	1.70	2.86	4.84	-	-	9.40 [3.0-10.6]	9.9	2190 [490-3150]	4.29
	25+50+50	1.60	3.20	3.20	-	-	8.00 [2.3-9.0]	9.1	1980 [430-2710]	4.04	1.88	3.76	3.76	-	-	9.40 [3.0-10.6]	9.5	2110 [550-3040]	4.45
	25+50+60	1.48	2.96	3.56	-	-	8.00 [2.3-9.0]	9.1	1980 [430-2710]	4.04	1.74	3.48	4.18	-	-	9.40 [3.0-10.6]	9.5	2110 [550-3040]	4.45
	25+50+71	1.37	2.74	3.89	-	-	8.00 [2.3-9.0]	9.1	1980 [470-2710]	4.04	1.61	3.22	4.57	-	-	9.40 [3.0-10.6]	9.5	2100 [580-3030]	4.48
	25+60+60	1.38	3.31	3.31	-	-	8.00 [2.3-9.0]	9.1	1980 [430-2710]	4.04	1.62	3.89	3.89	-	-	9.40 [3.0-10.6]	9.5	2110 [550-3040]	4.45
	35+35+35	2.66	2.66	2.66	-	-	7.98 [2.3-8.8]	10.2	2230 [340-3090]	3.58	3.13	3.13	3.13	-	-	9.39 [3.0-10.5]	10.4	2300 [460-3250]	4.08
	35+35+42	2.50	2.50	3.00	-	-	8.00 [2.3-8.8]	10.2	2230 [340-3090]	3.59	2.94	2.94	3.52	-	-	9.40 [3.0-10.6]	10.3	2290 [460-3290]	4.10
	35+35+50	2.33	2.33	3.33	-	-	7.99 [2.3-9.0]	9.4	2040 [380-2930]	3.92	2.74	2.74	3.92	-	-	9.40 [3.0-10.6]	9.8	2180 [490-3150]	4.31
	35+35+60	2.15	2.15	3.70	-	-	8.00 [2.3-9.0]	9.4	2040 [380-2930]	3.92	2.53	2.53	4.34	-	-	9.40 [3.0-10.6]	9.8	2180 [490-3150]	4.31
	35+35+71	1.99	1.99	4.02	-	-	8.00 [2.3-9.0]	9.4	2040 [420-2860]	3.92	2.33	2.33	4.74	-	-	9.40 [3.0-10.6]	9.8	2170 [500-3130]	4.33
	35+42+42	2.36	2.82	2.82	-	-	8.00 [2.3-9.0]	10.2	2230 [340-3160]	3.59	2.76	3.32	3.32	-	-	9.40 [3.0-10.6]	10.3	2280 [460-3280]	4.12
	35+42+50	2.20	2.65	3.15	-	-	8.00 [2.3-9.0]	9.4	2040 [380-2860]	3.92	2.59	3.11	3.70	-	-	9.40 [3.0-10.6]	9.8	2170 [500-3140]	4.33
	35+42+60	2.04	2.45	3.51	-	-	8.00 [2.3-9.0]	9.4	2040 [380-2860]	3.92	2.40	2.88	4.12	-	-	9.40 [3.0-10.6]	9.8	2170 [500-3140]	4.33
35+50+50	2.08	2.96	2.96	-	-	8.00 [2.3-9.0]	9.1	1980 [470-2710]	4.04	2.44	3.48	3.48	-	-	9.40 [3.0-10.6]	9.4	2090 [580-3010]	4.50	
35+50+60	1.93	2.76	3.31	-	-	8.00 [2.3-9.0]	9.1	1980 [470-2710]	4.04	2.27	3.24	3.89	-	-	9.40 [3.0-10.6]	9.4	2090 [580-3010]	4.50	
42+42+42	2.66	2.66	2.66	-	-	7.98 [2.3-9.0]	10.2	2230 [340-3160]	3.58	3.13	3.13	3.13	-	-	9.39 [3.0-10.6]	10.2	2270 [460-3270]	4.14	
42+42+50	2.51	2.51	2.98	-	-	8.00 [2.3-9.0]	9.4	2040 [380-2860]	3.92	2.95	2.95	3.50	-	-	9.40 [3.0-10.6]	9.8	2170 [500-3120]	4.33	
42+42+60	2.33	2.33	3.33	-	-	7.99 [2.3-9.0]	9.4	2040 [380-2860]	3.92	2.74	2.74	3.92	-	-	9.40 [3.0-10.6]	9.8	2170 [500-3120]	4.33	
42+50+50	2.36	2.82	2.82	-	-	8.00 [2.3-9.0]	9.1	1980 [470-2710]	4.04	2.78	3.31	3.31	-	-	9.40 [3.0-10.6]	9.4	2090 [590-3000]	4.50	
4 rooms	16+16+16+16	1.60	1.60	1.60	1.60	-	6.40 [2.3-9.2]	6.8	1490 [420-2940]	4.30	2.35	2.35	2.35	2.35	-	9.40 [3.0-11.6]	9.5	2060 [490-3470]	4.56
	16+16+16+20	1.60	1.60	1.60	2.00	-	6.80 [2.3-9.2]	7.3	1600 [420-2870]	4.25	2.21	2.21	2.21	2.77	-	9.40 [3.0-11.6]	9.4	2050 [500-3460]	4.59
	16+16+16+25	1.60	1.60	1.60	2.50	-	7.30 [2.3-9.2]	7.9	1760 [420-2870]	4.15	2.06	2.06	2.06	3.22	-	9.40 [3.0-11.6]	9.4	2050 [500-3460]	4.59
	16+16+16+35	1.54	1.54	1.54	3.38	-	8.00 [2.3-9.2]	8.9	1980 [420-2870]	4.04	1.81	1.81	1.81	3.97	-	9.40 [3.0-11.6]	9.3	2030 [500-3420]	4.63
	16+16+16+42	1.42	1.42	1.42	3.74	-	8.00 [2.3-9.2]	8.9	1980 [420-2870]	4.04	1.67	1.67	1.67	4.39	-	9.40 [3.0-11.6]	9.3	2020 [510-3410]	4.65
	16+16+16+50	1.31	1.31																

CU-4Z80VBR: Only Wall-Mounted Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION									
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP			
		Room A	Room B	Room C	Room D	Room E				Room A	Room B	Room C	Room D	Room E						
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	W	W/W			
4 rooms	16+16+42+50	1.03	1.03	2.71	3.23	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.21	1.21	3.18	3.80	-	9.40 [3.0-11.6]	9.0	1970 [650-3290]	4.77	
	16+16+42+60	0.96	0.96	2.51	3.57	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.12	1.12	2.95	4.21	-	9.40 [3.0-11.6]	9.0	1970 [650-3290]	4.77	
	16+16+42+71	0.88	0.88	2.32	3.92	-	8.00 [2.3-9.2]	8.5	1880 [530-2660]	4.26	1.04	1.04	2.72	4.60	-	9.40 [3.0-11.6]	9.0	1970 [670-3280]	4.77	
	16+16+50+50	0.97	0.97	3.03	3.03	-	8.00 [2.3-9.2]	8.5	1890 [580-2600]	4.23	1.14	1.14	3.56	3.56	-	9.40 [3.0-11.6]	9.2	2010 [780-3300]	4.68	
	16+16+50+60	0.90	0.90	2.82	3.38	-	8.00 [2.3-9.2]	8.5	1890 [580-2600]	4.23	1.06	1.06	3.31	3.97	-	9.40 [3.0-11.6]	9.2	2010 [780-3300]	4.68	
	16+20+20+20	1.60	2.00	2.00	2.00	-	7.60 [2.3-9.2]	8.4	1870 [420-2870]	4.06	1.99	2.47	2.47	2.47	-	9.40 [3.0-11.6]	9.4	2040 [500-3430]	4.61	
	16+20+20+25	1.58	1.98	1.98	2.46	-	8.00 [2.3-9.2]	8.9	1980 [420-2870]	4.04	1.86	2.32	2.32	2.90	-	9.40 [3.0-11.6]	9.4	2040 [500-3430]	4.61	
	16+20+20+35	1.41	1.76	1.76	3.07	-	8.00 [2.3-9.2]	8.7	1930 [420-2800]	4.15	1.65	2.07	2.07	3.61	-	9.40 [3.0-11.6]	9.3	2020 [530-3400]	4.65	
	16+20+20+42	1.31	1.63	1.63	3.43	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.53	1.92	1.92	4.03	-	9.40 [3.0-11.6]	9.2	2010 [530-3380]	4.68	
	16+20+20+50	1.21	1.51	1.51	3.77	-	8.00 [2.3-9.2]	8.5	1880 [480-2660]	4.26	1.42	1.77	1.77	4.44	-	9.40 [3.0-11.6]	9.1	1990 [630-3320]	4.72	
	16+20+20+60	1.10	1.38	1.38	4.14	-	8.00 [2.3-9.2]	8.5	1880 [480-2660]	4.26	1.30	1.62	1.62	4.86	-	9.40 [3.0-11.6]	9.1	1990 [630-3320]	4.72	
	16+20+20+71	1.01	1.26	1.26	4.47	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.18	1.48	1.48	5.26	-	9.40 [3.0-11.6]	9.1	1980 [640-3300]	4.75	
	16+20+25+25	1.48	1.86	2.33	2.33	-	8.00 [2.3-9.2]	8.9	1980 [420-2870]	4.04	1.75	2.19	2.73	2.73	-	9.40 [3.0-11.6]	9.4	2040 [500-3430]	4.61	
	16+20+25+35	1.33	1.67	2.08	2.92	-	8.00 [2.3-9.2]	8.7	1930 [420-2800]	4.15	1.57	1.96	2.45	3.42	-	9.40 [3.0-11.6]	9.3	2020 [530-3400]	4.65	
	16+20+25+42	1.24	1.55	1.94	3.27	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.46	1.83	2.28	3.83	-	9.40 [3.0-11.6]	9.2	2010 [530-3380]	4.68	
	16+20+25+50	1.15	1.44	1.80	3.61	-	8.00 [2.3-9.2]	8.5	1880 [480-2660]	4.26	1.35	1.69	2.12	4.24	-	9.40 [3.0-11.6]	9.1	1990 [630-3320]	4.72	
	16+20+25+60	1.06	1.32	1.65	3.97	-	8.00 [2.3-9.2]	8.5	1880 [480-2660]	4.26	1.24	1.55	1.94	4.67	-	9.40 [3.0-11.6]	9.1	1990 [630-3320]	4.72	
	16+20+25+71	0.97	1.21	1.52	4.30	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.14	1.42	1.78	5.06	-	9.40 [3.0-11.6]	9.1	1980 [640-3300]	4.75	
	16+20+35+35	1.21	1.51	2.64	2.64	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.42	1.78	3.10	3.10	-	9.40 [3.0-11.6]	9.2	2000 [540-3360]	4.70	
	16+20+35+42	1.13	1.42	2.48	2.97	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.33	1.66	2.91	3.50	-	9.40 [3.0-11.6]	9.1	1990 [550-3350]	4.72	
	16+20+35+50	1.06	1.32	2.31	3.31	--	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.24	1.55	2.72	3.89	-	9.40 [3.0-11.6]	9.0	1970 [650-3290]	4.77	
	16+20+35+60	0.98	1.22	2.14	3.66	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.15	1.44	2.51	4.30	-	9.40 [3.0-11.6]	9.0	1970 [650-3290]	4.77	
	16+20+35+71	0.90	1.13	1.97	4.00	-	8.00 [2.3-9.2]	8.5	1880 [530-2660]	4.26	1.06	1.32	2.32	4.70	-	9.40 [3.0-11.6]	9.0	1970 [670-3280]	4.77	
	16+20+42+42	1.07	1.33	2.80	2.80	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.25	1.57	3.29	3.29	-	9.40 [3.0-11.6]	9.1	1990 [550-3340]	4.72	
	16+20+42+50	1.00	1.25	2.63	3.12	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.18	1.47	3.08	3.67	-	9.40 [3.0-11.6]	9.0	1970 [670-3280]	4.77	
	16+20+42+60	0.93	1.16	2.43	3.48	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.09	1.36	2.86	4.09	-	9.40 [3.0-11.6]	9.0	1970 [670-3280]	4.77	
	16+20+50+50	0.94	1.18	2.94																

CU-4Z80VBR: Only Wall-Mounted Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION									
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP	
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E					
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W	
4 rooms	20+20+20+60	1.33	1.33	1.33	4.01	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.57	1.57	1.57	4.69	-	9.40 [3.0-11.6]	9.1	1980 [640-3310]	4.75	
	20+20+20+71	1.22	1.22	1.22	4.34	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.44	1.44	1.44	5.08	-	9.40 [3.0-11.6]	9.0	1970 [640-3290]	4.77	
	20+20+25+25	1.78	1.78	2.22	2.22	-	8.00 [2.3-9.2]	8.9	1980 [420-2870]	4.04	2.09	2.09	2.61	2.61	-	9.40 [3.0-11.6]	9.3	2030 [500-3420]	4.63	
	20+20+25+35	1.60	1.60	2.00	2.80	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.88	1.88	2.35	3.29	-	9.40 [3.0-11.6]	9.2	2010 [530-3380]	4.68	
	20+20+25+42	1.50	1.50	1.87	3.13	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.76	1.76	2.20	3.68	-	9.40 [3.0-11.6]	9.2	2000 [540-3370]	4.70	
	20+20+25+50	1.39	1.39	1.74	3.48	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.63	1.63	2.04	4.10	-	9.40 [3.0-11.6]	9.1	1980 [640-3310]	4.75	
	20+20+25+60	1.28	1.28	1.60	3.84	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.50	1.50	1.88	4.52	-	9.40 [3.0-11.6]	9.1	1980 [640-3310]	4.75	
	20+20+25+71	1.18	1.18	1.47	4.17	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.38	1.38	1.73	4.91	-	9.40 [3.0-11.6]	9.0	1970 [640-3290]	4.77	
	20+20+35+35	1.45	1.45	2.55	2.55	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.71	1.71	2.99	2.99	-	9.40 [3.0-11.6]	9.1	1990 [550-3350]	4.72	
	20+20+35+42	1.37	1.37	2.39	2.87	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.61	1.61	2.81	3.37	-	9.40 [3.0-11.6]	9.1	1990 [550-3340]	4.72	
	20+20+35+50	1.28	1.28	2.24	3.20	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.50	1.50	2.63	3.77	-	9.40 [3.0-11.6]	9.0	1970 [670-3280]	4.77	
	20+20+35+60	1.19	1.19	2.07	3.55	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.39	1.39	2.44	4.18	-	9.40 [3.0-11.6]	9.0	1970 [670-3280]	4.77	
	20+20+35+71	1.10	1.10	1.92	3.88	-	8.00 [2.3-9.2]	8.5	1880 [530-2660]	4.26	1.29	1.29	2.25	4.57	-	9.40 [3.0-11.6]	9.2	2000 [680-3270]	4.70	
	20+20+42+42	1.29	1.29	2.71	2.71	-	8.00 [2.3-9.2]	8.7	1930 [460-2800]	4.15	1.52	1.52	3.18	3.18	-	9.40 [3.0-11.6]	9.1	1980 [570-3330]	4.75	
	20+20+42+50	1.21	1.21	2.55	3.03	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.42	1.42	2.99	3.57	-	9.40 [3.0-11.6]	9.2	2000 [680-3270]	4.70	
	20+20+42+60	1.13	1.13	2.37	3.37	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.32	1.32	2.78	3.98	-	9.40 [3.0-11.6]	9.2	2000 [680-3270]	4.70	
	20+20+50+50	1.14	1.14	2.86	2.86	-	8.00 [2.3-9.2]	8.5	1890 [590-2610]	4.23	1.34	1.34	3.36	3.36	-	9.40 [3.0-11.6]	9.2	2000 [800-3290]	4.70	
	20+25+25+25	1.67	2.11	2.11	2.11	-	8.00 [2.3-9.2]	8.9	1980 [420-2870]	4.04	1.99	2.47	2.47	2.47	-	9.40 [3.0-11.6]	9.3	2030 [500-3420]	4.63	
	20+25+25+35	1.52	1.90	1.90	2.68	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.79	2.24	2.24	3.13	-	9.40 [3.0-11.6]	9.2	2010 [530-3380]	4.68	
	20+25+25+42	1.43	1.79	1.79	2.99	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.68	2.10	2.10	3.52	-	9.40 [3.0-11.6]	9.2	2000 [540-3370]	4.70	
	20+25+25+50	1.33	1.67	1.67	3.33	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.57	1.96	1.96	3.91	-	9.40 [3.0-11.6]	9.1	1980 [640-3310]	4.75	
	20+25+25+60	1.23	1.54	1.54	3.69	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.45	1.81	1.81	4.33	-	9.40 [3.0-11.6]	9.1	1980 [640-3310]	4.75	
	20+25+25+71	1.13	1.42	1.42	4.03	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.33	1.67	1.67	4.73	-	9.40 [3.0-11.6]	9.0	1970 [640-3290]	4.77	
	20+25+35+35	1.39	1.75	2.43	2.43	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.63	2.05	2.86	2.86	-	9.40 [3.0-11.6]	9.1	1990 [550-3350]	4.72	
	20+25+35+42	1.31	1.64	2.30	2.75	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.54	1.93	2.70	3.23	-	9.40 [3.0-11.6]	9.1	1990 [550-3340]	4.72	
	20+25+35+50	1.23	1.54	2.15	3.08	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.45	1.81	2.53	3.61	-	9.40 [3.0-11.6]	9.0	1970 [670-3280]	4.77	
	20+2																			

CU-4Z80VBR: Free Multi Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION									
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP			
		Room A	Room B	Room C	Room D	Room E				Room A	Room B	Room C	Room D	Room E						
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	W	W/W			
2 rooms	16+16	1.60	1.60	-	-	-	3.20 [2.3-5.8]	4.0	830 [350-2090]	3.86	2.60	2.60	-	-	-	5.20 [2.2-8.2]	7.9	1760 [430-3040]	2.95	
	16+20	1.60	2.00	-	-	-	3.60 [2.3-5.8]	4.6	970 [340-2090]	3.71	2.58	3.22	-	-	-	5.80 [2.2-8.2]	8.5	1880 [430-3030]	3.09	
	16+25	1.60	2.50	-	-	-	4.10 [2.3-5.8]	5.5	1170 [340-2090]	3.50	2.42	3.78	-	-	-	6.20 [2.2-8.2]	9.1	2020 [430-3030]	3.07	
	16+35	1.60	3.50	-	-	-	5.10 [2.3-5.8]	7.3	1580 [340-2020]	3.23	2.23	4.87	-	-	-	7.10 [2.2-8.6]	9.9	2190 [380-3110]	3.24	
	16+42	1.60	4.20	-	-	-	5.80 [2.3-6.7]	8.8	1920 [340-2580]	3.02	2.26	5.94	-	-	-	8.20 [2.2-9.8]	11.6	2570 [370-3640]	3.19	
	16+50	1.60	5.00	-	-	-	6.60 [2.3-7.2]	9.9	2160 [320-2580]	3.06	2.28	7.12	-	-	-	9.40 [2.2-10.0]	12.0	2660 [330-3450]	3.53	
	16+60	1.60	6.00	-	-	-	7.60 [2.3-8.5]	12.8	2790 [320-3590]	2.72	1.98	7.42	-	-	-	9.40 [2.2-10.0]	12.0	2660 [330-3450]	3.53	
	16+71	1.47	6.53	-	-	-	8.00 [2.3-8.5]	13.5	2940 [320-3440]	2.72	1.73	7.67	-	-	-	9.40 [2.2-10.3]	11.7	2600 [320-3620]	3.62	
	20+20	2.00	2.00	-	-	-	4.00 [2.3-5.8]	5.2	1110 [340-2030]	3.60	3.20	3.20	-	-	-	6.40 [2.2-8.2]	9.3	2060 [390-3020]	3.11	
	20+25	2.00	2.50	-	-	-	4.50 [2.3-5.8]	6.2	1340 [340-2030]	3.36	3.02	3.78	-	-	-	6.80 [2.2-8.2]	9.5	2120 [390-3020]	3.21	
	20+35	2.00	3.50	-	-	-	5.50 [2.3-5.8]	8.0	1750 [340-1960]	3.14	2.80	4.90	-	-	-	7.70 [2.2-8.6]	10.7	2370 [370-3050]	3.25	
	20+42	2.00	4.20	-	-	-	6.20 [2.3-7.2]	10.0	2170 [340-3000]	2.86	2.84	5.96	-	-	-	8.80 [2.2-10.0]	11.8	2620 [370-3750]	3.36	
	20+50	2.00	5.00	-	-	-	7.00 [2.3-8.1]	10.6	2310 [320-3200]	3.03	2.69	6.71	-	-	-	9.40 [2.2-10.0]	11.9	2650 [320-3430]	3.55	
	20+60	2.00	6.00	-	-	-	8.00 [2.3-8.5]	13.8	3010 [320-3590]	2.66	2.35	7.05	-	-	-	9.40 [2.2-10.0]	11.9	2650 [320-3430]	3.55	
	20+71	1.76	6.24	-	-	-	8.00 [2.3-8.5]	13.2	2870 [350-3440]	2.79	2.07	7.33	-	-	-	9.40 [2.2-10.3]	11.7	2590 [320-3600]	3.63	
	25+25	2.50	2.50	-	-	-	5.00 [2.3-5.8]	7.1	1530 [340-2030]	3.27	3.60	3.60	-	-	-	7.20 [2.2-8.6]	10.1	2250 [390-3130]	3.20	
	25+35	2.50	3.50	-	-	-	6.00 [2.3-6.7]	9.4	2040 [340-2580]	2.94	3.37	4.73	-	-	-	8.10 [2.2-9.8]	11.3	2520 [370-3640]	3.21	
	25+42	2.50	4.20	-	-	-	6.70 [2.3-7.2]	11.5	2510 [340-3000]	2.67	3.43	5.77	-	-	-	9.20 [2.2-10.0]	12.5	2770 [370-3750]	3.32	
	25+50	2.50	5.00	-	-	-	7.50 [2.3-8.5]	12.2	2650 [320-3590]	2.83	3.13	6.27	-	-	-	9.40 [2.2-10.0]	11.9	2650 [320-3430]	3.55	
	25+60	2.35	5.65	-	-	-	8.00 [2.3-8.5]	13.8	3010 [320-3590]	2.66	2.76	6.64	-	-	-	9.40 [2.2-10.0]	11.9	2650 [320-3430]	3.55	
	25+71	2.08	5.92	-	-	-	8.00 [2.3-8.5]	13.2	2870 [350-3440]	2.79	2.45	6.95	-	-	-	9.40 [2.2-10.3]	11.7	2590 [320-3600]	3.63	
	35+35	3.50	3.50	-	-	-	7.00 [2.3-8.1]	12.2	2650 [330-3730]	2.64	4.50	4.50	-	-	-	9.00 [2.2-10.0]	11.9	2650 [360-3670]	3.40	
	35+42	3.50	4.20	-	-	-	7.70 [2.3-8.5]	14.4	3140 [330-4220]	2.45	4.27	5.13	-	-	-	9.40 [2.2-10.0]	12.6	2790 [350-3660]	3.37	
	35+50	3.29	4.71	-	-	-	8.00 [2.3-8.5]	13.2	2870 [320-3440]	2.79	3.87	5.53	-	-	-	9.40 [2.2-10.0]	11.6	2580 [320-3400]	3.64	
	35+60	2.95	5.05	-	-	-	8.00 [2.3-8.5]	13.2	2870 [320-3440]	2.79	3.46	5.94	-	-	-	9.40 [2.2-10.3]	11.6	2580 [320-3520]	3.64	
	35+71	2.64	5.36	-	-	-	8.00 [2.3-8.6]	12.8	2800 [350-3440]	2.86	3.10	6.30	-	-	-	9.40 [2.2-10.5]	11.5	2560 [310-3630]	3.67	
	42+42	4.00	4.00	-	-	-	8.00 [2.3-8.5]	15.8	3440 [330-4140]	2.33	4.70	4.70	-	-	-	9.40 [2.2-10.0]	12.5	2780 [350-3650]	3.38	
	42+50	3.65	4.35	-	-	-	8.00 [2.3-8.5]	13.2	2870 [320-3440]	2.79	4.29	5.11	-	-	-	9.40 [2.2-10.3]	11.5	2560 [320-3510]	3.67	
	42+60	3.29	4.71	-	-	-	8.00 [2.3-8.6]	13.2	2870 [320-3520]	2.79	3.87	5.53	-	-	-	9.40 [2.2-10.3]	11.5	2560 [320-3510]		

CU-4Z80VBR: Free Multi Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION									
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP	
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E					
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W	
3 rooms	16+25+35	1.60	2.50	3.50	-	-	7.60 [2.3-8.5]	10.7	2340 [340-3100]	3.25	1.98	3.09	4.33	-	-	9.40 [3.0-10.4]	11.4	2540 [430-3510]	3.70	
	16+25+42	1.54	2.41	4.05	-	-	8.00 [2.3-8.6]	11.2	2440 [340-3180]	3.28	1.81	2.83	4.76	-	-	9.40 [3.0-10.4]	11.4	2530 [430-3500]	3.72	
	16+25+50	1.41	2.20	4.39	-	-	8.00 [2.3-8.6]	10.3	2250 [380-2880]	3.56	1.65	2.58	5.17	-	-	9.40 [3.0-10.5]	10.9	2420 [460-3350]	3.88	
	16+25+60	1.27	1.98	4.75	-	-	8.00 [2.3-8.8]	10.3	2250 [380-2950]	3.56	1.49	2.33	5.58	-	-	9.40 [3.0-10.5]	10.9	2420 [460-3350]	3.88	
	16+25+71	1.14	1.79	5.07	-	-	8.00 [2.3-8.8]	10.0	2190 [380-2950]	3.65	1.34	2.10	5.96	-	-	9.40 [3.0-10.6]	10.9	2410 [460-3390]	3.90	
	16+35+35	1.48	3.26	3.26	-	-	8.00 [2.3-8.6]	10.9	2380 [340-3100]	3.36	1.74	3.83	3.83	-	-	9.40 [3.0-10.5]	11.3	2510 [460-3540]	3.75	
	16+35+42	1.38	3.01	3.61	-	-	8.00 [2.3-8.6]	10.9	2380 [340-3100]	3.36	1.62	3.54	4.24	-	-	9.40 [3.0-10.5]	11.3	2500 [460-3460]	3.76	
	16+35+50	1.27	2.77	3.96	-	-	8.00 [2.3-8.8]	10.0	2190 [380-2950]	3.65	1.49	3.26	4.65	-	-	9.40 [3.0-10.5]	10.8	2390 [490-3310]	3.93	
	16+35+60	1.15	2.52	4.33	-	-	8.00 [2.3-8.8]	10.0	2190 [380-2950]	3.65	1.35	2.96	5.09	-	-	9.40 [3.0-10.6]	10.8	2390 [490-3370]	3.93	
	16+35+71	1.05	2.30	4.65	-	-	8.00 [2.3-9.0]	10.0	2190 [380-3020]	3.65	1.23	2.70	5.47	-	-	9.40 [3.0-10.6]	10.7	2380 [490-3360]	3.95	
	16+42+42	1.28	3.36	3.36	-	-	8.00 [2.3-8.8]	10.9	2380 [340-3250]	3.36	1.50	3.95	3.95	-	-	9.40 [3.0-10.5]	11.2	2490 [460-3450]	3.78	
	16+42+50	1.19	3.11	3.70	-	-	8.00 [2.3-8.8]	10.0	2190 [380-2950]	3.65	1.39	3.66	4.35	-	-	9.40 [3.0-10.5]	10.8	2390 [490-3300]	3.93	
	16+42+60	1.08	2.85	4.07	-	-	8.00 [2.3-9.0]	10.0	2190 [380-3020]	3.65	1.27	3.35	4.78	-	-	9.40 [3.0-10.6]	10.8	2390 [490-3360]	3.93	
	16+42+71	0.99	2.60	4.41	-	-	8.00 [2.3-9.0]	9.8	2130 [380-2950]	3.76	1.17	3.06	5.17	-	-	9.40 [3.0-10.6]	10.7	2370 [490-3340]	3.97	
	16+50+50	1.10	3.45	3.45	-	-	8.00 [2.3-8.8]	9.5	2070 [430-2730]	3.86	1.30	4.05	4.05	-	-	9.40 [3.0-10.6]	10.4	2300 [550-3230]	4.09	
	16+50+60	1.02	3.17	3.81	-	-	8.00 [2.3-9.0]	9.5	2070 [430-2800]	3.86	1.19	3.73	4.48	-	-	9.40 [3.0-10.6]	10.4	2300 [550-3230]	4.09	
	16+50+71	0.93	2.92	4.15	-	-	8.00 [2.3-9.0]	9.5	2070 [470-2800]	3.86	1.10	3.43	4.87	-	-	9.40 [3.0-10.6]	10.3	2290 [550-3220]	4.10	
	16+60+60	0.94	3.53	3.53	-	-	8.00 [2.3-9.0]	9.5	2070 [430-2800]	3.86	1.10	4.15	4.15	-	-	9.40 [3.0-10.6]	10.4	2300 [550-3230]	4.09	
	16+60+71	0.87	3.27	3.86	-	-	8.00 [2.3-9.0]	9.5	2070 [470-2800]	3.86	1.02	3.84	4.54	-	-	9.40 [3.0-10.6]	10.3	2290 [550-3220]	4.10	
	20+20+20	2.00	2.00	2.00	-	-	6.00 [2.3-8.5]	7.6	1650 [340-3180]	3.64	3.13	3.13	3.13	-	-	9.39 [3.0-10.4]	11.5	2560 [440-3540]	3.67	
	20+20+25	2.00	2.00	2.50	-	-	6.50 [2.3-8.5]	8.6	1880 [340-3180]	3.46	2.89	2.89	3.62	-	-	9.40 [3.0-10.4]	11.5	2560 [440-3540]	3.67	
	20+20+35	2.00	2.00	3.50	-	-	7.50 [2.3-8.5]	10.1	2210 [340-3100]	3.39	2.51	2.51	4.38	-	-	9.40 [3.0-10.4]	11.4	2530 [430-3500]	3.72	
	20+20+42	1.95	1.95	4.10	-	-	8.00 [2.3-8.6]	11.2	2440 [340-3180]	3.28	2.29	2.29	4.82	-	-	9.40 [3.0-10.4]	11.3	2520 [460-3490]	3.73	
	20+20+50	1.78	1.78	4.44	-	-	8.00 [2.3-8.6]	10.0	2190 [380-2800]	3.65	2.09	2.09	5.22	-	-	9.40 [3.0-10.5]	10.9	2410 [460-3330]	3.90	
	20+20+60	1.60	1.60	4.80	-	-	8.00 [2.3-8.8]	10.0	2190 [380-2950]	3.65	1.88	1.88	5.64	-	-	9.40 [3.0-10.5]	10.9	2410 [460-3330]	3.90	
	20+20+71	1.44	1.44	5.12	-	-	8.00 [2.3-8.8]	10.0	2190 [380-2870]	3.65	1.69	1.69	6.02	-	-	9.40 [3.0-10.6]	10.8	2400 [460-3380]	3.92	
	20+25+25	2.00	2.50	2.50	-	-	7.00 [2.3-8.5]	9.4	2040 [340-3180]	3.43	2.68	3.36	3.36	-	-	9.40 [3.0-10.4]	11.5	2560 [440-3540]	3.67	
	20+25+35	2.00	2.50	3.																

CU-4Z80VBR: Free Multi Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION									
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP	
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E					
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W	
3 rooms	25+35+42	1.96	2.75	3.29	-	-	8.00 [2.3-8.8]	10.9	2380 [340-3250]	3.36	2.30	3.23	3.87	-	-	9.40 [3.0-10.5]	11.2	2490 [460-3450]	3.78	
	25+35+50	1.82	2.55	3.63	-	-	8.00 [2.3-8.8]	10.0	2190 [380-2950]	3.65	2.14	2.99	4.27	-	-	9.40 [3.0-10.5]	10.8	2390 [490-3300]	3.93	
	25+35+60	1.67	2.33	4.00	-	-	8.00 [2.3-9.0]	10.0	2190 [380-3020]	3.65	1.96	2.74	4.70	-	-	9.40 [3.0-10.6]	10.8	2390 [490-3360]	3.93	
	25+35+71	1.53	2.14	4.33	-	-	8.00 [2.3-9.0]	9.8	2130 [380-2950]	3.76	1.79	2.51	5.10	-	-	9.40 [3.0-10.6]	10.7	2370 [490-3340]	3.97	
	25+42+42	1.84	3.08	3.08	-	-	8.00 [2.3-8.8]	10.9	2380 [340-3180]	3.36	2.16	3.62	3.62	-	-	9.40 [3.0-10.5]	11.2	2480 [460-3440]	3.79	
	25+42+50	1.71	2.87	3.42	-	-	8.00 [2.3-8.8]	10.0	2190 [380-2870]	3.65	2.01	3.37	4.02	-	-	9.40 [3.0-10.6]	10.7	2380 [490-3350]	3.95	
	25+42+60	1.57	2.65	3.78	-	-	8.00 [2.3-9.0]	10.0	2190 [380-3020]	3.65	1.85	3.11	4.44	-	-	9.40 [3.0-10.6]	10.7	2380 [490-3350]	3.95	
	25+42+71	1.45	2.43	4.12	-	-	8.00 [2.3-9.0]	9.8	2130 [380-2950]	3.76	1.70	2.86	4.84	-	-	9.40 [3.0-10.6]	10.7	2370 [490-3330]	3.97	
	25+50+50	1.60	3.20	3.20	-	-	8.00 [2.3-9.0]	9.5	2070 [430-2800]	3.86	1.88	3.76	3.76	-	-	9.40 [3.0-10.6]	10.3	2290 [550-3220]	4.10	
	25+50+60	1.48	2.96	3.56	-	-	8.00 [2.3-9.0]	9.5	2070 [430-2800]	3.86	1.74	3.48	4.18	-	-	9.40 [3.0-10.6]	10.3	2290 [550-3220]	4.10	
	25+50+71	1.37	2.74	3.89	-	-	8.00 [2.3-9.0]	9.5	2070 [470-2800]	3.86	1.61	3.22	4.57	-	-	9.40 [3.0-10.6]	10.3	2280 [580-3210]	4.12	
	25+60+60	1.38	3.31	3.31	-	-	8.00 [2.3-9.0]	9.5	2070 [430-2800]	3.86	1.62	3.89	3.89	-	-	9.40 [3.0-10.6]	10.3	2290 [550-3220]	4.10	
	35+35+35	2.66	2.66	2.66	-	-	7.98 [2.3-8.8]	10.6	2320 [340-3180]	3.44	3.13	3.13	3.13	-	-	9.39 [3.0-10.5]	11.2	2480 [460-3430]	3.79	
	35+35+42	2.50	2.50	3.00	-	-	8.00 [2.3-8.8]	10.6	2320 [340-3180]	3.45	2.94	2.94	3.52	-	-	9.40 [3.0-10.6]	11.1	2470 [460-3470]	3.81	
	35+35+50	2.33	2.33	3.33	-	-	7.99 [2.3-9.0]	9.8	2130 [380-3020]	3.75	2.74	2.74	3.92	-	-	9.40 [3.0-10.6]	10.6	2360 [490-3330]	3.98	
	35+35+60	2.15	2.15	3.70	-	-	8.00 [2.3-9.0]	9.8	2130 [380-3020]	3.76	2.53	2.53	4.34	-	-	9.40 [3.0-10.6]	10.6	2360 [490-3330]	3.98	
	35+35+71	1.99	1.99	4.02	-	-	8.00 [2.3-9.0]	9.8	2130 [420-2950]	3.76	2.33	2.33	4.74	-	-	9.40 [3.0-10.6]	10.6	2350 [500-3310]	4.00	
	35+42+42	2.36	2.82	2.82	-	-	8.00 [2.3-9.0]	10.6	2320 [340-3250]	3.45	2.76	3.32	3.32	-	-	9.40 [3.0-10.6]	11.1	2460 [460-3460]	3.82	
	35+42+50	2.20	2.65	3.15	-	-	8.00 [2.3-9.0]	9.8	2130 [380-2950]	3.76	2.59	3.11	3.70	-	-	9.40 [3.0-10.6]	10.6	2350 [500-3320]	4.00	
	35+42+60	2.04	2.45	3.51	-	-	8.00 [2.3-9.0]	9.8	2130 [380-2950]	3.76	2.40	2.88	4.12	-	-	9.40 [3.0-10.6]	10.6	2350 [500-3320]	4.00	
	35+50+50	2.08	2.96	2.96	-	-	8.00 [2.3-9.0]	9.5	2070 [470-2800]	3.86	2.44	3.48	3.48	-	-	9.40 [3.0-10.6]	10.2	2270 [580-3190]	4.14	
	35+50+60	1.93	2.76	3.31	-	-	8.00 [2.3-9.0]	9.5	2070 [470-2800]	3.86	2.27	3.24	3.89	-	-	9.40 [3.0-10.6]	10.2	2270 [580-3190]	4.14	
	42+42+42	2.66	2.66	2.66	-	-	7.98 [2.3-9.0]	10.6	2320 [340-3250]	3.44	3.13	3.13	3.13	-	-	9.39 [3.0-10.6]	11.0	2450 [460-3450]	3.83	
	42+42+50	2.51	2.51	2.98	-	-	8.00 [2.3-9.0]	9.8	2130 [380-2950]	3.76	2.95	2.95	3.50	-	-	9.40 [3.0-10.6]	10.6	2350 [500-3300]	4.00	
	42+42+60	2.33	2.33	3.33	-	-	7.99 [2.3-9.0]	9.8	2130 [380-2950]	3.75	2.74	2.74	3.92	-	-	9.40 [3.0-10.6]	10.6	2350 [500-3300]	4.00	
	42+50+50	2.36	2.82	2.82	-	-	8.00 [2.3-9.0]	9.5	2070 [470-2800]	3.86	2.78	3.31	3.31	-	-	9.40 [3.0-10.6]	10.2	2270 [590-3180]	4.14	
4 rooms	16+16+16+16	1.60	1.60	1.60	1.60	-	6.40 [2.3-9.2]	7.3	1610 [420-3060]	3.98	2.35	2.35	2.35	2.35	-	9.40 [3.0-11.6]	10.6	2300 [490-3710]	4.09	
	16+16+16+20	1.																		

CU-4Z80VBR: Free Multi Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION									
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP			
		Room A	Room B	Room C	Room D	Room E				Room A	Room B	Room C	Room D	Room E						
		kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	A	W	W/W			
4 rooms	16+16+25+50	1.20	1.20	1.87	3.73	-	8.00 [2.3-9.2]	9.0	2000 [480-2780]	4.00	1.41	1.41	2.20	4.38	-	9.40 [3.0-11.6]	10.2	2230 [620-3570]	4.22	
	16+16+25+60	1.09	1.09	1.71	4.11	-	8.00 [2.3-9.2]	9.0	2000 [480-2780]	4.00	1.29	1.29	2.01	4.81	-	9.40 [3.0-11.6]	10.2	2230 [620-3570]	4.22	
	16+16+25+71	1.00	1.00	1.56	4.44	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.18	1.18	1.84	5.20	-	9.40 [3.0-11.6]	10.2	2220 [630-3550]	4.23	
	16+16+35+35	1.25	1.25	2.75	2.75	-	8.00 [2.3-9.2]	9.2	2050 [430-2920]	3.90	1.47	1.47	3.23	3.23	-	9.40 [3.0-11.6]	10.3	2250 [540-3620]	4.18	
	16+16+35+42	1.17	1.17	2.57	3.09	-	8.00 [2.3-9.2]	9.2	2050 [430-2920]	3.90	1.38	1.38	3.02	3.62	-	9.40 [3.0-11.6]	10.3	2240 [540-3600]	4.20	
	16+16+35+50	1.09	1.09	2.39	3.43	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.29	1.29	2.81	4.01	-	9.40 [3.0-11.6]	10.2	2220 [640-3540]	4.23	
	16+16+35+60	1.01	1.01	2.20	3.78	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.18	1.18	2.59	4.45	-	9.40 [3.0-11.6]	10.2	2220 [640-3540]	4.23	
	16+16+35+71	0.93	0.93	2.03	4.11	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.09	1.09	2.38	4.84	-	9.40 [3.0-11.6]	10.1	2210 [650-3530]	4.25	
	16+16+42+42	1.10	1.10	2.90	2.90	-	8.00 [2.3-9.2]	9.2	2050 [430-2920]	3.90	1.30	1.30	3.40	3.40	-	9.40 [3.0-11.6]	10.2	2230 [550-3590]	4.22	
	16+16+42+50	1.03	1.03	2.71	3.23	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.21	1.21	3.18	3.80	-	9.40 [3.0-11.6]	10.1	2210 [650-3530]	4.25	
	16+16+42+60	0.96	0.96	2.51	3.57	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.12	1.12	2.95	4.21	-	9.40 [3.0-11.6]	10.1	2210 [650-3530]	4.25	
	16+16+42+71	0.88	0.88	2.32	3.92	-	8.00 [2.3-9.2]	9.0	2000 [530-2780]	4.00	1.04	1.04	2.72	4.60	-	9.40 [3.0-11.6]	10.1	2210 [670-3520]	4.25	
	16+16+50+50	0.97	0.97	3.03	3.03	-	8.00 [2.3-9.2]	9.1	2010 [580-2720]	3.98	1.14	1.14	3.56	3.56	-	9.40 [3.0-11.6]	10.3	2250 [780-3540]	4.18	
	16+16+50+60	0.90	0.90	2.82	3.38	-	8.00 [2.3-9.2]	9.1	2010 [580-2720]	3.98	1.06	1.06	3.31	3.97	-	9.40 [3.0-11.6]	10.3	2250 [780-3540]	4.18	
	16+20+20+20	1.60	2.00	2.00	2.00	-	7.60 [2.3-9.2]	9.0	1990 [420-2990]	3.82	1.99	2.47	2.47	2.47	-	9.40 [3.0-11.6]	10.5	2280 [500-3670]	4.12	
	16+20+20+25	1.58	1.98	1.98	2.46	-	8.00 [2.3-9.2]	9.5	2100 [420-2990]	3.81	1.86	2.32	2.32	2.90	-	9.40 [3.0-11.6]	10.5	2280 [500-3670]	4.12	
	16+20+20+35	1.41	1.76	1.76	3.07	-	8.00 [2.3-9.2]	9.2	2050 [420-2920]	3.90	1.65	2.07	2.07	3.61	-	9.40 [3.0-11.6]	10.4	2260 [530-3640]	4.16	
	16+20+20+42	1.31	1.63	1.63	3.43	-	8.00 [2.3-9.2]	9.2	2050 [430-2920]	3.90	1.53	1.92	1.92	4.03	-	9.40 [3.0-11.6]	10.3	2250 [530-3620]	4.18	
	16+20+20+50	1.21	1.51	1.51	3.77	-	8.00 [2.3-9.2]	9.0	2000 [480-2780]	4.00	1.42	1.77	1.77	4.44	-	9.40 [3.0-11.6]	10.2	2230 [630-3560]	4.22	
	16+20+20+60	1.10	1.38	1.38	4.14	-	8.00 [2.3-9.2]	9.0	2000 [480-2780]	4.00	1.30	1.62	1.62	4.86	-	9.40 [3.0-11.6]	10.2	2230 [630-3560]	4.22	
	16+20+20+71	1.01	1.26	1.26	4.47	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.18	1.48	1.48	5.26	-	9.40 [3.0-11.6]	10.2	2220 [640-3540]	4.23	
	16+20+25+25	1.48	1.86	2.33	2.33	-	8.00 [2.3-9.2]	9.5	2100 [420-2990]	3.81	1.75	2.19	2.73	2.73	-	9.40 [3.0-11.6]	10.5	2280 [500-3670]	4.12	
	16+20+25+35	1.33	1.67	2.08	2.92	-	8.00 [2.3-9.2]	9.2	2050 [420-2920]	3.90	1.57	1.96	2.45	3.42	-	9.40 [3.0-11.6]	10.4	2260 [530-3640]	4.16	
	16+20+25+42	1.24	1.55	1.94	3.27	-	8.00 [2.3-9.2]	9.2	2050 [430-2920]	3.90	1.46	1.83	2.28	3.83	-	9.40 [3.0-11.6]	10.3	2250 [530-3620]	4.18	
	16+20+25+50	1.15	1.44	1.80	3.61	-	8.00 [2.3-9.2]	9.0	2000 [480-2780]	4.00	1.35	1.69	2.12	4.24	-	9.40 [3.0-11.6]	10.2	2230 [630-3560]	4.22	
	16+20+25+60	1.06	1.32	1.65	3.97	-	8.00 [2.3-9.2]	9.0	2000 [480-2780]	4.00	1.24	1.55	1.94	4.67	-	9.40 [3.0-11.6]	10.2	2230 [630-3560]	4.22	
	16+20+25+71	0.97																		

CU-4Z80VBR: Free Multi Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION								HEATING OPERATION									
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	Total
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
4 rooms	16+35+42+50	0.90	1.96	2.35	2.79	-	8.00 [2.3-9.2]	9.0	2000 [530-2780]	4.00	1.05	2.30	2.76	3.29	-	9.40 [3.0-11.6]	10.3	2240 [690-3550]	4.20
	16+42+42+42	0.89	2.37	2.37	2.37	-	8.00 [2.3-9.2]	9.2	2050 [470-2850]	3.90	1.06	2.78	2.78	2.78	-	9.40 [3.0-11.6]	10.1	2210 [590-3600]	4.25
	20+20+20+20	2.00	2.00	2.00	2.00	-	8.00 [2.3-9.2]	9.5	2100 [420-2990]	3.81	2.35	2.35	2.35	2.35	-	9.40 [3.0-11.6]	10.4	2270 [500-3660]	4.14
	20+20+20+25	1.88	1.88	1.88	2.36	-	8.00 [2.3-9.2]	9.5	2100 [420-2990]	3.81	2.21	2.21	2.21	2.77	-	9.40 [3.0-11.6]	10.4	2270 [500-3660]	4.14
	20+20+20+35	1.68	1.68	1.68	2.96	-	8.00 [2.3-9.2]	9.2	2050 [430-2920]	3.90	1.98	1.98	1.98	3.46	-	9.40 [3.0-11.6]	10.3	2250 [530-3620]	4.18
	20+20+20+42	1.57	1.57	1.57	3.29	-	8.00 [2.3-9.2]	9.2	2050 [430-2920]	3.90	1.84	1.84	1.84	3.88	-	9.40 [3.0-11.6]	10.3	2240 [540-3610]	4.20
	20+20+20+50	1.45	1.45	1.45	3.65	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.71	1.71	1.71	4.27	-	9.40 [3.0-11.6]	10.2	2220 [640-3550]	4.23
	20+20+20+60	1.33	1.33	1.33	4.01	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.57	1.57	1.57	4.69	-	9.40 [3.0-11.6]	10.2	2220 [640-3550]	4.23
	20+20+20+71	1.22	1.22	1.22	4.34	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.44	1.44	1.44	5.08	-	9.40 [3.0-11.6]	10.1	2210 [640-3530]	4.25
	20+20+25+25	1.78	1.78	2.22	2.22	-	8.00 [2.3-9.2]	9.5	2100 [420-2990]	3.81	2.09	2.09	2.61	2.61	-	9.40 [3.0-11.6]	10.4	2270 [500-3660]	4.14
	20+20+25+35	1.60	1.60	2.00	2.80	-	8.00 [2.3-9.2]	9.2	2050 [430-2920]	3.90	1.88	1.88	2.35	3.29	-	9.40 [3.0-11.6]	10.3	2250 [530-3620]	4.18
	20+20+25+42	1.50	1.50	1.87	3.13	-	8.00 [2.3-9.2]	9.2	2050 [430-2920]	3.90	1.76	1.76	2.20	3.68	-	9.40 [3.0-11.6]	10.3	2240 [540-3610]	4.20
	20+20+25+50	1.39	1.39	1.74	3.48	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.63	1.63	2.04	4.10	-	9.40 [3.0-11.6]	10.2	2220 [640-3550]	4.23
	20+20+25+60	1.28	1.28	1.60	3.84	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.50	1.50	1.88	4.52	-	9.40 [3.0-11.6]	10.2	2220 [640-3550]	4.23
	20+20+25+71	1.18	1.18	1.47	4.17	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.38	1.38	1.73	4.91	-	9.40 [3.0-11.6]	10.1	2210 [640-3530]	4.25
	20+20+35+35	1.45	1.45	2.55	2.55	-	8.00 [2.3-9.2]	9.2	2050 [430-2920]	3.90	1.71	1.71	2.99	2.99	-	9.40 [3.0-11.6]	10.2	2230 [550-3590]	4.22
	20+20+35+42	1.37	1.37	2.39	2.87	-	8.00 [2.3-9.2]	9.2	2050 [430-2920]	3.90	1.61	1.61	2.81	3.37	-	9.40 [3.0-11.6]	10.2	2230 [550-3580]	4.22
	20+20+35+50	1.28	1.28	2.24	3.20	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.50	1.50	2.63	3.77	-	9.40 [3.0-11.6]	10.1	2210 [670-3520]	4.25
	20+20+35+60	1.19	1.19	2.07	3.55	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.39	1.39	2.44	4.18	-	9.40 [3.0-11.6]	10.1	2210 [670-3520]	4.25
	20+20+35+71	1.10	1.10	1.92	3.88	-	8.00 [2.3-9.2]	9.0	2000 [530-2780]	4.00	1.29	1.29	2.25	4.57	-	9.40 [3.0-11.6]	10.3	2240 [680-3510]	4.20
	20+20+42+42	1.29	1.29	2.71	2.71	-	8.00 [2.3-9.2]	9.2	2050 [460-2920]	3.90	1.52	1.52	3.18	3.18	-	9.40 [3.0-11.6]	10.2	2220 [570-3570]	4.23
	20+20+42+50	1.21	1.21	2.55	3.03	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.42	1.42	2.99	3.57	-	9.40 [3.0-11.6]	10.3	2240 [680-3510]	4.20
	20+20+42+60	1.13	1.13	2.37	3.37	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.32	1.32	2.78	3.98	-	9.40 [3.0-11.6]	10.3	2240 [680-3510]	4.20
	20+20+50+50	1.14	1.14	2.86	2.86	-	8.00 [2.3-9.2]	9.1	2010 [590-2730]	3.98	1.34	1.34	3.36	3.36	-	9.40 [3.0-11.6]	10.3	2240 [800-3530]	4.20
	20+25+25+25	1.67	2.11	2.11	2.11	-	8.00 [2.3-9.2]	9.5	2100 [420-2990]	3.81	1.99	2.47	2.47	2.47	-	9.40 [3.0-11.6]	10.4	2270 [500-3660]	4.14
	20+25+25+35	1.52	1.90	1.90	2.68	-	8.00 [2.3-9.2]	9.2	2050 [430-2920]	3.90	1.79	2.24	2.24	3.13	-	9.40 [3.0-11.6]	10.3	2250 [530-3620]	4.18
	20+25+25+42	1.43	1.79	1.79	2.99	-	8.00 [2.3-9.2]	9.2	2050 [430-2920]	3.90	1.68	2.10	2.10	3.52	-	9.40 [3.0-11.6]	10.3	2240 [540-3610]	4.20
	20+25+25+50	1.33	1.67	1.67	3.33	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.57	1.96	1.96	3.91	-	9.40 [3.0-11.6]	10.2	2220 [640-3550]	4.23
	20+25+25+60	1.23	1.54	1.54	3.69	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.45	1.81	1.81	4.33	-	9.40 [3.0-11.6]	10.2	2220 [640-3550]	4.23
	20+25+25+71	1.13	1.42	1.42	4.03	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.33	1.67	1.67	4.73	-	9.40 [3.0-11.6]	10.1	2210 [640-3530]	4.25
	20+25+35+35	1.39	1.75	2.43	2.43	-	8.00 [2.3-9.2]	9.2	2050 [430-2920]	3.90	1.63	2.05	2.86	2.86	-	9.40 [3.0-11.6]	10.2	2230 [550-3590]	4.22
	20+25+35+42	1.31	1.64	2.30	2.75	-	8.00 [2.3-9.2]	9.2	2050 [430-2920]	3.90	1.54	1.93	2.70	3.23	-	9.40 [3.0-11.6]	10.2	2230 [550-3580]	4.22
	20+25+35+50	1.23	1.54	2.15	3.08	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.45	1.81	2.53	3.61	-	9.40 [3.0-11.6]	10.1	2210 [670-3520]	4.25
	20+25+35+60	1.14	1.43	2.00	3.43	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.34	1.68	2.35	4.03	-	9.40 [3.0-11.6]	10.1	2210 [670-3520]	4.25
	20+25+42+42	1.24	1.56	2.60	2.60	-	8.00 [2.3-9.2]	9.2	2050 [460-2920]	3.90	1.46	1.82	3.06	3.06	-	9.40 [3.0-11.6]	10.2	2220 [570-3570]	4.23
	20+25+42+50	1.17	1.46	2.45	2.92	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.37	1.72	2.88	3.43	-	9.40 [3.0-11.6]	10.3	2240 [680-3510]	4.20
	20+25+42+60	1.09	1.36	2.29	3.26	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.28	1.60	2.69	3.83	-	9.40 [3.0-11.6]	10.3	2240 [680-3510]	4.20
	20+25+50+50	1.10	1.38	2.76	2.76	-	8.00 [2.3-9.2]	9.1	2010 [590-2730]	3.98	1.30	1.62	3.24	3.24	-	9.40 [3.0-11.6]	10.3	2240 [800-3530]	4.20
	20+35+35+35	1.28	2.24	2.24	2.24	-	8.00 [2.3-9.2]	9.2	2050 [470-2850]	3.90	1.51	2.63	2.63	2.63	-	9.40 [3.0-11.6]	10.2	2220 [580-3560]	4.23
	20+35+35+42	1.21	2.12	2.12	2.55	-	8.00 [2.3-9.2]	9.2	2050 [470-2850]	3.90	1.42	2.49	2.49	3.00	-	9.40 [3.0-11.6]	10.1	2210 [580-3610]	4.25
20+35+35+50	1.14	2.00	2.00	2.86	-	8.00 [2.3-9.2]	9.0	2000 [530-2780]	4.00	1.34	2.35	2.35	3.36	-	9.40 [3.0-11.6]	10.3	2240 [690-3550]	4.20	
20+35+42+42	1.15	2.01	2.42	2.42	-	8.00 [2.3-9.2]	9.2	2050 [470-2850]	3.90	1.35	2.37	2.84	2.84	-	9.40 [3.0-11.6]	10.1	2210 [590-3600]	4.25	
20+35+42+50	1.09	1.90	2.29	2.72	-	8.00 [2.3-9.2]	9.0	2000 [530-2780]	4.00	1.28	2.24	2.69	3.19	-	9.40 [3.0-11.6]	10.2	2230 [700-3540]	4.22	
20+42+42+42	1.10	2.30	2.30	2.30	-	8.00 [2.3-9.2]	9.0	1990 [470-2850]	4.02	1.30	2.70	2.70	2.70	-	9.40 [3.0-11.6]	10.3	2240 [590-3590]	4.20	
25+25+25+25	2.00	2.00	2.00	2.00	-	8.00 [2.3-9.2]	9.5	2100 [420-2990]	3.81	2.35	2.35	2.35	2.35	-	9.40 [3.0-11.6]	10.4	2270 [500-3660]	4.14	
25+25+25+35	1.82	1.82	1.82	2.54	-	8.00 [2.3-9.2]	9.2	2050 [430-2920]	3.90	2.14	2.14	2.14	2.98	-	9.40 [3.0-11.6]	10.3	2250 [530-3620]	4.18	
25+25+25+42	1.71	1.71	1.71	2.87	-	8.00 [2.3-9.2]	9.2	2050 [430-2920]	3.90	2.01	2.01	2.01	3.37	-	9.40 [3.0-11.6]	10.3	2240 [540-3610]	4.20	
25+25+25+50	1.60	1.60	1.60	3.20	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.88	1.88	1.88	3.76	-	9.40 [3.0-11.6]	10.2	2220 [640-3550]	4.23	
25+25+25+60	1.48	1.48	1.48	3.56	-	8.00 [2.3-9.2]	9.0	2000 [520-2780]	4.00	1.74	1.74	1.74	4.18	-	9.40 [3.0-11.				

CU-5Z100VBR: Only Wall-Mounted Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
2 rooms	16+16	1.60	1.60	-	-	-	3.20 [2.3-5.8]	3.4	700 [260-1780]	4.57	2.60	2.60	-	-	-	5.20 [2.0-8.2]	6.6	1460 [220-2490]	3.56
	16+20	1.60	2.00	-	-	-	3.60 [2.3-5.8]	4.0	830 [250-1780]	4.34	2.58	3.22	-	-	-	5.80 [2.0-8.2]	7.4	1620 [220-2480]	3.58
	16+25	1.60	2.50	-	-	-	4.10 [2.3-5.8]	4.7	1000 [250-1780]	4.10	2.42	3.78	-	-	-	6.20 [2.0-8.2]	7.9	1760 [220-2480]	3.52
	16+35	1.60	3.50	-	-	-	5.10 [2.3-5.8]	6.3	1360 [250-1720]	3.75	2.23	4.87	-	-	-	7.10 [2.0-8.6]	9.0	1990 [210-2560]	3.57
	16+42	1.60	4.20	-	-	-	5.80 [2.3-6.7]	7.7	1670 [250-2170]	3.47	2.26	5.94	-	-	-	8.20 [2.0-10.1]	10.6	2350 [210-3110]	3.49
	16+50	1.60	5.00	-	-	-	6.60 [2.3-7.2]	8.6	1880 [240-2170]	3.51	2.28	7.12	-	-	-	9.40 [2.0-11.0]	11.5	2550 [160-3120]	3.69
	16+60	1.60	6.00	-	-	-	7.60 [2.3-8.6]	11.1	2410 [240-3120]	3.15	2.34	8.76	-	-	-	11.10 [2.0-11.0]	13.4	2970 [160-3120]	3.74
	16+71	1.60	7.10	-	-	-	8.70 [2.3-9.1]	13.6	2960 [230-3200]	2.94	2.08	9.22	-	-	-	11.30 [2.0-13.0]	13.1	2910 [160-4060]	3.88
	20+20	2.00	2.00	-	-	-	4.00 [2.3-5.8]	4.5	960 [250-1720]	4.17	3.20	3.20	-	-	-	6.40 [2.0-8.2]	8.1	1790 [220-2470]	3.58
	20+25	2.00	2.50	-	-	-	4.50 [2.3-5.8]	5.4	1160 [250-1720]	3.88	3.02	3.78	-	-	-	6.80 [2.0-8.2]	8.6	1910 [220-2470]	3.56
	20+35	2.00	3.50	-	-	-	5.50 [2.3-5.8]	7.0	1510 [250-1670]	3.64	2.80	4.90	-	-	-	7.70 [2.0-8.6]	9.7	2160 [210-2500]	3.56
	20+42	2.00	4.20	-	-	-	6.20 [2.3-7.2]	8.6	1880 [250-2530]	3.30	2.84	5.96	-	-	-	8.80 [2.0-11.0]	11.3	2500 [200-3310]	3.52
	20+50	2.00	5.00	-	-	-	7.00 [2.3-8.1]	9.1	1990 [240-2650]	3.52	2.86	7.14	-	-	-	10.00 [2.0-11.0]	12.3	2730 [160-3060]	3.66
	20+60	2.00	6.00	-	-	-	8.00 [2.3-8.6]	11.9	2590 [240-3050]	3.09	2.93	8.77	-	-	-	11.70 [2.0-11.9]	13.8	3060 [160-3550]	3.82
	20+71	2.00	7.10	-	-	-	9.10 [2.3-10.0]	14.4	3130 [260-4070]	2.91	2.62	9.28	-	-	-	11.90 [2.0-13.0]	14.1	3140 [160-4050]	3.79
	25+25	2.50	2.50	-	-	-	5.00 [2.3-5.8]	6.1	1310 [250-1720]	3.82	3.60	3.60	-	-	-	7.20 [2.0-8.6]	9.2	2050 [220-2580]	3.51
	25+35	2.50	3.50	-	-	-	6.00 [2.3-6.7]	8.1	1770 [250-2170]	3.39	3.38	4.72	-	-	-	8.10 [2.0-10.1]	10.4	2300 [210-3110]	3.52
	25+42	2.50	4.20	-	-	-	6.70 [2.3-7.2]	10.0	2170 [250-2530]	3.09	3.43	5.77	-	-	-	9.20 [2.0-11.0]	11.9	2650 [200-3310]	3.47
	25+50	2.50	5.00	-	-	-	7.50 [2.3-8.6]	10.5	2290 [240-3050]	3.28	3.47	6.93	-	-	-	10.40 [2.0-11.0]	12.4	2760 [160-3060]	3.77
	25+60	2.50	6.00	-	-	-	8.50 [2.3-9.1]	13.7	2980 [240-3330]	2.85	3.53	8.47	-	-	-	12.00 [2.0-13.0]	14.5	3210 [160-4060]	3.74
	25+71	2.50	7.10	-	-	-	9.60 [2.3-10.1]	16.4	3570 [260-4220]	2.69	3.13	8.87	-	-	-	12.00 [2.0-13.0]	14.4	3190 [160-4050]	3.76
	35+35	3.50	3.50	-	-	-	7.00 [2.3-8.1]	10.5	2290 [250-3100]	3.06	4.50	4.50	-	-	-	9.00 [2.0-11.0]	11.4	2530 [200-3300]	3.56
	35+42	3.50	4.20	-	-	-	7.70 [2.3-8.6]	12.4	2710 [250-3590]	2.84	4.59	5.51	-	-	-	10.10 [2.0-11.0]	13.0	2880 [200-3240]	3.51
	35+50	3.50	5.00	-	-	-	8.50 [2.3-9.1]	13.1	2850 [230-3200]	2.98	4.65	6.65	-	-	-	11.30 [2.0-13.0]	12.8	2840 [160-4040]	3.98
35+60	3.50	6.00	-	-	-	9.50 [2.3-10.1]	16.6	3610 [230-4220]	2.63	4.42	7.58	-	-	-	12.00 [2.0-13.0]	14.1	3130 [160-4040]	3.83	
35+71	3.30	6.70	-	-	-	10.00 [2.3-10.4]	17.7	3860 [260-4380]	2.59	3.96	8.04	-	-	-	12.00 [2.0-13.8]	14.1	3120 [160-4390]	3.85	
42+42	4.20	4.20	-	-	-	8.40 [2.3-9.1]	15.5	3380 [250-4000]	2.49	5.60	5.60	-	-	-	11.20 [2.0-13.0]	13.6	3020 [190-4230]	3.71	
42+50	4.20	5.00	-	-	-	9.20 [2.3-10.0]	15.0	3270 [230-4070]	2.81	5.48	6.52	-	-	-	12.00 [2.0-13.0]	14.1	3120 [160-3970]	3.85	
42+60	4.12	5.88	-	-	-	10.00 [2.3-10.4]	18.7	4070 [230-4370]	2.46	4.94	7.06	-	-	-	12.00 [2.0-13.8]	14.1	3120 [160-4390]	3.85	
42+71	3.72	6.28	-	-	-	10.00 [2.3-10.4]	17.4	3790 [260-4380]	2.64	4.46	7.54	-	-	-	12.00 [2.0-13.8]	14.0	3110 [160-4380]	3.86	
50+50	5.00	5.00	-	-	-	10.00 [2.3-10.4]	15.2	3310 [250-3650]	3.02	6.00	6.00	-	-	-	12.00 [2.0-13.8]	13.1	2910 [170-4140]	4.12	
50+60	4.55	5.45	-	-	-	10.00 [2.3-10.4]	15.2	3310 [250-3650]	3.02	5.45	6.55	-	-	-	12.00 [2.0-13.8]	13.1	2910 [170-4140]	4.12	
50+71	4.13	5.87	-	-	-	10.00 [2.3-10.4]	14.5	3170 [250-3520]	3.15	4.96	7.04	-	-	-	12.00 [2.0-13.8]	13.0	2890 [170-4120]	4.15	
60+60	5.00	5.00	-	-	-	10.00 [2.3-10.4]	15.2	3310 [250-3650]	3.02	6.00	6.00	-	-	-	12.00 [2.0-13.8]	13.1	2910 [170-4140]	4.12	
60+71	4.58	5.42	-	-	-	10.00 [2.3-10.4]	14.5	3170 [250-3520]	3.15	5.50	6.50	-	-	-	12.00 [2.0-13.8]	13.0	2890 [170-4120]	4.15	
71+71	5.00	5.00	-	-	-	10.00 [2.3-10.4]	13.9	3040 [280-3380]	3.29	6.00	6.00	-	-	-	12.00 [2.0-13.8]	13.0	2880 [180-4100]	4.17	
3 rooms	16+16+16	1.60	1.60	1.60	-	-	4.80 [2.3-8.5]	4.9	1050 [260-2680]	4.57	2.60	2.60	2.60	-	-	7.80 [2.7-12.3]	8.6	1920 [230-3640]	4.06
	16+16+20	1.60	1.60	2.00	-	-	5.20 [2.3-8.5]	5.4	1160 [260-2680]	4.48	2.58	2.58	3.24	-	-	8.40 [2.7-12.3]	9.6	2140 [230-3620]	3.93
	16+16+25	1.60	1.60	2.50	-	-	5.70 [2.3-8.5]	6.3	1350 [260-2680]	4.22	2.47	2.47	3.86	-	-	8.80 [2.7-12.3]	10.0	2210 [230-3620]	3.98
	16+16+35	1.60	1.60	3.50	-	-	6.70 [2.3-8.5]	7.7	1670 [260-2610]	4.01	2.32	2.32	5.06	-	-	9.70 [2.7-12.3]	11.3	2520 [230-3540]	3.85
	16+16+42	1.60	1.60	4.20	-	-	7.40 [2.3-8.5]	9.2	2010 [250-2550]	3.68	2.34	2.34	6.12	-	-	10.80 [2.7-12.3]	11.9	2650 [230-3520]	4.08
	16+16+50	1.60	1.60	5.00	-	-	8.20 [2.3-8.7]	10.0	2170 [280-2350]	3.78	2.34	2.34	7.32	-	-	12.00 [2.7-12.9]	12.9	2870 [250-3610]	4.18
	16+16+60	1.60	1.60	6.00	-	-	9.20 [2.3-10.1]	11.5	2510 [280-3060]	3.67	2.09	2.09	7.82	-	-	12.00 [2.7-13.6]	12.9	2870 [250-3970]	4.18
	16+16+71	1.55	1.55	6.90	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3400]	3.48	1.86	1.86	8.28	-	-	12.00 [2.7-13.6]	12.9	2860 [250-3890]	4.20
	16+20+20	1.60	2.00	2.00	-	-	5.60 [2.3-8.5]	6.0	1300 [260-2610]	4.31	2.58	3.21	3.21	-	-	9.00 [2.7-12.3]	10.1	2250 [230-3610]	4.00
	16+20+25	1.60	2.00	2.50	-	-	6.10 [2.3-8.5]	7.0	1510 [260-2610]	4.04	2.47	3.08	3.85	-	-	9.40 [2.7-12.3]	10.8	2390 [230-3610]	3.93
	16+20+35	1.60	2.00	3.50	-	-	7.10 [2.3-8.5]	8.4	1840 [250-2550]	3.86	2.32	2.90	5.08	-	-	10.30 [2.7-12.3]	11.5	2550 [230-3520]	4.04
	16+20+42	1.60	2.00	4.20	-	-	7.80 [2.3-8.5]	9.7	2120 [250-2550]	3.68	2.34	2.92	6.14	-	-	11.40 [2.7-12.9]	12.6	2790 [230-3800]	4.09
	16+20+50	1.60	2.00	5.00	-	-	8.60 [2.3-9.6]	10.8	2360 [280-2680]	3.64	2.23	2.79	6.98	-	-	12.00 [2.7-13.6]	12.9	2860 [250-3890]	4.20
	16+20+60	1.60	2.00	6.00	-	-	9.60 [2.3-10.1]	12.3	2680 [280-3000]	3.58	2.00	2.50	7.50	-	-	12.00 [2.7-13.6]	12.9	2860 [250-3890]	4.20
	16+20+71	1.50	1.87	6.63	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3400]	3.48	1.80	2.24	7.96	-	-	12.00 [2.7-13.8]	12.8	2850 [250-4000]	4.21
	16+25+25	1.60	2.50	2.50	-	-	6.60 [2.3-8.5]	8.0	1720 [260-2610]	3.84	2.38	3.71	3.71	-	-	9.80 [2.7-12.3]	11.7	2590 [230-3610]	3.78
	16+25+35	1.60	2.50	3.50	-	-	7.60 [2.3-8.5]	9.7	2120 [250-2550]	3.58	2.25	3.52	4.93	-	-	10.70 [2.7-12.3]	12.1	2690 [230-3520	

CU-5Z100VBR: Only Wall-Mounted Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION								HEATING OPERATION									
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
3 rooms	16+42+60	1.36	3.56	5.08	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3400]	3.48	1.63	4.27	6.10	-	-	12.00 [2.7-13.8]	12.5	2770 [270-3970]	4.33
	16+42+71	1.24	3.26	5.50	-	-	10.00 [2.3-10.7]	12.8	2800 [280-3260]	3.57	1.49	3.91	6.60	-	-	12.00 [2.7-14.1]	12.4	2760 [270-4070]	4.35
	16+50+50	1.38	4.31	4.31	-	-	10.00 [2.3-10.7]	12.0	2610 [320-3000]	3.83	1.66	5.17	5.17	-	-	12.00 [2.7-13.8]	12.0	2660 [300-3760]	4.51
	16+50+60	1.27	3.97	4.76	-	-	10.00 [2.3-10.7]	12.0	2610 [320-3000]	3.83	1.53	4.76	5.71	-	-	12.00 [2.7-13.8]	12.0	2660 [300-3760]	4.51
	16+50+71	1.17	3.65	5.18	-	-	10.00 [2.3-10.7]	11.7	2550 [340-2930]	3.92	1.40	4.38	6.22	-	-	12.00 [2.7-14.1]	11.9	2650 [310-3920]	4.53
	16+60+60	1.18	4.41	4.41	-	-	10.00 [2.3-10.7]	12.0	2610 [320-3000]	3.83	1.42	5.29	5.29	-	-	12.00 [2.7-14.1]	12.0	2660 [300-3930]	4.51
	16+60+71	1.09	4.08	4.83	-	-	10.00 [2.3-10.7]	11.7	2550 [340-2930]	3.92	1.31	4.90	5.79	-	-	12.00 [2.7-14.1]	11.9	2650 [310-3920]	4.53
	16+71+71	1.02	4.49	4.49	-	-	10.00 [2.3-10.7]	11.4	2490 [350-2870]	4.02	1.22	5.39	5.39	-	-	12.00 [2.7-14.4]	11.9	2640 [320-4020]	4.55
	20+20+20	2.00	2.00	2.00	-	-	6.00 [2.3-8.5]	6.7	1450 [260-2610]	4.14	3.20	3.20	3.20	-	-	9.60 [2.7-12.3]	11.2	2480 [230-3600]	3.87
	20+20+25	2.00	2.00	2.50	-	-	6.50 [2.3-8.5]	7.7	1660 [260-2610]	3.92	3.08	3.08	3.84	-	-	10.00 [2.7-12.3]	11.8	2630 [230-3600]	3.80
	20+20+35	2.00	2.00	3.50	-	-	7.50 [2.3-8.5]	9.2	2010 [250-2550]	3.73	2.91	2.91	5.08	-	-	10.90 [2.7-12.3]	12.1	2690 [230-3510]	4.05
	20+20+42	2.00	2.00	4.20	-	-	8.20 [2.3-8.7]	10.8	2360 [250-2600]	3.47	2.93	2.93	6.14	-	-	12.00 [2.7-12.9]	13.6	3020 [230-3790]	3.97
	20+20+50	2.00	2.00	5.00	-	-	9.00 [2.3-9.6]	11.3	2470 [280-2680]	3.64	2.67	2.67	6.66	-	-	12.00 [2.7-13.6]	12.8	2850 [250-3880]	4.21
	20+20+60	2.00	2.00	6.00	-	-	10.00 [2.3-10.7]	13.4	2930 [280-3470]	3.41	2.40	2.40	7.20	-	-	12.00 [2.7-13.6]	12.8	2850 [250-3880]	4.21
	20+20+71	1.80	1.80	6.40	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3330]	3.48	2.16	2.16	7.68	-	-	12.00 [2.7-13.8]	12.6	2790 [250-3980]	4.30
	20+25+25	2.00	2.50	2.50	-	-	7.00 [2.3-8.5]	8.4	1840 [260-2610]	3.80	2.98	3.71	3.71	-	-	10.40 [2.7-12.3]	11.8	2610 [230-3600]	3.98
	20+25+35	2.00	2.50	3.50	-	-	8.00 [2.3-8.5]	10.3	2240 [250-2550]	3.57	2.83	3.53	4.94	-	-	11.30 [2.7-12.9]	12.3	2740 [230-3800]	4.12
	20+25+42	2.00	2.50	4.20	-	-	8.70 [2.3-9.6]	11.9	2600 [250-3060]	3.35	2.76	3.45	5.79	-	-	12.00 [2.7-13.6]	13.6	3020 [230-4150]	3.97
	20+25+50	2.00	2.50	5.00	-	-	9.50 [2.3-10.1]	12.4	2700 [280-3000]	3.52	2.53	3.16	6.31	-	-	12.00 [2.7-13.6]	12.8	2850 [250-3880]	4.21
	20+25+60	1.91	2.38	5.71	-	-	10.00 [2.3-10.7]	13.4	2930 [280-3470]	3.41	2.29	2.86	6.85	-	-	12.00 [2.7-13.8]	12.8	2850 [250-4000]	4.21
	20+25+71	1.72	2.16	6.12	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3330]	3.48	2.07	2.59	7.34	-	-	12.00 [2.7-13.8]	12.6	2790 [250-3980]	4.30
	20+35+35	2.00	3.50	3.50	-	-	9.00 [2.3-9.6]	12.5	2720 [250-2990]	3.31	2.66	4.67	4.67	-	-	12.00 [2.7-13.6]	13.3	2950 [240-4130]	4.07
	20+35+42	2.00	3.50	4.20	-	-	9.70 [2.3-10.7]	13.7	2990 [250-3970]	3.24	2.47	4.33	5.20	-	-	12.00 [2.7-13.6]	13.2	2940 [240-4050]	4.08
	20+35+50	1.91	3.33	4.76	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3400]	3.48	2.29	4.00	5.71	-	-	12.00 [2.7-13.8]	12.5	2770 [270-3970]	4.33
	20+35+60	1.74	3.04	5.22	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3400]	3.48	2.09	3.65	6.26	-	-	12.00 [2.7-13.8]	12.5	2770 [270-3970]	4.33
	20+35+71	1.59	2.78	5.63	-	-	10.00 [2.3-10.7]	12.8	2800 [280-3260]	3.57	1.91	3.33	6.76	-	-	12.00 [2.7-13.8]	12.4	2760 [270-3950]	4.35
	20+42+42	1.92	4.04	4.04	-	-	10.00 [2.3-10.7]	15.0	3260 [250-3970]	3.07	2.30	4.85	4.85	-	-	12.00 [2.7-13.6]	13.2	2930 [240-4040]	4.10
	20+42+50	1.79	3.75	4.46	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3330]	3.48	2.14	4.50	5.36	-	-	12.00 [2.7-13.8]	12.4	2760 [270-3950]	4.35
	20+42+60	1.64	3.44	4.92	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3330]	3.48	1.97	4.13	5.90	-	-	12.00 [2.7-13.8]	12.4	2760 [270-3950]	4.35
	20+42+71	1.50	3.16	5.34	-	-	10.00 [2.3-10.7]	12.6	2740 [280-3260]	3.65	1.80	3.79	6.41	-	-	12.00 [2.7-14.1]	12.4	2750 [270-4060]	4.36
	20+50+50	1.66	4.17	4.17	-	-	10.00 [2.3-10.7]	12.0	2620 [320-3000]	3.82	2.00	5.00	5.00	-	-	12.00 [2.7-13.8]	11.9	2650 [310-3740]	4.53
	20+50+60	1.54	3.85	4.61	-	-	10.00 [2.3-10.7]	12.0	2620 [320-3000]	3.82	1.85	4.62	5.53	-	-	12.00 [2.7-14.1]	11.9	2650 [310-3920]	4.53
	20+50+71	1.42	3.55	5.03	-	-	10.00 [2.3-10.7]	11.7	2550 [350-2930]	3.92	1.70	4.26	6.04	-	-	12.00 [2.7-14.1]	11.9	2640 [320-3900]	4.55
	20+60+60	1.42	4.29	4.29	-	-	10.00 [2.3-10.7]	12.0	2620 [320-3000]	3.82	1.72	5.14	5.14	-	-	12.00 [2.7-14.1]	11.9	2650 [310-3920]	4.53
	20+60+71	1.33	3.97	4.70	-	-	10.00 [2.3-10.7]	11.7	2550 [350-2930]	3.92	1.59	4.77	5.64	-	-	12.00 [2.7-14.4]	11.9	2640 [320-4020]	4.55
	20+71+71	1.24	4.38	4.38	-	-	10.00 [2.3-10.7]	11.4	2490 [350-2870]	4.02	1.48	5.26	5.26	-	-	12.00 [2.7-14.4]	12.0	2670 [330-4010]	4.49
	25+25+25	2.50	2.50	2.50	-	-	7.50 [2.3-8.5]	9.5	2070 [260-2610]	3.62	3.60	3.60	3.60	-	-	10.80 [2.7-12.3]	12.0	2670 [230-3600]	4.04
	25+25+35	2.50	2.50	3.50	-	-	8.50 [2.3-9.6]	11.7	2550 [250-3060]	3.33	3.44	3.44	4.82	-	-	11.70 [2.7-12.6]	13.0	2880 [230-4160]	4.06
	25+25+42	2.50	2.50	4.20	-	-	9.20 [2.3-10.1]	13.0	2830 [250-3460]	3.25	3.26	3.26	5.48	-	-	12.00 [2.7-13.6]	13.6	3020 [230-4150]	3.97
	25+25+50	2.50	2.50	5.00	-	-	10.00 [2.3-10.7]	13.4	2930 [280-3470]	3.41	3.00	3.00	6.00	-	-	12.00 [2.7-13.6]	12.8	2850 [250-3880]	4.21
	25+25+60	2.27	2.27	5.46	-	-	10.00 [2.3-10.7]	13.4	2930 [280-3470]	3.41	2.73	2.73	6.54	-	-	12.00 [2.7-13.8]	12.8	2850 [250-4000]	4.21
	25+25+71	2.07	2.07	5.86	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3330]	3.48	2.48	2.48	7.04	-	-	12.00 [2.7-13.8]	12.6	2790 [250-3980]	4.30
	25+35+35	2.50	3.50	3.50	-	-	9.50 [2.3-10.1]	13.6	2960 [250-3390]	3.21	3.16	4.42	4.42	-	-	12.00 [2.7-13.6]	13.3	2950 [240-4130]	4.07
	25+35+42	2.45	3.43	4.12	-	-	10.00 [2.3-10.7]	15.0	3260 [250-3970]	3.07	2.94	4.12	4.94	-	-	12.00 [2.7-13.6]	13.2	2940 [240-4050]	4.08
	25+35+50	2.27	3.18	4.55	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3400]	3.48	2.73	3.82	5.45	-	-	12.00 [2.7-13.8]	12.5	2770 [270-3970]	4.33
	25+35+60	2.08	2.92	5.00	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3400]	3.48	2.50	3.50	6.00	-	-	12.00 [2.7-13.8]	12.5	2770 [270-3970]	4.33
	25+35+71	1.91	2.67	5.42	-	-	10.00 [2.3-10.7]	12.8	2800 [280-3260]	3.57	2.29	3.21	6.50	-	-	12.00 [2.7-14.1]	12.4	2760 [270-4070]	4.35
	25+42+42	2.30	3.85	3.85	-	-	10.00 [2.3-10.7]	15.0	3260 [250-3970]	3.07	2.76	4.62	4.62	-	-	12.00 [2.7-13.8]	13.2	2930 [240-4160]	4.10
	25+42+50	2.14	3.59	4.27	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3330]	3.48	2.56	4.31	5.13	-	-	12.00 [2.7-13.8]	12.4	2760 [270-3950]	4.35
	25+42+60	1.97	3.31	4.72	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3330]	3.48	2.36	3.97	5.67	-	-	12.00 [2.7-14.1]	12.4	2760 [270-4070]	4.35
	25+42+71	1.82	3.04	5.14	-	-	10.00 [2.3-10.7												

CU-5Z100VBR: Only Wall-Mounted Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	
		kW	kW	kW	kW	kW		kW	A	W	W/W	kW	kW	kW		kW	kW	kW	A
3 rooms	35+42+60	2.55	3.07	4.38	-	-	10.00 [2.3-10.7]	12.8	2800 [280-3260]	3.57	3.07	3.68	5.25	-	-	12.00 [2.7-14.1]	12.3	2740 [270-4040]	4.38
	35+42+71	2.36	2.84	4.80	-	-	10.00 [2.3-10.7]	12.6	2740 [310-3200]	3.65	2.84	3.41	5.75	-	-	12.00 [2.7-14.1]	12.2	2720 [280-4020]	4.41
	35+50+50	2.60	3.70	3.70	-	-	10.00 [2.3-10.7]	11.7	2550 [350-2930]	3.92	3.12	4.44	4.44	-	-	12.00 [2.7-14.1]	12.0	2670 [330-3890]	4.49
	35+50+60	2.41	3.45	4.14	-	-	10.00 [2.3-10.7]	11.7	2550 [350-2930]	3.92	2.90	4.14	4.96	-	-	12.00 [2.7-14.1]	12.0	2670 [330-3890]	4.49
	35+50+71	2.24	3.21	4.55	-	-	10.00 [2.3-10.7]	11.4	2490 [350-2870]	4.02	2.69	3.85	5.46	-	-	12.00 [2.7-14.4]	12.0	2660 [330-3990]	4.51
	35+60+60	2.26	3.87	3.87	-	-	10.00 [2.3-10.7]	11.7	2550 [350-2930]	3.92	2.70	4.65	4.65	-	-	12.00 [2.7-14.4]	12.0	2670 [330-4010]	4.49
	35+60+71	2.11	3.61	4.28	-	-	10.00 [2.3-10.7]	11.4	2490 [350-2870]	4.02	2.53	4.34	5.13	-	-	12.00 [2.7-14.4]	12.0	2660 [330-3990]	4.51
	35+71+71	1.98	4.01	4.01	-	-	10.00 [2.3-10.7]	11.5	2500 [350-2870]	4.00	2.38	4.81	4.81	-	-	12.00 [2.7-14.4]	11.9	2650 [340-3970]	4.53
	42+42+42	3.33	3.33	3.33	-	-	9.99 [2.3-10.7]	14.4	3130 [250-3750]	3.19	4.00	4.00	4.00	-	-	12.00 [2.7-13.8]	13.0	2890 [250-4050]	4.15
	42+42+50	3.13	3.13	3.74	-	-	10.00 [2.3-10.7]	12.6	2740 [280-3260]	3.65	3.76	3.76	4.48	-	-	12.00 [2.7-14.1]	12.3	2730 [280-4020]	4.40
	42+42+60	2.92	2.92	4.16	-	-	10.00 [2.3-10.7]	12.6	2740 [280-3260]	3.65	3.50	3.50	5.00	-	-	12.00 [2.7-14.1]	12.3	2730 [280-4020]	4.40
	42+42+71	2.71	2.71	4.58	-	-	10.00 [2.3-10.7]	12.3	2680 [310-3130]	3.73	3.25	3.25	5.50	-	-	12.00 [2.7-14.4]	12.2	2710 [280-4130]	4.43
	42+50+50	2.96	3.52	3.52	-	-	10.00 [2.3-10.7]	11.7	2550 [350-2930]	3.92	3.54	4.23	4.23	-	-	12.00 [2.7-14.1]	12.0	2670 [330-3870]	4.49
	42+50+60	2.76	3.29	3.95	-	-	10.00 [2.3-10.7]	11.7	2550 [350-2930]	3.92	3.32	3.95	4.73	-	-	12.00 [2.7-14.4]	12.0	2670 [330-3990]	4.49
	42+50+71	2.58	3.07	4.35	-	-	10.00 [2.3-10.7]	11.4	2490 [350-2870]	4.02	3.09	3.68	5.23	-	-	12.00 [2.7-14.4]	11.9	2650 [340-3980]	4.53
	42+60+60	2.60	3.70	3.70	-	-	10.00 [2.3-10.7]	11.7	2550 [350-2930]	3.92	3.12	4.44	4.44	-	-	12.00 [2.7-14.4]	12.0	2670 [330-3990]	4.49
	42+60+71	2.43	3.47	4.10	-	-	10.00 [2.3-10.7]	11.4	2490 [350-2870]	4.02	2.92	4.16	4.92	-	-	12.00 [2.7-14.4]	11.9	2650 [340-3980]	4.53
	50+50+50	3.33	3.33	3.33	-	-	9.99 [2.3-10.7]	10.9	2380 [390-2740]	4.20	4.00	4.00	4.00	-	-	12.00 [2.7-14.4]	11.8	2620 [400-3910]	4.58
	50+50+60	3.13	3.13	3.74	-	-	10.00 [2.3-10.7]	11.2	2440 [390-2740]	4.10	3.75	3.75	4.50	-	-	12.00 [2.7-14.4]	11.8	2620 [400-3910]	4.58
	50+50+71	2.92	2.92	4.16	-	-	10.00 [2.3-10.7]	10.9	2380 [390-2750]	4.20	3.51	3.51	4.98	-	-	12.00 [2.7-14.4]	11.8	2610 [410-3890]	4.60
50+60+60	2.94	3.53	3.53	-	-	10.00 [2.3-10.7]	11.2	2440 [390-2740]	4.10	3.52	4.24	4.24	-	-	12.00 [2.7-14.4]	11.8	2620 [400-3910]	4.58	
50+60+71	2.77	3.31	3.92	-	-	10.00 [2.3-10.7]	10.9	2380 [390-2750]	4.20	3.31	3.98	4.71	-	-	12.00 [2.7-14.4]	11.8	2610 [410-3890]	4.60	
60+60+60	3.33	3.33	3.33	-	-	9.99 [2.3-10.7]	10.9	2380 [390-2740]	4.20	4.00	4.00	4.00	-	-	12.00 [2.7-14.4]	11.8	2620 [400-3910]	4.58	
4 rooms	16+16+16+16	1.60	1.60	1.60	1.60	-	6.40 [2.3-10.6]	6.9	1480 [310-3560]	4.32	2.60	2.60	2.60	2.60	-	10.40 [3.4-14.2]	10.8	2400 [340-4160]	4.33
	16+16+16+20	1.60	1.60	1.60	2.00	-	6.80 [2.3-10.6]	7.5	1620 [310-3560]	4.20	2.59	2.59	2.59	3.23	-	11.00 [3.4-14.2]	11.4	2540 [340-4150]	4.33
	16+16+16+25	1.60	1.60	1.60	2.50	-	7.30 [2.3-10.6]	8.2	1780 [310-3560]	4.10	2.50	2.50	2.50	3.90	-	11.40 [3.4-14.2]	11.7	2600 [340-4150]	4.38
	16+16+16+35	1.60	1.60	1.60	3.50	-	8.30 [2.3-10.6]	10.0	2170 [310-3480]	3.82	2.31	2.31	2.31	5.07	-	12.00 [3.4-14.2]	12.4	2760 [340-4110]	4.35
	16+16+16+42	1.60	1.60	1.60	4.20	-	9.00 [2.3-10.6]	11.3	2460 [310-3480]	3.66	2.13	2.13	2.13	5.61	-	12.00 [3.4-14.2]	12.4	2750 [340-4100]	4.36
	16+16+16+50	1.60	1.60	1.60	5.00	-	9.80 [2.3-10.6]	12.2	2660 [350-3190]	3.68	1.96	1.96	1.96	6.12	-	12.00 [3.4-14.2]	12.1	2690 [390-3950]	4.46
	16+16+16+60	1.48	1.48	1.48	5.56	-	10.00 [2.3-10.6]	12.8	2790 [350-3190]	3.58	1.78	1.78	1.78	6.66	-	12.00 [3.4-14.2]	12.1	2690 [390-3950]	4.46
	16+16+16+71	1.34	1.34	1.34	5.98	-	10.00 [2.3-10.6]	12.5	2730 [380-3120]	3.66	1.61	1.61	1.61	7.17	-	12.00 [3.4-14.2]	12.1	2680 [400-3930]	4.48
	16+16+20+20	1.60	1.60	2.00	2.00	-	7.20 [2.3-10.6]	8.0	1730 [310-3480]	4.16	2.58	2.58	3.22	3.22	-	11.60 [3.4-14.2]	11.8	2630 [340-4130]	4.41
	16+16+20+25	1.60	1.60	2.00	2.50	-	7.70 [2.3-10.6]	8.9	1930 [310-3480]	3.99	2.49	2.49	3.12	3.90	-	12.00 [3.4-14.2]	12.5	2770 [340-4130]	4.33
	16+16+20+35	1.60	1.60	2.00	3.50	-	8.70 [2.3-10.6]	10.7	2330 [310-3410]	3.73	2.21	2.21	2.76	4.82	-	12.00 [3.4-14.2]	12.4	2750 [340-4100]	4.36
	16+16+20+42	1.60	1.60	2.00	4.20	-	9.40 [2.3-10.6]	12.0	2620 [310-3410]	3.59	2.04	2.04	2.56	5.36	-	12.00 [3.4-14.2]	12.3	2740 [340-4080]	4.38
	16+16+20+50	1.57	1.57	1.96	4.90	-	10.00 [2.3-10.6]	12.8	2790 [350-3190]	3.58	1.88	1.88	2.36	5.88	-	12.00 [3.4-14.2]	12.1	2680 [400-3930]	4.48
	16+16+20+60	1.43	1.43	1.79	5.35	-	10.00 [2.3-10.6]	12.8	2790 [350-3190]	3.58	1.71	1.71	2.15	6.43	-	12.00 [3.4-14.2]	12.1	2680 [400-3930]	4.48
	16+16+20+71	1.30	1.30	1.63	5.77	-	10.00 [2.3-10.8]	12.5	2730 [380-3260]	3.66	1.56	1.56	1.95	6.93	-	12.00 [3.4-14.2]	12.0	2670 [400-3920]	4.49
	16+16+25+25	1.60	1.60	2.50	2.50	-	8.20 [2.3-10.6]	9.7	2110 [310-3480]	3.89	2.34	2.34	3.66	3.66	-	12.00 [3.4-14.2]	12.5	2770 [340-4130]	4.33
	16+16+25+35	1.60	1.60	2.50	3.50	-	9.20 [2.3-10.6]	11.7	2560 [310-3410]	3.59	2.09	2.09	3.26	4.56	-	12.00 [3.4-14.2]	12.4	2750 [340-4100]	4.36
	16+16+25+42	1.60	1.60	2.50	4.20	-	9.90 [2.3-10.6]	13.4	2920 [310-3410]	3.39	1.94	1.94	3.03	5.09	-	12.00 [3.4-14.2]	12.3	2740 [340-4080]	4.38
	16+16+25+50	1.50	1.50	2.34	4.66	-	10.00 [2.3-10.6]	12.8	2790 [350-3190]	3.58	1.79	1.79	2.81	5.61	-	12.00 [3.4-14.2]	12.1	2680 [400-3930]	4.48
	16+16+25+60	1.37	1.37	2.14	5.12	-	10.00 [2.3-10.6]	12.8	2790 [350-3190]	3.58	1.64	1.64	2.57	6.15	-	12.00 [3.4-14.2]	12.1	2680 [400-3930]	4.48
16+16+25+71	1.25	1.25	1.95	5.55	-	10.00 [2.3-10.8]	12.5	2730 [380-3260]	3.66	1.50	1.50	2.34	6.66	-	12.00 [3.4-14.4]	12.0	2670 [400-3980]	4.49	
16+16+35+35	1.57	1.57	3.43	3.43	-	10.00 [2.3-10.6]	13.4	2920 [320-3410]	3.42	1.88	1.88	4.12	4.12	-	12.00 [3.4-14.2]	12.2	2720 [360-4060]	4.41	
16+16+35+42	1.47	1.47	3.21	3.85	-	10.00 [2.3-10.6]	13.4	2920 [320-3330]	3.42	1.76	1.76	3.86	4.62	-	12.00 [3.4-14.2]	12.2	2710 [360-3980]	4.43	
16+16+35+50	1.37	1.37	2.99	4.27	-	10.00 [2.3-10.6]	12.5	2730 [380-3120]	3.66	1.64	1.64	3.59	5.13	-	12.00 [3.4-14.2]	12.0	2660 [420-3900]	4.51	
16+16+35+60	1.26	1.26	2.76	4.72	-	10.00 [2.3-10.8]	12.5	2730 [380-3260]	3.66	1.51	1.51	3.31	5.67	-	12.00 [3.4-14.2]	12.0	2660 [420-3900]	4.51	
16+16+35+71	1.16	1.16	2.54	5.14	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.39	1.39	3.05	6.17	-	12.00 [3.4-14.4]	11.9	2650 [420-3940]	4.53	
16+16+42+42	1.38	1.38	3.62	3.62	-	10.00 [2.3-10.6]	13.4	2920 [320-3330]	3.42	1.66	1.66	4.34	4.34	-	12.00 [3.4-14.2]	12.2	2700 [370-3970]	4.44	
16+16+42+50	1.29	1.29																	

CU-5Z100VBR: Only Wall-Mounted Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION								HEATING OPERATION									
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	Total
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
4 rooms	16+16+50+50	1.21	1.21	3.79	3.79	-	10.00 [2.3-10.8]	12.0	2610 [430-3060]	3.83	1.45	1.45	4.55	4.55	-	12.00 [3.4-14.4]	11.8	2610 [490-3870]	4.60
	16+16+50+60	1.13	1.13	3.52	4.22	-	10.00 [2.3-11.0]	12.0	2610 [430-3200]	3.83	1.35	1.35	4.23	5.07	-	12.00 [3.4-14.4]	11.8	2610 [490-3870]	4.60
	16+16+50+71	1.05	1.05	3.27	4.63	-	10.00 [2.3-11.0]	12.0	2610 [460-3200]	3.83	1.25	1.25	3.93	5.57	-	12.00 [3.4-14.4]	11.9	2650 [510-3860]	4.53
	16+16+60+60	1.05	1.05	3.95	3.95	-	10.00 [2.3-11.0]	12.0	2610 [430-3200]	3.83	1.26	1.26	4.74	4.74	-	12.00 [3.4-14.4]	11.8	2610 [490-3870]	4.60
	16+16+60+71	0.98	0.98	3.68	4.36	-	10.00 [2.3-11.2]	12.0	2610 [460-3280]	3.83	1.18	1.18	4.42	5.22	-	12.00 [3.4-14.4]	11.9	2650 [510-3860]	4.53
	16+16+71+71	0.92	0.92	4.08	4.08	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.10	1.10	4.90	4.90	-	12.00 [3.4-14.4]	11.9	2640 [510-3900]	4.55
	16+20+20+20	1.60	2.00	2.00	2.00	-	7.60 [2.3-10.6]	8.7	1900 [310-3480]	4.00	2.52	3.16	3.16	3.16	-	12.00 [3.4-14.2]	12.4	2760 [340-4120]	4.35
	16+20+20+25	1.60	2.00	2.00	2.50	-	8.10 [2.3-10.6]	9.4	2050 [310-3480]	3.95	2.38	2.96	2.96	3.70	-	12.00 [3.4-14.2]	12.4	2760 [340-4120]	4.35
	16+20+20+35	1.60	2.00	2.00	3.50	-	9.10 [2.3-10.6]	11.4	2490 [310-3410]	3.65	2.11	2.64	2.64	4.61	-	12.00 [3.4-14.2]	12.3	2740 [340-4080]	4.38
	16+20+20+42	1.60	2.00	2.00	4.20	-	9.80 [2.3-10.6]	12.8	2790 [310-3410]	3.51	1.96	2.45	2.45	5.14	-	12.00 [3.4-14.2]	12.3	2730 [350-4070]	4.40
	16+20+20+50	1.51	1.89	1.89	4.71	-	10.00 [2.3-10.6]	12.5	2730 [360-3120]	3.66	1.82	2.26	2.26	5.66	-	12.00 [3.4-14.2]	12.0	2670 [400-3920]	4.49
	16+20+20+60	1.39	1.72	1.72	5.17	-	10.00 [2.3-10.6]	12.5	2730 [360-3120]	3.66	1.66	2.07	2.07	6.20	-	12.00 [3.4-14.2]	12.0	2670 [400-3920]	4.49
	16+20+20+71	1.27	1.57	1.57	5.59	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.51	1.89	1.89	6.71	-	12.00 [3.4-14.2]	12.0	2660 [420-3900]	4.51
	16+20+25+25	1.60	2.00	2.50	2.50	-	8.60 [2.3-10.6]	10.5	2290 [310-3480]	3.76	2.23	2.79	3.49	3.49	-	12.00 [3.4-14.2]	12.4	2760 [340-4120]	4.35
	16+20+25+35	1.60	2.00	2.50	3.50	-	9.60 [2.3-10.6]	12.5	2720 [310-3410]	3.53	2.00	2.50	3.13	4.37	-	12.00 [3.4-14.2]	12.3	2740 [340-4080]	4.38
	16+20+25+42	1.55	1.94	2.43	4.08	-	10.00 [2.3-10.6]	13.4	2920 [310-3410]	3.42	1.87	2.33	2.91	4.89	-	12.00 [3.4-14.2]	12.3	2730 [350-4070]	4.40
	16+20+25+50	1.45	1.80	2.25	4.50	-	10.00 [2.3-10.6]	12.5	2730 [360-3120]	3.66	1.73	2.16	2.70	5.41	-	12.00 [3.4-14.2]	12.0	2670 [400-3920]	4.49
	16+20+25+60	1.32	1.65	2.07	4.96	-	10.00 [2.3-10.8]	12.5	2730 [360-3260]	3.66	1.59	1.98	2.48	5.95	-	12.00 [3.4-14.2]	12.0	2670 [400-3920]	4.49
	16+20+25+71	1.21	1.52	1.89	5.38	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.46	1.82	2.27	6.45	-	12.00 [3.4-14.4]	12.0	2660 [420-3960]	4.51
	16+20+35+35	1.51	1.89	3.30	3.30	-	10.00 [2.3-10.6]	13.4	2920 [320-3330]	3.42	1.82	2.26	3.96	3.96	-	12.00 [3.4-14.2]	12.2	2710 [360-3980]	4.43
	16+20+35+42	1.42	1.77	3.10	3.71	-	10.00 [2.3-10.6]	13.4	2920 [320-3330]	3.42	1.70	2.12	3.72	4.46	-	12.00 [3.4-14.2]	12.2	2700 [370-3970]	4.44
	16+20+35+50	1.33	1.65	2.89	4.13	-	10.00 [2.3-10.8]	12.5	2730 [380-3260]	3.66	1.59	1.98	3.47	4.96	-	12.00 [3.4-14.2]	11.9	2650 [420-3890]	4.53
	16+20+35+60	1.22	1.53	2.67	4.58	-	10.00 [2.3-10.8]	12.5	2730 [380-3260]	3.66	1.47	1.83	3.21	5.49	-	12.00 [3.4-14.4]	11.9	2650 [420-3950]	4.53
	16+20+35+71	1.13	1.41	2.46	5.00	-	10.00 [2.3-11.0]	12.2	2660 [390-3340]	3.76	1.35	1.69	2.96	6.00	-	12.00 [3.4-14.4]	11.9	2640 [430-3930]	4.55
	16+20+42+42	1.33	1.67	3.50	3.50	-	10.00 [2.3-10.6]	13.1	2860 [320-3330]	3.50	1.60	2.00	4.20	4.20	-	12.00 [3.4-14.2]	12.1	2690 [370-3960]	4.46
	16+20+42+50	1.25	1.56	3.28	3.91	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.50	1.88	3.94	4.68	-	12.00 [3.4-14.4]	11.9	2640 [420-3930]	4.55
	16+20+42+60	1.16	1.45	3.04	4.35	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.39	1.74	3.65	5.22	-	12.00 [3.4-14.4]	11.9	2640 [420-3930]	4.55
	16+20+42+71	1.07	1.34	2.82	4.77	-	10.00 [2.3-11.0]	12.2	2660 [390-3270]	3.76	1.29	1.61	3.38	5.72	-	12.00 [3.4-14.4]	11.8	2630 [430-3920]	4.56
	16+20+50+50	1.18	1.47	3.68	3.67	-	10.00 [2.3-10.8]	12.0	2610 [430-3060]	3.83	1.42	1.76	4.41	4.41	-	12.00 [3.4-14.4]	11.9	2650 [500-3860]	4.53
	16+20+50+60	1.10	1.37	3.42	4.11	-	10.00 [2.3-11.0]	12.0	2610 [430-3200]	3.83	1.32	1.64	4.11	4.93	-	12.00 [3.4-14.4]	11.9	2650 [500-3860]	4.53
	16+20+50+71	1.03	1.27	3.18	4.52	-	10.00 [2.3-11.0]	12.0	2610 [470-3130]	3.83	1.22	1.53	3.82	5.43	-	12.00 [3.4-14.4]	11.9	2640 [510-3900]	4.55
	16+20+60+60	1.03	1.27	3.85	3.85	-	10.00 [2.3-11.0]	12.0	2610 [430-3200]	3.83	1.23	1.53	4.62	4.62	-	12.00 [3.4-14.4]	11.9	2650 [500-3860]	4.53
	16+20+60+71	0.96	1.20	3.59	4.25	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.15	1.44	4.31	5.10	-	12.00 [3.4-14.4]	11.9	2640 [510-3900]	4.55
	16+20+71+71	0.90	1.12	3.99	3.99	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.08	1.34	4.79	4.79	-	12.00 [3.4-14.4]	11.8	2630 [520-3890]	4.56
	16+25+25+25	1.60	2.50	2.50	2.50	-	9.10 [2.3-10.6]	11.4	2490 [310-3480]	3.65	2.10	3.30	3.30	3.30	-	12.00 [3.4-14.2]	12.4	2760 [340-4120]	4.35
	16+25+25+35	1.58	2.48	2.48	3.46	-	10.00 [2.3-10.6]	13.4	2920 [310-3410]	3.42	1.90	2.97	2.97	4.16	-	12.00 [3.4-14.2]	12.3	2740 [340-4080]	4.38
	16+25+25+42	1.49	2.31	2.31	3.89	-	10.00 [2.3-10.6]	13.4	2920 [310-3410]	3.42	1.78	2.78	2.78	4.66	-	12.00 [3.4-14.2]	12.3	2730 [350-4070]	4.40
	16+25+25+50	1.38	2.16	2.16	4.30	-	10.00 [2.3-10.6]	12.5	2730 [360-3120]	3.66	1.66	2.59	2.59	5.16	-	12.00 [3.4-14.2]	12.0	2670 [400-3920]	4.49
	16+25+25+60	1.28	1.98	1.98	4.76	-	10.00 [2.3-10.8]	12.5	2730 [360-3260]	3.66	1.53	2.38	2.38	5.71	-	12.00 [3.4-14.2]	12.0	2670 [400-3920]	4.49
	16+25+25+71	1.18	1.82	1.82	5.18	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.40	2.19	2.19	6.22	-	12.00 [3.4-14.4]	12.0	2660 [420-3960]	4.51
	16+25+35+35	1.45	2.25	3.15	3.15	-	10.00 [2.3-10.6]	13.4	2920 [320-3330]	3.42	1.74	2.70	3.78	3.78	-	12.00 [3.4-14.2]	12.2	2710 [360-3980]	4.43
	16+25+35+42	1.36	2.12	2.97	3.55	-	10.00 [2.3-10.6]	13.4	2920 [320-3330]	3.42	1.63	2.54	3.56	4.27	-	12.00 [3.4-14.2]	12.2	2700 [370-3970]	4.44
	16+25+35+50	1.27	1.98	2.78	3.97	-	10.00 [2.3-10.8]	12.5	2730 [380-3260]	3.66	1.53	2.38	3.33	4.76	-	12.00 [3.4-14.2]	11.9	2650 [420-3890]	4.53
	16+25+35+60	1.18	1.84	2.57	4.41	-	10.00 [2.3-10.8]	12.5	2730 [380-3260]	3.66	1.41	2.21	3.09	5.29	-	12.00 [3.4-14.4]	11.9	2650 [430-3950]	4.53
	16+25+35+71	1.09	1.70	2.38	4.83	-	10.00 [2.3-11.0]	12.2	2660 [390-3340]	3.76	1.31	2.04	2.86	5.79	-	12.00 [3.4-14.4]	11.9	2640 [430-3930]	4.55
	16+25+42+42	1.28	2.00	3.36	3.36	-	10.00 [2.3-10.8]	13.1	2860 [320-3480]	3.50	1.54	2.40	4.03	4.03	-	12.00 [3.4-14.2]	12.1	2690 [370-3960]	4.46
	16+25+42+50	1.20	1.88	3.16	3.76	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.44	2.26	3.79	4.51	-	12.00 [3.4-14.4]	11.9	2640 [420-3930]	4.55
	16+25+42+60	1.12	1.75	2.94	4.19	-	10.00 [2.3-11.0]	12.5	2730 [390-3340]	3.66	1.35	2.10	3.52	5.					

CU-5Z100VBR: Only Wall-Mounted Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION								HEATING OPERATION									
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
4 rooms	16+35+42+71	0.98	2.13	2.56	4.33	-	10.00 [2.3-11.2]	12.2	2670 [400-3410]	3.75	1.17	2.56	3.07	5.20	-	12.00 [3.4-14.4]	11.9	2650 [450-3940]	4.53
	16+35+50+50	1.06	2.32	3.31	3.31	-	10.00 [2.3-11.0]	12.0	2610 [470-3130]	3.83	1.28	2.78	3.97	3.97	-	12.00 [3.4-14.4]	11.8	2630 [520-3890]	4.56
	16+35+50+60	0.99	2.17	3.11	3.73	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.19	2.61	3.73	4.47	-	12.00 [3.4-14.4]	11.8	2630 [520-3890]	4.56
	16+35+50+71	0.93	2.03	2.91	4.13	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.12	2.44	3.49	4.95	-	12.00 [3.4-14.4]	11.8	2620 [540-3880]	4.58
	16+35+60+60	0.93	2.05	3.51	3.51	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.12	2.46	4.21	4.21	-	12.00 [3.4-14.4]	11.8	2630 [520-3890]	4.56
	16+35+60+71	0.88	1.92	3.30	3.90	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.05	2.31	3.96	4.68	-	12.00 [3.4-14.4]	11.8	2620 [540-3880]	4.58
	16+42+42+42	1.12	2.96	2.96	2.96	-	10.00 [2.3-11.0]	13.1	2860 [350-3560]	3.50	1.35	3.55	3.55	3.55	-	12.00 [3.4-14.4]	12.2	2700 [390-4030]	4.44
	16+42+42+50	1.07	2.80	2.80	3.33	-	10.00 [2.3-11.0]	12.2	2660 [390-3270]	3.76	1.28	3.36	3.36	4.00	-	12.00 [3.4-14.4]			

CU-5Z100VBR: Only Wall-Mounted Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	Total
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
4 rooms	20+25+60+71	1.14	1.42	3.41	4.03	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.37	1.70	4.09	4.84	-	12.00 [3.4-14.4]	11.8	2630 [520-3890]	4.56
	20+35+35+35	1.60	2.80	2.80	2.80	-	10.00 [2.3-10.8]	13.1	2860 [350-3410]	3.50	1.92	3.36	3.36	3.36	-	12.00 [3.4-14.2]	12.1	2680 [370-3940]	4.48
	20+35+35+42	1.52	2.65	2.65	3.18	-	10.00 [2.3-10.8]	13.1	2860 [350-3410]	3.50	1.82	3.18	3.18	3.82	-	12.00 [3.4-14.4]	12.2	2710 [370-4040]	4.43
	20+35+35+50	1.43	2.50	2.50	3.57	-	10.00 [2.3-10.8]	12.2	2660 [390-3190]	3.76	1.71	3.00	3.00	4.29	-	12.00 [3.4-14.4]	11.8	2620 [450-3960]	4.58
	20+35+35+60	1.34	2.33	2.33	4.00	-	10.00 [2.3-11.0]	12.2	2660 [390-3340]	3.76	1.60	2.80	2.80	4.80	-	12.00 [3.4-14.4]	11.8	2620 [450-3960]	4.58
	20+35+35+71	1.25	2.17	2.17	4.41	-	10.00 [2.3-11.2]	12.2	2670 [420-3410]	3.75	1.49	2.61	2.61	5.29	-	12.00 [3.4-14.4]	11.9	2650 [450-3940]	4.53
	20+35+42+42	1.44	2.52	3.02	3.02	-	10.00 [2.3-10.8]	13.1	2860 [350-3410]	3.50	1.73	3.01	3.63	3.63	-	12.00 [3.4-14.4]	12.2	2700 [390-4030]	4.44
	20+35+42+50	1.36	2.38	2.86	3.40	-	10.00 [2.3-11.0]	12.2	2660 [390-3270]	3.76	1.63	2.86	3.43	4.08	-	12.00 [3.4-14.4]	12.0	2660 [450-3950]	4.51
	20+35+42+60	1.27	2.23	2.68	3.82	-	10.00 [2.3-11.0]	12.2	2660 [390-3270]	3.76	1.53	2.68	3.21	4.58	-	12.00 [3.4-14.4]	12.0	2660 [450-3950]	4.51
	20+35+42+71	1.19	2.08	2.50	4.23	-	10.00 [2.3-11.2]	12.2	2670 [420-3420]	3.75	1.43	2.50	3.00	5.07	-	12.00 [3.4-14.4]	11.9	2650 [460-3930]	4.53
	20+35+50+50	1.29	2.25	3.23	3.23	-	10.00 [2.3-11.0]	12.0	2610 [470-3130]	3.83	1.55	2.71	3.87	3.87	-	12.00 [3.4-14.4]	11.8	2630 [530-3880]	4.56
	20+35+50+60	1.21	2.12	3.03	3.64	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.45	2.55	3.64	4.36	-	12.00 [3.4-14.4]	11.8	2630 [530-3880]	4.56
	20+35+50+71	1.14	1.99	2.84	4.03	-	10.00 [2.3-11.2]	12.0	2620 [480-3280]	3.82	1.36	2.39	3.41	4.84	-	12.00 [3.4-14.4]	11.8	2620 [540-3870]	4.58
	20+35+60+60	1.14	2.00	3.43	3.43	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.38	2.40	4.11	4.11	-	12.00 [3.4-14.4]	11.8	2630 [530-3880]	4.56
	20+42+42+42	1.36	2.88	2.88	2.88	-	10.00 [2.3-11.0]	12.8	2790 [350-3480]	3.58	1.65	3.45	3.45	3.45	-	12.00 [3.4-14.4]	12.2	2700 [390-4020]	4.44
	20+42+42+50	1.30	2.73	2.73	3.24	-	10.00 [2.3-11.0]	12.2	2660 [390-3270]	3.76	1.56	3.27	3.27	3.90	-	12.00 [3.4-14.4]	11.9	2650 [450-3940]	4.53
	20+42+42+60	1.22	2.56	2.56	3.66	-	10.00 [2.3-11.2]	12.2	2660 [390-3410]	3.76	1.47	3.07	3.07	4.39	-	12.00 [3.4-14.4]	11.9	2650 [450-3940]	4.53
	20+42+42+71	1.14	2.40	2.40	4.06	-	10.00 [2.3-11.2]	12.2	2670 [420-3340]	3.75	1.37	2.88	2.88	4.87	-	12.00 [3.4-14.4]	11.9	2640 [460-3920]	4.55
	20+42+50+50	1.23	2.59	3.09	3.09	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.49	3.11	3.70	3.70	-	12.00 [3.4-14.4]	11.8	2620 [540-3870]	4.58
	20+42+50+60	1.16	2.44	2.91	3.49	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.40	2.93	3.49	4.18	-	12.00 [3.4-14.4]	11.8	2620 [540-3870]	4.58
	20+42+50+71	1.09	2.30	2.73	3.88	-	10.00 [2.3-11.2]	12.0	2620 [480-3210]	3.82	1.31	2.75	3.28	4.66	-	12.00 [3.4-14.4]	12.0	2660 [550-3860]	4.51
	20+42+60+60	1.10	2.30	3.30	3.30	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.32	2.76	3.96	3.96	-	12.00 [3.4-14.4]	11.8	2620 [540-3870]	4.58
	20+50+50+50	1.18	2.94	2.94	2.94	-	10.00 [2.3-11.2]	11.8	2570 [550-3220]	3.89	1.41	3.53	3.53	3.53	-	12.00 [3.4-14.4]	12.1	2690 [630-3870]	4.46
	20+50+50+60	1.11	2.78	2.78	3.33	-	10.00 [2.3-11.2]	11.8	2570 [550-3220]	3.89	1.34	3.33	3.33	4.00	-	12.00 [3.4-14.4]	12.1	2690 [630-3870]	4.46
	25+25+25+25	2.50	2.50	2.50	2.50	-	10.00 [2.3-10.6]	13.7	2990 [310-3480]	3.34	3.00	3.00	3.00	3.00	-	12.00 [3.4-14.2]	12.4	2750 [340-4110]	4.36
	25+25+25+35	2.27	2.27	2.27	3.19	-	10.00 [2.3-10.6]	13.4	2920 [320-3410]	3.42	2.73	2.73	2.73	3.81	-	12.00 [3.4-14.2]	12.3	2730 [350-4070]	4.40
	25+25+25+42	2.14	2.14	2.14	3.58	-	10.00 [2.3												

CU-5Z100VBR: Only Wall-Mounted Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
4 rooms	25+50+50+50	1.42	2.86	2.86	2.86	-	10.00 [2.3-11.2]	11.8	2570 [550-3220]	3.89	1.71	3.43	3.43	3.43	-	12.00 [3.4-14.4]	12.1	2690 [630-3870]	4.46
	35+35+35+35	2.50	2.50	2.50	2.50	-	10.00 [2.3-10.8]	12.8	2790 [350-3330]	3.58	3.00	3.00	3.00	3.00	-	12.00 [3.4-14.4]	12.2	2700 [390-4020]	4.44
	35+35+35+42	2.38	2.38	2.38	2.86	-	10.00 [2.3-11.0]	12.8	2790 [350-3480]	3.58	2.86	2.86	2.86	3.42	-	12.00 [3.4-14.4]	12.1	2690 [390-4010]	4.46
	35+35+35+50	2.26	2.26	2.26	3.22	-	10.00 [2.3-11.0]	12.2	2660 [390-3270]	3.76	2.71	2.71	2.71	3.87	-	12.00 [3.4-14.4]	11.9	2650 [460-3930]	4.53
	35+35+35+60	2.12	2.12	2.12	3.64	-	10.00 [2.3-11.2]	12.2	2660 [390-3410]	3.76	2.55	2.55	2.55	4.35	-	12.00 [3.4-14.4]	11.9	2650 [460-3930]	4.53
	35+35+35+71	1.99	1.99	1.99	4.03	-	10.00 [2.3-11.2]	12.2	2670 [430-3340]	3.75	2.39	2.39	2.39	4.83	-	12.00 [3.4-14.4]	11.9	2640 [470-3910]	4.55
	35+35+42+42	2.27	2.27	2.73	2.73	-	10.00 [2.3-11.0]	12.8	2790 [350-3480]	3.58	2.73	2.73	3.27	3.27	-	12.00 [3.4-14.4]	12.1	2680 [400-4000]	4.48
	35+35+42+50	2.16	2.16	2.59	3.09	-	10.00 [2.3-11.2]	12.2	2670 [420-3410]	3.75	2.59	2.59	3.12	3.70	-	12.00 [3.4-14.4]	11.9	2640 [470-3920]	4.55
	35+35+42+60	2.03	2.03	2.45	3.49	-	10.00 [2.3-11.2]	12.2	2670 [420-3410]	3.75	2.44	2.44	2.93	4.19	-	12.00 [3.4-14.4]	11.9	2640 [470-3920]	4.55
	35+35+42+71	1.91	1.91	2.30	3.88	-	10.00 [2.3-11.2]	12.2	2670 [430-3340]	3.75	2.30	2.30	2.75	4.65	-	12.00 [3.4-14.4]	11.8	2630 [480-3900]	4.56
	35+35+50+50	2.06	2.06	2.94	2.94	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	2.47	2.47	3.53	3.53	-	12.00 [3.4-14.4]	11.9	2650 [550-3850]	4.53
	35+35+50+60	1.94	1.94	2.79	3.33	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	2.33	2.33	3.33	4.01	-	12.00 [3.4-14.4]	11.9	2650 [550-3850]	4.53
	35+42+42+42	2.17	2.61	2.61	2.61	-	10.00 [2.3-11.2]	12.8	2790 [350-3640]	3.58	2.61	3.13	3.13	3.13	-	12.00 [3.4-14.4]	12.0	2670 [400-3980]	4.49
	35+42+42+50	2.07	2.49	2.49	2.95	-	10.00 [2.3-11.2]	12.2	2670 [420-3420]	3.75	2.49	2.98	2.98	3.55	-	12.00 [3.4-14.4]	11.8	2630 [480-3900]	4.56
	35+42+42+60	1.96	2.35	2.35	3.34	-	10.00 [2.3-11.2]	12.2	2670 [420-3420]	3.75	2.35	2.82	2.82	4.01	-	12.00 [3.4-14.4]	11.8	2630 [480-3900]	4.56
	35+42+50+50	1.99	2.37	2.82	2.82	-	10.00 [2.3-11.2]	12.0	2620 [470-3280]	3.82	2.37	2.85	3.39	3.39	-	12.00 [3.4-14.4]	11.9	2650 [560-3840]	4.53
42+42+42+42	2.50	2.50	2.50	2.50	-	10.00 [2.3-11.2]	12.8	2790 [350-3560]	3.58	3.00	3.00	3.00	3.00	-	12.00 [3.4-14.4]	12.0	2660 [400-3970]	4.51	
42+42+42+50	2.39	2.39	2.39	2.83	-	10.00 [2.3-11.2]	12.2	2670 [420-3340]	3.75	2.86	2.86	2.86	3.42	-	12.00 [3.4-14.4]	11.8	2620 [480-3890]	4.58	
5 rooms	16+16+16+16+16	1.60	1.60	1.60	1.60	1.60	8.00 [2.3-11.5]	8.4	1840 [390-3660]	4.35	2.40	2.40	2.40	2.40	2.40	12.00 [3.4-14.5]	12.0	2750 [540-4020]	4.36
	16+16+16+16+20	1.60	1.60	1.60	1.60	2.00	8.40 [2.3-11.5]	8.9	1950 [390-3660]	4.31	2.29	2.29	2.29	2.29	2.84	12.00 [3.4-14.5]	12.0	2740 [560-4010]	4.38
	16+16+16+16+25	1.60	1.60	1.60	1.60	2.50	8.90 [2.3-11.5]	9.6	2120 [390-3660]	4.20	2.16	2.16	2.16	2.16	3.36	12.00 [3.4-14.5]	12.0	2740 [560-4010]	4.38
	16+16+16+16+35	1.60	1.60	1.60	1.60	3.50	9.90 [2.3-11.5]	11.5	2540 [420-3590]	3.90	1.94	1.94	1.94	1.94	4.24	12.00 [3.4-14.5]	12.1	2770 [570-3970]	4.33
	16+16+16+16+42	1.51	1.51	1.51	1.51	3.96	10.00 [2.3-11.5]	11.8	2600 [430-3590]	3.85	1.81	1.81	1.81	1.81	4.76	12.00 [3.4-14.5]	12.1	2760 [580-4020]	4.35
	16+16+16+16+50	1.40	1.40	1.40	1.40	4.40	10.00 [2.3-11.5]	11.6	2550 [480-3450]	3.92	1.68	1.68	1.68	1.68	5.28	12.00 [3.4-14.5]	12.2	2780 [680-3950]	4.32
	16+16+16+16+60	1.29	1.29	1.29	1.29	4.84	10.00 [2.3-11.5]	11.6	2550 [480-3450]	3.92	1.55	1.55	1.55	1.55	5.80	12.00 [3.4-14.5]	12.2	2780 [680-3950]	4.32
	16+16+16+16+71	1.19	1.19	1.19	1.19	5.24	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.42	1							

CU-5Z100VBR: Only Wall-Mounted Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
5 rooms	16+16+20+20+20	1.60	1.60	2.00	2.00	2.00	9.20 [2.3-11.5]	10.2	2240 [420-3590]	4.11	2.10	2.10	2.60	2.60	2.60	12.00 [3.4-14.5]	12.1	2770 [570-3980]	4.33
	16+16+20+20+25	1.60	1.60	2.00	2.00	2.50	9.70 [2.3-11.5]	11.3	2480 [420-3590]	3.91	1.98	1.98	2.47	2.47	3.10	12.00 [3.4-14.5]	12.1	2770 [570-3980]	4.33
	16+16+20+20+35	1.50	1.50	1.87	1.87	3.26	10.00 [2.3-11.5]	11.8	2600 [430-3590]	3.85	1.79	1.79	2.24	2.24	3.94	12.00 [3.4-14.5]	12.0	2750 [600-4010]	4.36
	16+16+20+20+42	1.41	1.41	1.75	1.75	3.68	10.00 [2.3-11.5]	11.8	2600 [430-3510]	3.85	1.68	1.68	2.11	2.11	4.42	12.00 [3.4-14.5]	12.0	2750 [600-4000]	4.36
	16+16+20+20+50	1.31	1.31	1.64	1.64	4.10	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.57	1.57	1.97	1.97	4.92	12.00 [3.4-14.5]	12.1	2770 [710-3930]	4.33
	16+16+20+20+60	1.21	1.21	1.52	1.52	4.54	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.45	1.45	1.82	1.82	5.46	12.00 [3.4-14.5]	12.1	2770 [710-3930]	4.33
	16+16+20+20+71	1.12	1.12	1.40	1.40	4.96	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.34	1.34	1.68	1.68	5.96	12.00 [3.4-14.5]	12.1	2760 [720-3920]	4.35
	16+16+20+25+25	1.57	1.57	1.96	2.45	2.45	10.00 [2.3-11.5]	11.8	2600 [420-3590]	3.85	1.88	1.88	2.36	2.94	2.94	12.00 [3.4-14.5]	12.1	2770 [570-3980]	4.33
	16+16+20+25+35	1.43	1.43	1.79	2.23	3.12	10.00 [2.3-11.5]	11.8	2600 [430-3590]	3.85	1.71	1.71	2.15	2.68	3.75	12.00 [3.4-14.5]	12.0	2750 [600-4010]	4.36
	16+16+20+25+42	1.34	1.34	1.69	2.10	3.53	10.00 [2.3-11.5]	11.8	2600 [430-3510]	3.85	1.61	1.61	2.02	2.52	4.24	12.00 [3.4-14.5]	12.0	2750 [600-4000]	4.36
	16+16+20+25+50	1.26	1.26	1.57	1.97	3.94	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.51	1.51	1.90	2.36	4.72	12.00 [3.4-14.5]	12.1	2770 [710-3930]	4.33
	16+16+20+25+60	1.17	1.17	1.46	1.82	4.38	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.40	1.40	1.75	2.19	5.26	12.00 [3.4-14.5]	12.1	2770 [710-3930]	4.33
	16+16+20+25+71	1.08	1.08	1.35	1.69	4.80	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.30	1.30	1.62	2.03	5.75	12.00 [3.4-14.5]	12.1	2760 [720-3920]	4.35
	16+16+20+35+35	1.31	1.31	1.64	2.87	2.87	10.00 [2.3-11.5]	11.5	2540 [430-3510]	3.94	1.57	1.57	1.98	3.44	3.44	12.00 [3.4-14.5]	12.0	2740 [610-3980]	4.38
	16+16+20+35+42	1.24	1.24	1.55	2.71	3.26	10.00 [2.3-11.5]	11.5	2540 [430-3510]	3.94	1.49	1.49	1.86	3.26	3.90	12.00 [3.4-14.5]	11.9	2730 [630-3970]	4.40
	16+16+20+35+50	1.17	1.17	1.46	2.55	3.65	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.40	1.40	1.75	3.07	4.38	12.00 [3.4-14.5]	12.0	2750 [740-3960]	4.36
	16+16+20+35+60	1.09	1.09	1.36	2.38	4.08	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.31	1.31	1.63	2.86	4.89	12.00 [3.4-14.5]	12.0	2750 [740-3960]	4.36
	16+16+20+35+71	1.01	1.01	1.27	2.22	4.49	10.00 [2.3-11.5]	11.4	2500 [520-3390]	4.00	1.22	1.22	1.52	2.66	5.38	12.00 [3.4-14.5]	12.2	2790 [750-3950]	4.30
	16+16+20+42+42	1.18	1.18	1.46	3.09	3.09	10.00 [2.3-11.5]	11.5	2540 [440-3520]	3.94	1.41	1.41	1.76	3.71	3.71	12.00 [3.4-14.5]	12.1	2770 [640-3960]	4.33
	16+16+20+42+50	1.11	1.11	1.39	2.92	3.47	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.33	1.33	1.67	3.50	4.17	12.00 [3.4-14.5]	12.2	2790 [750-3950]	4.30
	16+16+20+42+60	1.04	1.04	1.30	2.73	3.89	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.25	1.25	1.56	3.27	4.67	12.00 [3.4-14.5]	12.2	2790 [750-3950]	4.30
	16+16+20+42+71	0.97	0.97	1.21	2.55	4.30	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.17	1.17	1.45	3.05	5.16	12.00 [3.4-14.5]	12.2	2780 [760-3940]	4.32
	16+16+20+50+50	1.05	1.05	1.32	3.29	3.29	10.00 [2.3-11.5]	11.5	2520 [610-3330]	3.97	1.26	1.26	1.58	3.95	3.95	12.00 [3.4-14.5]	12.4	2830 [870-3970]	4.24
	16+16+20+50+60	0.99	0.99	1.23	3.09	3.70	10.00 [2.3-11.5]	11.5	2520 [610-3330]	3.97	1.19	1.19	1.48	3.70	4.44	12.00 [3.4-14.5]	12.4	2830 [870-3970]	4.24
	16+16+20+50+71	0.92	0.92	1.17	2.89	4.10	10.00 [2.3-11.5]	11.5	2530 [620-3340]	3.95	1.11	1.11	1.39	3.47	4.92				

CU-5Z100VBR: Only Wall-Mounted Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION								HEATING OPERATION									
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
5 rooms	16+20+20+20+25	1.58	1.98	1.98	1.98	2.48	10.00 [2.3-11.5]	11.8	2600 [420-3590]	3.85	1.90	2.38	2.38	2.38	2.96	12.00 [3.4-14.5]	12.1	2770 [570-4030]	4.33
	16+20+20+20+35	1.45	1.80	1.80	1.80	3.15	10.00 [2.3-11.5]	11.8	2600 [430-3510]	3.85	1.74	2.16	2.16	2.16	3.78	12.00 [3.4-14.5]	12.0	2750 [600-4000]	4.36
	16+20+20+20+42	1.37	1.69	1.69	1.69	3.56	10.00 [2.3-11.5]	11.5	2540 [430-3510]	3.94	1.64	2.03	2.03	2.03	4.27	12.00 [3.4-14.5]	12.0	2740 [610-3990]	4.38
	16+20+20+20+50	1.27	1.59	1.59	1.59	3.96	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.53	1.90	1.90	1.90	4.77	12.00 [3.4-14.5]	12.1	2760 [720-3920]	4.35
	16+20+20+20+60	1.18	1.47	1.47	1.47	4.41	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.42	1.76	1.76	1.76	5.30	12.00 [3.4-14.5]	12.1	2760 [720-3920]	4.35
	16+20+20+20+71	1.09	1.36	1.36	1.36	4.83	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.31	1.63	1.63	1.63	5.80	12.00 [3.4-14.5]	12.0	2750 [730-3970]	4.36
	16+20+20+25+25	1.50	1.89	1.89	2.36	2.36	10.00 [2.3-11.5]	11.8	2600 [420-3590]	3.85	1.82	2.26	2.26	2.83	2.83	12.00 [3.4-14.5]	12.1	2770 [570-4030]	4.33
	16+20+20+25+35	1.38	1.72	1.72	2.16	3.02	10.00 [2.3-11.5]	11.8	2600 [430-3510]	3.85	1.66	2.07	2.07	2.59	3.61	12.00 [3.4-14.5]	12.0	2750 [600-4000]	4.36
	16+20+20+25+42	1.30	1.63	1.63	2.03	3.41	10.00 [2.3-11.5]	11.5	2540 [430-3510]	3.94	1.56	1.95	1.95	2.44	4.10	12.00 [3.4-14.5]	12.0	2740 [610-3990]	4.38
	16+20+20+25+50	1.22	1.53	1.53	1.91	3.81	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.47	1.83	1.83	2.29	4.58	12.00 [3.4-14.5]	12.1	2760 [720-3920]	4.35
	16+20+20+25+60	1.13	1.42	1.42	1.77	4.26	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.36	1.70	1.70	2.13	5.11	12.00 [3.4-14.5]	12.1	2760 [720-3920]	4.35
	16+20+20+25+71	1.05	1.32	1.32	1.64	4.67	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.26	1.58	1.58	1.97	5.61	12.00 [3.4-14.5]	12.0	2750 [730-3970]	4.36
	16+20+20+35+35	1.26	1.59	1.59	2.78	2.78	10.00 [2.3-11.5]	11.5	2540 [440-3510]	3.94	1.52	1.90	1.90	3.34	3.34	12.00 [3.4-14.5]	11.9	2730 [630-3970]	4.40
	16+20+20+35+42	1.21	1.50	1.50	2.63	3.16	10.00 [2.3-11.5]	11.5	2540 [440-3520]	3.94	1.45	1.80	1.80	3.16	3.79	12.00 [3.4-14.5]	12.1	2770 [640-3960]	4.33
	16+20+20+35+50	1.13	1.42	1.42	2.48	3.55	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.36	1.70	1.70	2.98	4.26	12.00 [3.4-14.5]	12.2	2790 [750-3950]	4.30
	16+20+20+35+60	1.07	1.32	1.32	2.32	3.97	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.27	1.59	1.59	2.78	4.77	12.00 [3.4-14.5]	12.2	2790 [750-3950]	4.30
	16+20+20+35+71	1.00	1.23	1.23	2.16	4.38	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.19	1.48	1.48	2.59	5.26	12.00 [3.4-14.5]	12.2	2780 [760-3940]	4.32
	16+20+20+42+42	1.14	1.43	1.43	3.00	3.00	10.00 [2.3-11.5]	11.6	2550 [460-3520]	3.92	1.38	1.71	1.71	3.60	3.60	12.00 [3.4-14.5]	12.1	2760 [640-3950]	4.35
	16+20+20+42+50	1.08	1.35	1.35	2.84	3.38	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.30	1.62	1.62	3.41	4.05	12.00 [3.4-14.5]	12.2	2790 [760-3950]	4.30
	16+20+20+42+60	1.01	1.27	1.27	2.66	3.79	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.22	1.52	1.52	3.19	4.55	12.00 [3.4-14.5]	12.2	2790 [760-3950]	4.30
	16+20+20+42+71	0.95	1.18	1.18	2.49	4.20	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.14	1.42	1.42	2.98	5.04	12.00 [3.4-14.5]	12.2	2780 [780-3930]	4.32
	16+20+20+50+50	1.02	1.28	1.28	3.21	3.21	10.00 [2.3-11.5]	11.5	2530 [610-3330]	3.95	1.22	1.54	1.54	3.85	3.85	12.00 [3.4-14.5]	12.6	2870 [890-3960]	4.18
	16+20+20+50+60	0.96	1.21	1.21	3.01	3.61	10.00 [2.3-11.5]	11.5	2530 [610-3330]	3.95	1.16	1.45	1.45	3.61	4.33	12.00 [3.4-14.5]	12.6	2870 [890-3960]	4.18
	16+20+20+50+71	0.90	1.13	1.13	2.82	4.02	10.00 [2.3-11.5]	11.5	2530 [650-3340]	3.95	1.08	1.36	1.36	3.39	4.81	12.00 [3.4-14.5]	12.5	2860 [900-4000]	4.20
	16+20+20+60+60	0.90	1.14	1.14	3.41	3.41	10.00 [2.3-11.5]	11.5	2530 [610-3330]	3.95	1.10	1.36	1.36	4.09	4.09				

CU-5Z100VBR: Only Wall-Mounted Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION									
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP			
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	Total	
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W	
5 rooms	16+25+25+25+71	1.00	1.54	1.54	1.54	4.38	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.19	1.85	1.85	1.85	5.26	12.00 [3.4-14.5]	12.0	2750 [730-3970]	4.36	
	16+25+25+35+35	1.18	1.84	1.84	2.57	2.57	10.00 [2.3-11.5]	11.5	2540 [440-3510]	3.94	1.40	2.21	2.21	3.09	3.09	12.00 [3.4-14.5]	11.9	2730 [630-3970]	4.40	
	16+25+25+35+42	1.12	1.75	1.75	2.45	2.93	10.00 [2.3-11.5]	11.5	2540 [440-3520]	3.94	1.34	2.10	2.10	2.94	3.52	12.00 [3.4-14.5]	12.1	2770 [640-3960]	4.33	
	16+25+25+35+50	1.06	1.66	1.66	2.32	3.30	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.27	1.99	1.99	2.78	3.97	12.00 [3.4-14.5]	12.2	2790 [750-3950]	4.30	
	16+25+25+35+60	1.00	1.55	1.55	2.17	3.73	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.20	1.86	1.86	2.61	4.47	12.00 [3.4-14.5]	12.2	2790 [750-3950]	4.30	
	16+25+25+35+71	0.94	1.45	1.45	2.03	4.13	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.13	1.74	1.74	2.44	4.95	12.00 [3.4-14.5]	12.2	2780 [760-3940]	4.32	
	16+25+25+42+42	1.06	1.67	1.67	2.80	2.80	10.00 [2.3-11.5]	11.6	2550 [460-3520]	3.92	1.28	2.00	2.00	3.36	3.36	12.00 [3.4-14.5]	12.1	2760 [640-3950]	4.35	
	16+25+25+42+50	1.02	1.58	1.58	2.66	3.16	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.22	1.90	1.90	3.19	3.79	12.00 [3.4-14.5]	12.2	2790 [760-3950]	4.30	
	16+25+25+42+60	0.95	1.49	1.49	2.50	3.57	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.14	1.79	1.79	3.00	4.28	12.00 [3.4-14.5]	12.2	2790 [760-3950]	4.30	
	16+25+25+42+71	0.89	1.40	1.40	2.35	3.96	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.07	1.68	1.68	2.82	4.75	12.00 [3.4-14.5]	12.2	2780 [780-3930]	4.32	
	16+25+25+50+50	0.96	1.51	1.51	3.01	3.01	10.00 [2.3-11.5]	11.5	2530 [610-3330]	3.95	1.16	1.81	1.81	3.61	3.61	12.00 [3.4-14.5]	12.6	2870 [890-3960]	4.18	
	16+25+25+50+60	0.91	1.42	1.42	2.84	3.41	10.00 [2.3-11.5]	11.5	2530 [610-3330]	3.95	1.10	1.70	1.70	3.41	4.09	12.00 [3.4-14.5]	12.6	2870 [890-3960]	4.18	
	16+25+35+35+35	1.10	1.70	2.40	2.40	2.40	10.00 [2.3-11.5]	11.6	2550 [470-3440]	3.92	1.32	2.04	2.88	2.88	2.88	12.00 [3.4-14.5]	12.1	2760 [650-3940]	4.35	
	16+25+35+35+42	1.05	1.63	2.29	2.29	2.74	10.00 [2.3-11.5]	11.6	2550 [470-3440]	3.92	1.25	1.96	2.75	2.75	3.29	12.00 [3.4-14.5]	12.0	2750 [650-3980]	4.36	
	16+25+35+35+50	1.00	1.55	2.17	2.17	3.11	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.19	1.86	2.61	2.61	3.73	12.00 [3.4-14.5]	12.2	2780 [780-3930]	4.32	
	16+25+35+35+60	0.94	1.46	2.05	2.05	3.50	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.12	1.75	2.46	2.46	4.21	12.00 [3.4-14.5]	12.2	2780 [780-3930]	4.32	
	16+25+35+35+71	0.89	1.37	1.92	1.92	3.90	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.05	1.65	2.31	2.31	4.68	12.00 [3.4-14.5]	12.3	2810 [790-3970]	4.27	
	16+25+35+42+42	1.00	1.56	2.18	2.63	2.63	10.00 [2.3-11.5]	11.6	2550 [470-3440]	3.92	1.20	1.88	2.62	3.15	3.15	12.00 [3.4-14.5]	12.0	2740 [670-3970]	4.38	
	16+25+35+42+50	0.95	1.49	2.08	2.50	2.98	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.14	1.79	2.50	3.00	3.57	12.00 [3.4-14.5]	12.3	2820 [790-3980]	4.26	
	16+25+35+42+60	0.90	1.40	1.97	2.36	3.37	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.08	1.69	2.36	2.83	4.04	12.00 [3.4-14.5]	12.3	2820 [790-3980]	4.26	
	16+25+35+50+50	0.91	1.42	1.99	2.84	2.84	10.00 [2.3-11.5]	11.5	2530 [620-3340]	3.95	1.09	1.70	2.39	3.41	3.41	12.00 [3.4-14.5]	12.5	2860 [930-3990]	4.20	
	16+25+42+42+42	0.97	1.50	2.51	2.51	2.51	10.00 [2.3-11.5]	11.6	2550 [470-3440]	3.92	1.15	1.79	3.02	3.02	3.02	12.00 [3.4-14.5]	12.0	2740 [680-3960]	4.38	
	16+25+42+42+50	0.91	1.43	2.40	2.40	2.86	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.10	1.71	2.88	2.88	3.43	12.00 [3.4-14.5]	12.3	2810 [800-3970]	4.27	
	16+25+42+50+50	0.87	1.37	2.30	2.73	2.73	10.00 [2.3-11.5]	11.5	2530 [650-3340]	3.95	1.05	1.64	2.75	3.28	3.28	12.00 [3.4-14.5]	12.7	2900 [940-3990]	4.14	
	16+35+35+35+35	1.04	2.24	2.24	2.24	2.24	10.00 [2.3-11.5]	11.6	2550 [470-3450]	3.92	1.24	2.69	2.69							

CU-5Z100VBR: Only Wall-Mounted Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
5 rooms	20+20+25+35+35	1.48	1.48	1.86	2.59	2.59	10.00 [2.3-11.5]	11.6	2550 [460-3520]	3.92	1.78	1.78	2.22	3.11	3.11	12.00 [3.4-14.5]	12.1	2770 [640-3960]	4.33
	20+20+25+35+42	1.41	1.41	1.76	2.46	2.96	10.00 [2.3-11.5]	11.6	2550 [460-3520]	3.92	1.69	1.69	2.11	2.96	3.55	12.00 [3.4-14.5]	12.1	2760 [640-3950]	4.35
	20+20+25+35+50	1.33	1.33	1.68	2.33	3.33	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.60	1.60	2.00	2.80	4.00	12.00 [3.4-14.5]	12.2	2790 [760-3950]	4.30
	20+20+25+35+60	1.25	1.25	1.56	2.19	3.75	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.50	1.50	1.88	2.63	4.49	12.00 [3.4-14.5]	12.2	2790 [760-3950]	4.30
	20+20+25+35+71	1.17	1.17	1.46	2.05	4.15	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.40	1.40	1.76	2.46	4.98	12.00 [3.4-14.5]	12.2	2780 [780-3930]	4.32
	20+20+25+42+42	1.34	1.34	1.68	2.82	2.82	10.00 [2.3-11.5]	11.6	2550 [470-3520]	3.92	1.61	1.61	2.02	3.38	3.38	12.00 [3.4-14.5]	12.1	2760 [650-3930]	4.35
	20+20+25+42+50	1.27	1.27	1.60	2.68	3.18	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.53	1.53	1.91	3.21	3.82	12.00 [3.4-14.5]	12.2	2780 [760-3940]	4.32
	20+20+25+42+60	1.20	1.20	1.50	2.51	3.59	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.44	1.44	1.80	3.02	4.30	12.00 [3.4-14.5]	12.2	2780 [760-3940]	4.32
	20+20+25+42+71	1.12	1.12	1.41	2.36	3.99	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.35	1.35	1.69	2.83	4.78	12.00 [3.4-14.5]	12.2	2780 [780-3980]	4.32
	20+20+25+50+50	1.21	1.21	1.52	3.03	3.03	10.00 [2.3-11.5]	11.5	2530 [610-3330]	3.95	1.45	1.45	1.82	3.64	3.64	12.00 [3.4-14.5]	12.6	2870 [900-4010]	4.18
	20+20+25+50+60	1.14	1.14	1.43	2.86	3.43	10.00 [2.3-11.5]	11.5	2530 [610-3330]	3.95	1.37	1.37	1.72	3.43	4.11	12.00 [3.4-14.5]	12.6	2870 [900-4010]	4.18
	20+20+35+35+35	1.37	1.37	2.42	2.42	2.42	10.00 [2.3-11.5]	11.6	2550 [470-3440]	3.92	1.65	1.65	2.90	2.90	2.90	12.00 [3.4-14.5]	12.0	2750 [650-3980]	4.36
	20+20+35+35+42	1.32	1.32	2.30	2.30	2.76	10.00 [2.3-11.5]	11.6	2550 [470-3440]	3.92	1.58	1.58	2.76	2.76	3.32	12.00 [3.4-14.5]	12.0	2740 [670-3970]	4.38
	20+20+35+35+50	1.25	1.25	2.19	2.19	3.12	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.50	1.50	2.63	2.63	3.74	12.00 [3.4-14.5]	12.3	2820 [790-3980]	4.26
	20+20+35+35+60	1.18	1.18	2.06	2.06	3.52	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.41	1.41	2.47	2.47	4.24	12.00 [3.4-14.5]	12.3	2820 [790-3980]	4.26
	20+20+35+35+71	1.11	1.11	1.93	1.93	3.92	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.33	1.33	2.32	2.32	4.70	12.00 [3.4-14.5]	12.3	2810 [800-3960]	4.27
	20+20+35+42+42	1.26	1.26	2.20	2.64	2.64	10.00 [2.3-11.5]	11.6	2550 [470-3450]	3.92	1.51	1.51	2.64	3.17	3.17	12.00 [3.4-14.5]	12.0	2740 [680-3960]	4.38
	20+20+35+42+50	1.20	1.20	2.10	2.51	2.99	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.44	1.44	2.51	3.02	3.59	12.00 [3.4-14.5]	12.3	2810 [800-3970]	4.27
	20+20+35+42+60	1.13	1.13	1.98	2.37	3.39	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.36	1.36	2.37	2.85	4.06	12.00 [3.4-14.5]	12.3	2810 [800-3970]	4.27
	20+20+35+50+50	1.14	1.14	2.00	2.86	2.86	10.00 [2.3-11.5]	11.5	2540 [650-3340]	3.94	1.37	1.37	2.40	3.43	3.43	12.00 [3.4-14.5]	12.7	2900 [940-3990]	4.14
	20+20+42+42+42	1.19	1.19	2.54	2.54	2.54	10.00 [2.3-11.5]	11.6	2550 [470-3450]	3.92	1.44	1.44	3.04	3.04	3.04	12.00 [3.4-14.5]	12.2	2780 [680-3950]	4.32
	20+20+42+42+50	1.15	1.15	2.41	2.41	2.88	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.38	1.38	2.90	2.90	3.44	12.00 [3.4-14.5]	12.3	2810 [810-3960]	4.27
	20+20+42+50+50	1.10	1.10	2.30	2.75	2.75	10.00 [2.3-11.5]	11.5	2540 [650-3340]	3.94	1.32	1.32	2.76	3.30	3.30	12.00 [3.4-14.5]	12.7	2900 [950-4030]	4.14
	20+25+25+25+25	1.68	2.08	2.08	2.08	2.08	10.00 [2.3-11.5]	11.8	2600 [430-3590]	3.85	2.00	2.50	2.50	2.50	2.50	12.00 [3.4-14.5]	12.1	2760 [580-4020]	4.35
	20+25+25+25+35	1.55	1.92	1.92	1.92	2.69	10.00 [2.3-11.5]	11.5	2540 [430-3510]	3.94	1.85	2.31	2.31	2.31	3.22	12.00 [3.4-14.5]	12.0	2740 [610-3990]	4.38
	20+25+25+25+42	1.47	1.82	1.82	1.82	3.07	10.00 [2.3-11.5]	11.5	2540 [430-3510]	3.94	1.75	2.19	2.19	2.19	3.68	12.00 [3.4-14.5]	11.9	2730 [610-3980]	4.40
	20+25+25+25+50	1.39	1.72	1.72	1.72	3.45	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.66	2.07	2.07	2.07	4.13	12.00 [3.4-14.5]	12.1	2760 [720-3970]	4.35
	20+25+25+25+60	1.30	1.61	1.61	1.61	3.87	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.54	1.94	1.94	1.94	4.64	12.00 [3.4-14.5]	12.1	2760 [720-3970]	4.35
	20+25+25+25+71	1.20	1.51	1.51	1.51	4.27	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.45	1.81	1.81	1.81	5.12	12.00 [3.4-14.5]	12.2	2790 [750-3960]	4.30
	20+25+25+35+35	1.42	1.79	1.79	2.50	2.50	10.00 [2.3-11.5]	11.6	2550 [460-3520]	3.92	1.72	2.14	2.14	3.00	3.00	12.00 [3.4-14.5]	12.1	2770 [640-3960]	4.33
	20+25+25+35+42	1.36	1.70	1.70	2.38	2.86	10.00 [2.3-11.5]	11.6	2550 [460-3520]	3.92	1.63	2.04	2.04	2.86	3.43	12.00 [3.4-14.5]	12.1	2760 [640-3950]	4.35
	20+25+25+35+50	1.29	1.61	1.61	2.26	3.23	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.55	1.94	1.94	2.71	3.86	12.00 [3.4-14.5]	12.2	2790 [760-3950]	4.30
	20+25+25+35+60	1.21	1.52	1.52	2.12	3.63	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.45	1.82	1.82	2.55	4.36	12.00 [3.4-14.5]	12.2	2790 [760-3950]	4.30
	20+25+25+35+71	1.14	1.42	1.42	1.99	4.03	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.37	1.70	1.70	2.39	4.84	12.00 [3.4-14.5]	12.2	2780 [780-3930]	4.32
	20+25+25+42+42	1.30	1.62	1.62	2.73	2.73	10.00 [2.3-11.5]	11.6	2550 [470-3520]	3.92	1.56	1.95	1.95	3.27	3.27	12.00 [3.4-14.5]	12.1	2760 [650-3930]	4.35
	20+25+25+42+50	1.24	1.54	1.54	2.59	3.09	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.49	1.85	1.85	3.11	3.70	12.00 [3.4-14.5]	12.2	2780 [760-3940]	4.32
	20+25+25+42+60	1.17	1.45	1.45	2.44	3.49	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.40	1.74	1.74	2.93	4.19	12.00 [3.4-14.5]	12.2	2780 [760-3940]	4.32
	20+25+25+42+71	1.09	1.37	1.37	2.30	3.87	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.31	1.64	1.64	2.75	4.66	12.00 [3.4-14.5]	12.2	2780 [780-3980]	4.32
	20+25+25+50+50	1.18	1.47	1.47	2.94	2.94	10.00 [2.3-11.5]	11.5	2530 [610-3330]	3.95	1.42	1.76	1.76	3.53	3.53	12.00 [3.4-14.5]	12.6	2870 [900-4010]	4.18
	20+25+25+50+60	1.11	1.39	1.39	2.78	3.33	10.00 [2.3-11.5]	11.5	2530 [610-3330]	3.95	1.33	1.67	1.67	3.33	4.00	12.00 [3.4-14.5]	12.6	2870 [900-4010]	4.18
	20+25+35+35+35	1.34	1.67	2.33	2.33	2.33	10.00 [2.3-11.5]	11.6	2550 [470-3440]	3.92	1.60	2.00	2.80	2.80	2.80	12.00 [3.4-14.5]	12.0	2750 [650-3980]	4.36
	20+25+35+35+42	1.27	1.59	2.23	2.23	2.68	10.00 [2.3-11.5]	11.6	2550 [470-3440]	3.92	1.53	1.91	2.68	2.68	3.20	12.00 [3.4-14.5]	12.0	2740 [670-3970]	4.38
	20+25+35+35+50	1.21	1.52	2.12	2.12	3.03	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.45	1.82	2.55	2.55	3.63	12.00 [3.4-14.5]	12.3	2820 [790-3980]	4.26
	20+25+35+35+60	1.14	1.43	2.00	2.00	3.43	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.38	1.71	2.40	2.40	4.11	12.00 [3.4-14.5]	12.3	2820 [790-3980]	4.26
	20+25+35+42+42	1.23	1.52	2.13	2.56	2.56	10.00 [2.3-11.5]	11.6	2550 [470-3450]	3.92	1.47	1.83	2.56	3.07	3.07	12.00 [3.4-14.5]	12.0	2740 [680-3960]	4.38
	20+25+35+42+50	1.17	1.45	2.03	2.														

CU-5Z100VBR: Only Wall-Mounted Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	Total
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
5 rooms	25+25+25+35+42	1.64	1.64	1.64	2.31	2.77	10.00 [2.3-11.5]	11.6	2550 [460-3520]	3.92	1.97	1.97	1.97	2.77	3.32	12.00 [3.4-14.5]	12.1	2760 [640-3950]	4.35
	25+25+25+35+50	1.56	1.56	1.56	2.19	3.13	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.88	1.88	1.88	2.62	3.74	12.00 [3.4-14.5]	12.2	2790 [760-3950]	4.30
	25+25+25+35+60	1.47	1.47	1.47	2.06	3.53	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.76	1.76	1.76	2.48	4.24	12.00 [3.4-14.5]	12.2	2790 [760-3950]	4.30
	25+25+25+35+71	1.38	1.38	1.38	1.93	3.93	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.66	1.66	1.66	2.32	4.70	12.00 [3.4-14.5]	12.2	2780 [780-3930]	4.32
	25+25+25+42+42	1.58	1.58	1.58	2.63	2.63	10.00 [2.3-11.5]	11.6	2550 [470-3520]	3.92	1.88	1.88	1.88	3.18	3.18	12.00 [3.4-14.5]	12.1	2760 [650-3930]	4.35
	25+25+25+42+50	1.50	1.50	1.50	2.51	2.99	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.80	1.80	1.80	3.02	3.58	12.00 [3.4-14.5]	12.2	2780 [760-3940]	4.32
	25+25+25+42+60	1.41	1.41	1.41	2.38	3.39	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.69	1.69	1.69	2.86	4.07	12.00 [3.4-14.5]	12.2	2780 [760-3940]	4.32
	25+25+25+50+50	1.42	1.42	1.42	2.87	2.87	10.00 [2.3-11.5]	11.5	2530 [610-3330]	3.95	1.72	1.72	1.72	3.42	3.42	12.00 [3.4-14.5]	12.6	2870 [900-4010]	4.18
	25+25+35+35+35	1.61	1.61	2.26	2.26	2.26	10.00 [2.3-11.5]	11.6	2550 [470-3440]	3.92	1.95	1.95	2.70	2.70	2.70	12.00 [3.4-14.5]	12.0	2750 [650-3980]	4.36
	25+25+35+35+42	1.54	1.54	2.16	2.16	2.60	10.00 [2.3-11.5]	11.6	2550 [470-3440]	3.92	1.85	1.85	2.59	2.59	3.12	12.00 [3.4-14.5]	12.0	2740 [670-3970]	4.38
	25+25+35+35+50	1.47	1.47	2.06	2.06	2.94	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.76	1.76	2.47	2.47	3.54	12.00 [3.4-14.5]	12.3	2820 [790-3980]	4.26
	25+25+35+35+60	1.39	1.39	1.94	1.94	3.34	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.67	1.67	2.33	2.33	4.00	12.00 [3.4-14.5]	12.3	2820 [790-3980]	4.26
	25+25+35+42+42	1.48	1.48	2.06	2.49	2.49	10.00 [2.3-11.5]	11.6	2550 [470-3450]	3.92	1.78	1.78	2.48	2.98	2.98	12.00 [3.4-14.5]	12.0	2740 [680-3960]	4.38
	25+25+35+42+50	1.41	1.41	1.99	2.37	2.82	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.69	1.69	2.37	2.85	3.40	12.00 [3.4-14.5]	12.3	2810 [800-3970]	4.27
	25+25+42+42+42	1.43	1.43	2.38	2.38	2.38	10.00 [2.3-11.5]	11.6	2550 [470-3450]	3.92	1.71	1.71	2.86	2.86	2.86	12.00 [3.4-14.5]	12.2	2780 [680-3950]	4.32
	25+35+35+35+35	1.52	2.12	2.12	2.12	2.12	10.00 [2.3-11.5]	11.6	2550 [470-3450]	3.92	1.80	2.55	2.55	2.55	2.55	12.00 [3.4-14.5]	12.2	2780 [680-3960]	4.32
	25+35+35+35+42	1.46	2.03	2.03	2.03	2.45	10.00 [2.3-11.5]	11.6	2550 [480-3450]	3.92	1.75	2.44	2.44	2.44	2.93	12.00 [3.4-14.5]	12.1	2770 [690-3950]	4.33
	25+35+35+35+50	1.40	1.94	1.94	1.94	2.78	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.68	2.33	2.33	2.33	3.33	12.00 [3.4-14.5]	12.3	2810 [820-3950]	4.27
	25+35+35+42+42	1.40	1.96	1.96	2.34	2.34	10.00 [2.3-11.5]	11.6	2550 [480-3450]	3.92	1.68	2.35	2.35	2.81	2.81	12.00 [3.4-14.5]	12.1	2770 [710-3940]	4.33
	35+35+35+35+35	2.00	2.00	2.00	2.00	2.00	10.00 [2.3-11.5]	11.6	2550 [510-3450]	3.92	2.40	2.40	2.40	2.40	2.40	12.00 [3.4-14.5]	12.1	2760 [710-3930]	4.35
	35+35+35+35+42	1.92	1.92	1.92	1.92	2.32	10.00 [2.3-11.5]	11.6	2560 [510-3450]	3.91	2.31	2.31	2.31	2.31	2.76	12.00 [3.4-14.5]	12.1	2760 [720-3980]	4.35

CU-5Z100VBR: Free Multi Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION								HEATING OPERATION									
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	Total
		kW	kW	kW	kW	kW				kW	kW	kW	kW	kW				kW	kW
2 rooms	16+16	1.60	1.60	-	-	-	3.20 [2.3-5.8]	3.7	760 [260-1840]	4.21	2.60	2.60	-	-	-	5.20 [2.0-8.2]	7.2	1580 [220-2610]	3.29
	16+20	1.60	2.00	-	-	-	3.60 [2.3-5.8]	4.3	890 [250-1840]	4.04	2.58	3.22	-	-	-	5.80 [2.0-8.2]	7.9	1740 [220-2600]	3.33
	16+25	1.60	2.50	-	-	-	4.10 [2.3-5.8]	5.0	1060 [250-1840]	3.87	2.42	3.78	-	-	-	6.20 [2.0-8.2]	8.5	1880 [220-2600]	3.30
	16+35	1.60	3.50	-	-	-	5.10 [2.3-5.8]	6.6	1420 [250-1780]	3.59	2.23	4.87	-	-	-	7.10 [2.0-8.6]	9.5	2110 [210-2680]	3.36
	16+42	1.60	4.20	-	-	-	5.80 [2.3-6.7]	8.0	1730 [250-2230]	3.35	2.26	5.94	-	-	-	8.20 [2.0-10.1]	11.1	2470 [210-3230]	3.32
	16+50	1.60	5.00	-	-	-	6.60 [2.3-7.2]	8.9	1940 [240-2230]	3.40	2.28	7.12	-	-	-	9.40 [2.0-11.0]	12.0	2670 [160-3240]	3.52
	16+60	1.60	6.00	-	-	-	7.60 [2.3-8.6]	11.3	2470 [240-3180]	3.08	2.34	8.76	-	-	-	11.10 [2.0-11.0]	13.9	3090 [160-3240]	3.59
	16+71	1.60	7.10	-	-	-	8.70 [2.3-9.1]	13.9	3020 [230-3260]	2.88	2.08	9.22	-	-	-	11.30 [2.0-13.0]	13.6	3030 [160-4180]	3.73
	20+20	2.00	2.00	-	-	-	4.00 [2.3-5.8]	4.8	1020 [250-1780]	3.92	3.20	3.20	-	-	-	6.40 [2.0-8.2]	8.6	1910 [220-2590]	3.35
	20+25	2.00	2.50	-	-	-	4.50 [2.3-5.8]	5.7	1220 [250-1780]	3.69	3.02	3.78	-	-	-	6.80 [2.0-8.2]	9.1	2030 [220-2590]	3.35
	20+35	2.00	3.50	-	-	-	5.50 [2.3-5.8]	7.3	1570 [250-1730]	3.50	2.80	4.90	-	-	-	7.70 [2.0-8.6]	10.3	2280 [210-2620]	3.38
	20+42	2.00	4.20	-	-	-	6.20 [2.3-7.2]	8.9	1940 [250-2590]	3.20	2.84	5.96	-	-	-	8.80 [2.0-11.0]	11.8	2620 [200-3430]	3.36
	20+50	2.00	5.00	-	-	-	7.00 [2.3-8.1]	9.4	2050 [240-2710]	3.41	2.86	7.14	-	-	-	10.00 [2.0-11.0]	12.8	2850 [160-3180]	3.51
	20+60	2.00	6.00	-	-	-	8.00 [2.3-8.6]	12.2	2650 [240-3110]	3.02	2.93	8.77	-	-	-	11.70 [2.0-11.9]	14.3	3180 [160-3670]	3.68
	20+71	2.00	7.10	-	-	-	9.10 [2.3-10.0]	14.6	3190 [260-4130]	2.85	2.62	9.28	-	-	-	11.90 [2.0-13.0]	14.7	3260 [160-4170]	3.65
	25+25	2.50	2.50	-	-	-	5.00 [2.3-5.8]	6.3	1370 [250-1780]	3.65	3.60	3.60	-	-	-	7.20 [2.0-8.6]	9.8	2170 [220-2700]	3.32
	25+35	2.50	3.50	-	-	-	6.00 [2.3-6.7]	8.4	1830 [250-2230]	3.28	3.38	4.72	-	-	-	8.10 [2.0-10.1]	10.9	2420 [210-3230]	3.35
	25+42	2.50	4.20	-	-	-	6.70 [2.3-7.2]	10.2	2230 [250-2590]	3.00	3.43	5.77	-	-	-	9.20 [2.0-11.0]	12.5	2770 [200-3430]	3.32
	25+50	2.50	5.00	-	-	-	7.50 [2.3-8.6]	10.8	2350 [240-3110]	3.19	3.47	6.93	-	-	-	10.40 [2.0-11.0]	13.0	2880 [160-3180]	3.61
	25+60	2.50	6.00	-	-	-	8.50 [2.3-9.1]	13.9	3040 [240-3390]	2.80	3.53	8.47	-	-	-	12.00 [2.0-13.0]	15.0	3330 [160-4180]	3.60
	25+71	2.50	7.10	-	-	-	9.60 [2.3-10.1]	16.7	3630 [260-4280]	2.64	3.13	8.87	-	-	-	12.00 [2.0-13.0]	14.9	3310 [160-4170]	3.63
	35+35	3.50	3.50	-	-	-	7.00 [2.3-8.1]	10.8	2350 [250-3160]	2.98	4.50	4.50	-	-	-	9.00 [2.0-11.0]	11.9	2650 [200-3420]	3.40
	35+42	3.50	4.20	-	-	-	7.70 [2.3-8.6]	12.7	2770 [250-3650]	2.78	4.59	5.51	-	-	-	10.10 [2.0-11.0]	13.5	3000 [200-3360]	3.37
	35+50	3.50	5.00	-	-	-	8.50 [2.3-9.1]	13.3	2910 [230-3260]	2.92	4.65	6.65	-	-	-	11.30 [2.0-13.0]	13.3	2960 [160-4160]	3.82
	35+60	3.50	6.00	-	-	-	9.50 [2.3-10.1]	16.8	3670 [230-4280]	2.59	4.42	7.58	-	-	-	12.00 [2.0-13.0]	14.6	3250 [160-4160]	3.69
	35+71	3.30	6.70	-	-	-	10.00 [2.3-10.4]	18.0	3920 [260-4440]	2.55	3.96	8.04	-	-	-	12.00 [2.0-13.8]	14.6	3240 [160-4510]	3.70
	42+42	4.20	4.20	-	-	-	8.40 [2.3-9.1]	15.8	3440 [250-4060]	2.44	5.60	5.60	-	-	-	11.20 [2.0-13.0]	14.1	3140 [190-4350]	3.57
	42+50	4.20	5.00	-	-	-	9.20 [2.3-10.0]	15.3	3330 [230-4130]	2.76	5.48	6.52	-	-	-	12.00 [2.0-13.0]	14.6	3240 [160-4090]	3.70

CU-5Z100VBR: Free Multi Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION								HEATING OPERATION									
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	
		kW	kW	kW	kW	kW					kW	kW	kW	kW				kW	kW
2 rooms	42+60	4.12	5.88	-	-	-	10.00 [2.3 -10.4]	18.9	4130 [230-4430]	2.42	4.94	7.06	-	-	-	12.00 [2.0-13.8]	14.6	3240 [160-4510]	3.70
	42+71	3.72	6.28	-	-	-	10.00 [2.3 -10.4]	17.7	3850 [260-4440]	2.60	4.46	7.54	-	-	-	12.00 [2.0-13.8]	14.5	3230 [160-4500]	3.72
	50+50	5.00	5.00	-	-	-	10.00 [2.3 -10.4]	15.5	3370 [250-3710]	2.97	6.00	6.00	-	-	-	12.00 [2.0-13.8]	13.6	3030 [170-4260]	3.96
	50+60	4.55	5.45	-	-	-	10.00 [2.3 -10.4]	15.5	3370 [250-3710]	2.97	5.45	6.55	-	-	-	12.00 [2.0-13.8]	13.6	3030 [170-4260]	3.96
	50+71	4.13	5.87	-	-	-	10.00 [2.3 -10.4]	14.8	3230 [250-3580]	3.10	4.96	7.04	-	-	-	12.00 [2.0-13.8]	13.6	3010 [170-4240]	3.99
	60+60	5.00	5.00	-	-	-	10.00 [2.3 -10.4]	15.5	3370 [250-3710]	2.97	6.00	6.00	-	-	-	12.00 [2.0-13.8]	13.6	3030 [170-4260]	3.96
	60+71	4.58	5.42	-	-	-	10.00 [2.3 -10.4]	14.8	3230 [250-3580]	3.10	5.50	6.50	-	-	-	12.00 [2.0-13.8]	13.6	3010 [170-4240]	3.99
	71+71	5.00	5.00	-	-	-	10.00 [2.3 -10.4]	14.2	3100 [280-3440]	3.23	6.00	6.00	-	-	-	12.00 [2.0-13.8]	13.5	3000 [180-4220]	4.00
3 rooms	16+16+16	1.60	1.60	1.60	-	-	4.80 [2.3 -8.5]	5.3	1140 [260-2770]	4.21	2.60	2.60	2.60	-	-	7.80 [2.7-12.3]	9.5	2100 [230-3820]	3.71
	16+16+20	1.60	1.60	2.00	-	-	5.20 [2.3 -8.5]	5.8	1250 [260-2770]	4.16	2.58	2.58	3.24	-	-	8.40 [2.7-12.3]	10.4	2320 [230-3800]	3.62
	16+16+25	1.60	1.60	2.50	-	-	5.70 [2.3 -8.5]	6.7	1440 [260-2770]	3.96	2.47	2.47	3.86	-	-	8.80 [2.7-12.3]	10.8	2390 [230-3800]	3.68
	16+16+35	1.60	1.60	3.50	-	-	6.70 [2.3 -8.5]	8.1	1760 [260-2700]	3.81	2.32	2.32	5.06	-	-	9.70 [2.7-12.3]	12.2	2700 [230-3720]	3.59
	16+16+42	1.60	1.60	4.20	-	-	7.40 [2.3 -8.5]	9.6	2100 [250-2640]	3.52	2.34	2.34	6.12	-	-	10.80 [2.7-12.3]	12.7	2830 [230-3700]	3.82
	16+16+50	1.60	1.60	5.00	-	-	8.20 [2.3 -8.7]	10.4	2260 [280-2440]	3.63	2.34	2.34	7.32	-	-	12.00 [2.7-12.9]	13.7	3050 [250-3790]	3.93
	16+16+60	1.60	1.60	6.00	-	-	9.20 [2.3 -10.1]	11.9	2600 [280-3150]	3.54	2.09	2.09	7.82	-	-	12.00 [2.7-13.6]	13.7	3050 [250-4150]	3.93
	16+16+71	1.55	1.55	6.90	-	-	10.00 [2.3 -10.7]	13.6	2960 [280-3490]	3.38	1.86	1.86	8.28	-	-	12.00 [2.7-13.6]	13.7	3040 [250-4070]	3.95
	16+20+20	1.60	2.00	2.00	-	-	5.60 [2.3 -8.5]	6.4	1390 [260-2700]	4.03	2.58	3.21	3.21	-	-	9.00 [2.7-12.3]	10.9	2430 [230-3790]	3.70
	16+20+25	1.60	2.00	2.50	-	-	6.10 [2.3 -8.5]	7.4	1600 [260-2700]	3.81	2.47	3.08	3.85	-	-	9.40 [2.7-12.3]	11.6	2570 [230-3790]	3.66
	16+20+35	1.60	2.00	3.50	-	-	7.10 [2.3 -8.5]	8.9	1930 [250-2640]	3.68	2.32	2.90	5.08	-	-	10.30 [2.7-12.3]	12.3	2730 [230-3700]	3.77
	16+20+42	1.60	2.00	4.20	-	-	7.80 [2.3 -8.5]	10.1	2210 [250-2640]	3.53	2.34	2.92	6.14	-	-	11.40 [2.7-12.9]	13.4	2970 [230-3980]	3.84
	16+20+50	1.60	2.00	5.00	-	-	8.60 [2.3 -9.6]	11.2	2450 [280-2770]	3.51	2.23	2.79	6.98	-	-	12.00 [2.7-13.6]	13.7	3040 [250-4070]	3.95
	16+20+60	1.60	2.00	6.00	-	-	9.60 [2.3 -10.1]	12.7	2770 [280-3090]	3.47	2.00	2.50	7.50	-	-	12.00 [2.7-13.6]	13.7	3040 [250-4070]	3.95
	16+20+71	1.50	1.87	6.63	-	-	10.00 [2.3 -10.7]	13.6	2960 [280-3490]	3.38	1.80	2.24	7.96	-	-	12.00 [2.7-13.8]	13.6	3030 [250-4180]	3.96
	16+25+25	1.60	2.50	2.50	-	-	6.60 [2.3 -8.5]	8.3	1810 [260-2700]	3.65	2.38	3.71	3.71	-	-	9.80 [2.7-12.3]	12.5	2770 [230-3790]	3.54
	16+25+35	1.60	2.50	3.50	-	-	7.60 [2.3 -8.5]	10.1	2210 [250-2640]	3.44	2.25	3.52	4.93	-	-	10.70 [2.7-12.3]	12.9	2870 [230-3700]	3.73
	16+25+42	1.60	2.50	4.20	-	-	8.30 [2.3 -8.7]	11.5	2510 [250-2690]	3.31	2.28	3.55	5.97	-	-	11.80 [2.7-12.9]	14.0	3110 [230-3980]	3.79
	16+25+50	1.60	2.50	5.00	-	-	9.10 [2.3 -10.1]	11.7	2540 [280-3090]	3.58	2.11	3.30	6.59	-	-	12.00 [2.7-13.6]	13.7	3040 [250-4070]	3.95
	16+25+60	1.58	2.48	5.94	-	-	10.00 [2.3 -10.7]	13.9	3020 [280-3630]	3.31	1.90	2.97	7.13	-	-	12.00 [2.7-13.6]	13.7	3040 [250-4070]	3.95
	16+25+71	1.43	2.23	6.34	-	-	10.00 [2.3 -10.7]	13.6	2960 [280-3490]	3.38	1.71	2.68	7.61	-	-	12.00 [2.7-13.8]	13.6	3030 [250-4180]	3.96
	16+35+35	1.60	3.50	3.50	-	-	8.60 [2.3 -9.6]	12.1	2640 [250-3080]	3.26	2.16	4.72	4.72	-	-	11.60 [2.7-13.6]	13.5	3000 [230-4320]	3.87
	16+35+42	1.60	3.50	4.20	-	-	9.30 [2.3 -10.1]	13.4	2920 [250-3480]	3.18	2.06	4.52	5.42	-	-	12.00 [2.7-13.6]	14.1	3130 [240-4310]	3.83
	16+35+50	1.58	3.47	4.95	-	-	10.00 [2.3 -10.7]	13.6	2960 [280-3490]	3.38	1.90	4.16	5.94	-	-	12.00 [2.7-13.6]	13.3	2960 [250-4040]	4.05
	16+35+60	1.44	3.15	5.41	-	-	10.00 [2.3 -10.7]	13.6	2960 [280-3490]	3.38	1.73	3.78	6.49	-	-	12.00 [2.7-13.8]	13.3	2960 [250-4160]	4.05
	16+35+71	1.31	2.87	5.82	-	-	10.00 [2.3 -10.7]	13.3	2890 [280-3350]	3.46	1.58	3.44	6.98	-	-	12.00 [2.7-13.8]	13.3	2950 [270-4140]	4.07
	16+42+42	1.60	4.20	4.20	-	-	10.00 [2.3 -10.7]	15.4	3350 [250-4060]	2.99	1.92	5.04	5.04	-	-	12.00 [2.7-13.6]	14.1	3120 [240-4230]	3.85
	16+42+50	1.48	3.89	4.63	-	-	10.00 [2.3 -10.7]	13.6	2960 [280-3490]	3.38	1.78	4.67	5.55	-	-	12.00 [2.7-13.8]	13.3	2950 [270-4150]	4.07
	16+42+60	1.36	3.56	5.08	-	-	10.00 [2.3 -10.7]	13.6	2960 [280-3490]	3.38	1.63	4.27	6.10	-	-	12.00 [2.7-13.8]	13.3	2950 [270-4150]	4.07
	16+42+71	1.24	3.26	5.50	-	-	10.00 [2.3 -10.7]	13.3	2890 [280-3350]	3.46	1.49	3.91	6.60	-	-	12.00 [2.7-14.1]	13.2	2940 [270-4250]	4.08
	16+50+50	1.38	4.31	4.31	-	-	10.00 [2.3 -10.7]	12.4	2700 [320-3090]	3.70	1.66	5.17	5.17	-	-	12.00 [2.7-13.8]	12.8	2840 [300-3940]	4.23
	16+50+60	1.27	3.97	4.76	-	-	10.00 [2.3 -10.7]	12.4	2700 [320-3090]	3.70	1.53	4.76	5.71	-	-	12.00 [2.7-13.8]	12.8	2840 [300-3940]	4.23
	16+50+71	1.17	3.65	5.18	-	-	10.00 [2.3 -10.7]	12.1	2640 [340-3020]	3.79	1.40	4.38	6.22	-	-	12.00 [2.7-14.1]	12.7	2830 [310-4100]	4.24
	16+60+60	1.18	4.41	4.41	-	-	10.00 [2.3 -10.7]	12.4	2700 [320-3090]	3.70	1.42	5.29	5.29	-	-	12.00 [2.7-14.1]	12.8	2840 [300-4110]	4.23
	16+60+71	1.09	4.08	4.83	-	-	10.00 [2.3 -10.7]	12.1	2640 [340-3020]	3.79	1.31	4.90	5.79	-	-	12.00 [2.7-14.1]	12.7	2830 [310-4100]	4.24
	16+71+71	1.02	4.49	4.49	-	-	10.00 [2.3 -10.7]	11.8	2580 [350-2960]	3.88	1.22	5.39	5.39	-	-	12.00 [2.7-14.4]	12.7	2820 [320-4200]	4.26
	20+20+20	2.00	2.00	2.00	-	-	6.00 [2.3 -8.5]	7.1	1540 [260-2700]	3.90	3.20	3.20	3.20	-	-	9.60 [2.7-12.3]	12.0	2660 [230-3780]	3.61
	20+20+25	2.00	2.00	2.50	-	-	6.50 [2.3 -8.5]	8.0	1750 [260-2700]	3.71	3.08	3.08	3.84	-	-	10.00 [2.7-12.3]	12.7	2810 [230-3780]	3.56
	20+20+35	2.00	2.00	3.50	-	-	7.50 [2.3 -8.5]	9.6	2100 [250-2640]	3.57	2.91	2.91	5.08	-	-	10.90 [2.7-12.3]	12.9	2870 [230-3690]	3.80
	20+20+42	2.00	2.00	4.20	-	-	8.20 [2.3 -8.7]	11.2	2450 [250-2690]	3.35	2.93	2.93	6.14	-	-	12.00 [2.7-12.9]	14.4	3200 [230-3970]	3.75
	20+20+50	2.00	2.00	5.00	-	-	9.00 [2.3 -9.6]	11.7	2560 [280-2770]	3.52	2.67	2.67	6.66	-	-	12.00 [2.7-13.6]	13.6	3030 [250-4060]	3.96
	20+20+60	2.00	2.00	6.00	-	-	10.00 [2.3 -10.7]	13.9	3020 [280-3560]	3.31	2.40	2.40	7.20	-	-	12.00 [2.7-13.6]	13.6	3030 [250-4060]	3.96
20+20+71	1.80	1.80	6.40	-	-	10.00 [2.3 -10.7]	13.6	2960 [280-3420]	3.38	2.16	2.16	7.68	-	-	12.00 [2.7-13.8]	13.4			

CU-5Z100VBR: Free Multi Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION								HEATING OPERATION									
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
3 rooms	20+42+50	1.79	3.75	4.46	-	-	10.00 [2.3-10.7]	13.6	2960 [280-3420]	3.38	2.14	4.50	5.36	-	-	12.00 [2.7-13.8]	13.2	2940 [270-4130]	4.08
	20+42+60	1.64	3.44	4.92	-	-	10.00 [2.3-10.7]	13.6	2960 [280-3420]	3.38	1.97	4.13	5.90	-	-	12.00 [2.7-13.8]	13.2	2940 [270-4130]	4.08
	20+42+71	1.50	3.16	5.34	-	-	10.00 [2.3-10.7]	13.0	2830 [280-3350]	3.53	1.80	3.79	6.41	-	-	12.00 [2.7-14.1]	13.2	2930 [270-4240]	4.10
	20+50+50	1.66	4.17	4.17	-	-	10.00 [2.3-10.7]	12.4	2710 [320-3090]	3.69	2.00	5.00	5.00	-	-	12.00 [2.7-13.8]	12.7	2830 [310-3920]	4.24
	20+50+60	1.54	3.85	4.61	-	-	10.00 [2.3-10.7]	12.4	2710 [320-3090]	3.69	1.85	4.62	5.53	-	-	12.00 [2.7-14.1]	12.7	2830 [310-4100]	4.24
	20+50+71	1.42	3.55	5.03	-	-	10.00 [2.3-10.7]	12.1	2640 [350-3020]	3.79	1.70	4.26	6.04	-	-	12.00 [2.7-14.1]	12.7	2820 [320-4080]	4.26
	20+60+60	1.42	4.29	4.29	-	-	10.00 [2.3-10.7]	12.4	2710 [320-3090]	3.69	1.72	5.14	5.14	-	-	12.00 [2.7-14.1]	12.7	2830 [310-4100]	4.24
	20+60+71	1.33	3.97	4.70	-	-	10.00 [2.3-10.7]	12.1	2640 [350-3020]	3.79	1.59	4.77	5.64	-	-	12.00 [2.7-14.4]	12.7	2820 [320-4200]	4.26
	20+71+71	1.24	4.38	4.38	-	-	10.00 [2.3-10.7]	11.8	2580 [350-2960]	3.88	1.48	5.26	5.26	-	-	12.00 [2.7-14.4]	12.8	2850 [330-4190]	4.21
	25+25+25	2.50	2.50	2.50	-	-	7.50 [2.3-8.5]	9.9	2160 [260-2700]	3.47	3.60	3.60	3.60	-	-	10.80 [2.7-12.3]	12.8	2850 [230-3780]	3.79
	25+25+35	2.50	2.50	3.50	-	-	8.50 [2.3-9.6]	12.1	2640 [250-3150]	3.22	3.44	3.44	4.82	-	-	11.70 [2.7-13.6]	13.8	3060 [230-4340]	3.82
	25+25+42	2.50	2.50	4.20	-	-	9.20 [2.3-10.1]	13.4	2920 [250-3550]	3.15	3.26	3.26	5.48	-	-	12.00 [2.7-13.6]	14.4	3200 [230-4330]	3.75
	25+25+50	2.50	2.50	5.00	-	-	10.00 [2.3-10.7]	13.9	3020 [280-3560]	3.31	3.00	3.00	6.00	-	-	12.00 [2.7-13.6]	13.6	3030 [250-4060]	3.96
	25+25+60	2.27	2.27	5.46	-	-	10.00 [2.3-10.7]	13.9	3020 [280-3560]	3.31	2.73	2.73	6.54	-	-	12.00 [2.7-13.8]	13.6	3030 [250-4180]	3.96
	25+25+71	2.07	2.07	5.86	-	-	10.00 [2.3-10.7]	13.6	2960 [280-3420]	3.38	2.48	2.48	7.04	-	-	12.00 [2.7-13.8]	13.4	2970 [250-4160]	4.04
	25+35+35	2.50	3.50	3.50	-	-	9.50 [2.3-10.1]	14.0	3050 [250-3480]	3.11	3.16	4.42	4.42	-	-	12.00 [2.7-13.6]	14.1	3130 [240-4310]	3.83
	25+35+42	2.45	3.43	4.12	-	-	10.00 [2.3-10.7]	15.4	3350 [250-4060]	2.99	2.94	4.12	4.94	-	-	12.00 [2.7-13.6]	14.1	3120 [240-4230]	3.85
	25+35+50	2.27	3.18	4.55	-	-	10.00 [2.3-10.7]	13.6	2960 [280-3490]	3.38	2.73	3.82	5.45	-	-	12.00 [2.7-13.8]	13.3	2950 [270-4150]	4.07
	25+35+60	2.08	2.92	5.00	-	-	10.00 [2.3-10.7]	13.6	2960 [280-3490]	3.38	2.50	3.50	6.00	-	-	12.00 [2.7-13.8]	13.3	2950 [270-4150]	4.07
	25+35+71	1.91	2.67	5.42	-	-	10.00 [2.3-10.7]	13.3	2890 [280-3350]	3.46	2.29	3.21	6.50	-	-	12.00 [2.7-14.1]	13.2	2940 [270-4250]	4.08
	25+42+42	2.30	3.85	3.85	-	-	10.00 [2.3-10.7]	15.4	3350 [250-4060]	2.99	2.76	4.62	4.62	-	-	12.00 [2.7-13.8]	14.0	3110 [240-4340]	3.86
	25+42+50	2.14	3.59	4.27	-	-	10.00 [2.3-10.7]	13.6	2960 [280-3420]	3.38	2.56	4.31	5.13	-	-	12.00 [2.7-13.8]	13.2	2940 [270-4130]	4.08
	25+42+60	1.97	3.31	4.72	-	-	10.00 [2.3-10.7]	13.6	2960 [280-3420]	3.38	2.36	3.97	5.67	-	-	12.00 [2.7-14.1]	13.2	2940 [270-4250]	4.08
	25+42+71	1.82	3.04	5.14	-	-	10.00 [2.3-10.7]	13.0	2830 [280-3350]	3.53	2.18	3.65	6.17	-	-	12.00 [2.7-14.1]	13.2	2930 [270-4240]	4.10
	25+50+50	2.00	4.00	4.00	-	-	10.00 [2.3-10.7]	12.4	2710 [320-3090]	3.69	2.40	4.80	4.80	-	-	12.00 [2.7-13.8]	12.7	2830 [310-3920]	4.24
	25+50+60	1.86	3.70	4.44	-	-	10.00 [2.3-10.7]	12.4	2710 [320-3090]	3.69	2.23	4.44	5.33	-	-	12.00 [2.7-14.1]	12.7	2830 [310-4100]	4.24
	25+50+71	1.72	3.42	4.86	-	-	10.00 [2.3-10.7]	12.1	2640 [350-3020]	3.79	2.05	4.11	5.84	-	-	12.00 [2.7-14.1]	12.7	2820 [320-4080]	4.26
	25+60+60	1.72	4.14	4.14	-	-	10.00 [2.3-10.7]	12.4	2710 [320-3090]	3.69	2.06	4.97	4.97	-	-	12.00 [2.7-14.1]	12.7	2830 [310-4100]	4.24
	25+60+71	1.60	3.85	4.55	-	-	10.00 [2.3-10.7]	12.1	2640 [350-3020]	3.79	1.92	4.62	5.46	-	-	12.00 [2.7-14.4]	12.7	2820 [320-4200]	4.26
	25+71+71	1.50	4.25	4.25	-	-	10.00 [2.3-10.7]	11.8	2580 [350-2960]	3.88	1.80	5.10	5.10	-	-	12.00 [2.7-14.4]	12.8	2850 [330-4190]	4.21
	35+35+35	3.33	3.33	3.33	-	-	9.99 [2.3-10.7]	15.0	3280 [250-3980]	3.05	4.00	4.00	4.00	-	-	12.00 [2.7-13.8]	14.0	3100 [240-4330]	3.87
	35+35+42	3.13	3.13	3.74	-	-	10.00 [2.3-10.7]	15.0	3280 [250-3910]	3.05	3.75	3.75	4.50	-	-	12.00 [2.7-13.8]	13.9	3090 [240-4320]	3.88
	35+35+50	2.92	2.92	4.16	-	-	10.00 [2.3-10.7]	13.3	2890 [280-3350]	3.46	3.50	3.50	5.00	-	-	12.00 [2.7-13.8]	13.2	2930 [270-4110]	4.10
	35+35+60	2.69	2.69	4.62	-	-	10.00 [2.3-10.7]	13.3	2890 [280-3350]	3.46	3.23	3.23	5.54	-	-	12.00 [2.7-14.1]	13.2	2930 [270-4230]	4.10
	35+35+71	2.48	2.48	5.04	-	-	10.00 [2.3-10.7]	13.0	2830 [310-3290]	3.53	2.98	2.98	6.04	-	-	12.00 [2.7-14.1]	13.1	2910 [270-4210]	4.12
	35+42+42	2.94	3.53	3.53	-	-	10.00 [2.3-10.7]	14.8	3220 [250-3910]	3.11	3.52	4.24	4.24	-	-	12.00 [2.7-13.8]	13.9	3080 [250-4310]	3.90
	35+42+50	2.76	3.31	3.93	-	-	10.00 [2.3-10.7]	13.3	2890 [280-3350]	3.46	3.31	3.97	4.72	-	-	12.00 [2.7-14.1]	13.1	2920 [270-4220]	4.11
	35+42+60	2.55	3.07	4.38	-	-	10.00 [2.3-10.7]	13.3	2890 [280-3350]	3.46	3.07	3.68	5.25	-	-	12.00 [2.7-14.1]	13.1	2920 [270-4220]	4.11
	35+42+71	2.36	2.84	4.80	-	-	10.00 [2.3-10.7]	13.0	2830 [310-3290]	3.53	2.84	3.41	5.75	-	-	12.00 [2.7-14.1]	13.1	2900 [280-4200]	4.14
	35+50+50	2.60	3.70	3.70	-	-	10.00 [2.3-10.7]	12.1	2640 [350-3020]	3.79	3.12	4.44	4.44	-	-	12.00 [2.7-14.1]	12.8	2850 [330-4070]	4.21
	35+50+60	2.41	3.45	4.14	-	-	10.00 [2.3-10.7]	12.1	2640 [350-3020]	3.79	2.90	4.14	4.96	-	-	12.00 [2.7-14.1]	12.8	2850 [330-4070]	4.21
	35+50+71	2.24	3.21	4.55	-	-	10.00 [2.3-10.7]	11.8	2580 [350-2960]	3.88	2.69	3.85	5.46	-	-	12.00 [2.7-14.4]	12.8	2840 [330-4170]	4.23
	35+60+60	2.26	3.87	3.87	-	-	10.00 [2.3-10.7]	12.1	2640 [350-3020]	3.79	2.70	4.65	4.65	-	-	12.00 [2.7-14.4]	12.8	2850 [330-4190]	4.21
	35+60+71	2.11	3.61	4.28	-	-	10.00 [2.3-10.7]	11.8	2580 [350-2960]	3.88	2.53	4.34	5.13	-	-	12.00 [2.7-14.4]	12.8	2840 [330-4170]	4.23
	35+71+71	1.98	4.01	4.01	-	-	10.00 [2.3-10.7]	11.9	2590 [350-2960]	3.86	2.38	4.81	4.81	-	-	12.00 [2.7-14.4]	12.7	2830 [340-4150]	4.24
	42+42+42	3.33	3.33	3.33	-	-	9.99 [2.3-10.7]	14.8	3220 [250-3840]	3.10	4.00	4.00	4.00	-	-	12.00 [2.7-13.8]	13.8	3070 [250-4230]	3.91
	42+42+50	3.13	3.13	3.74	-	-	10.00 [2.3-10.7]	13.0	2830 [280-3350]	3.53	3.76	3.76	4.48	-	-	12.00 [2.7-14.1]	13.1	2910 [280-4200]	4.12
	42+42+60	2.92	2.92	4.16	-	-	10.00 [2.3-10.7]	13.0	2830 [280-3350]	3.53	3.50	3.50	5.00	-	-	12.00 [2.7-14.1]	13.1	2910 [280-4200]	4.12
	42+42+71	2.71	2.71	4.58	-	-	10.00 [2.3-10.7]	12.7	2770 [310-3220]	3.61	3.25	3.25	5.50	-	-	12.00 [2.7-14.4]	13.0	2890 [280-4310]	4.15
	42+50+50	2.96	3.52	3.52	-	-	10.00 [2.3-10.7]	12.1	2640 [350-3020]	3.79	3.54	4.23	4.23	-	-	12.00 [2.7-14.1]	12.8	2850 [330-4050]	4.21
	42+50+60	2.76	3.29	3															

CU-5Z100VBR: Free Multi Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION								HEATING OPERATION									
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
4 rooms	16+16+16+16	1.60	1.60	1.60	1.60	-	6.40 [2.3-10.6]	7.4	1600 [310-3680]	4.00	2.60	2.60	2.60	2.60	-	10.40 [3.4-14.2]	11.9	2640 [340-4400]	3.94
	16+16+16+20	1.60	1.60	1.60	2.00	-	6.80 [2.3-10.6]	8.1	1740 [310-3680]	3.91	2.59	2.59	2.59	3.23	-	11.00 [3.4-14.2]	12.5	2780 [340-4390]	3.96
	16+16+16+25	1.60	1.60	1.60	2.50	-	7.30 [2.3-10.6]	8.7	1900 [310-3680]	3.84	2.50	2.50	2.50	3.90	-	11.40 [3.4-14.2]	12.8	2840 [340-4390]	4.01
	16+16+16+35	1.60	1.60	1.60	3.50	-	8.30 [2.3-10.6]	10.5	2290 [310-3600]	3.62	2.31	2.31	2.31	5.07	-	12.00 [3.4-14.2]	13.5	3000 [340-4350]	4.00
	16+16+16+42	1.60	1.60	1.60	4.20	-	9.00 [2.3-10.6]	11.8	2580 [310-3600]	3.49	2.13	2.13	2.13	5.61	-	12.00 [3.4-14.2]	13.5	2990 [340-4340]	4.01
	16+16+16+50	1.60	1.60	1.60	5.00	-	9.80 [2.3-10.6]	12.8	2780 [350-3310]	3.53	1.96	1.96	1.96	6.12	-	12.00 [3.4-14.2]	13.2	2930 [390-4190]	4.10
	16+16+16+60	1.48	1.48	1.48	5.56	-	10.00 [2.3-10.6]	13.3	2910 [350-3310]	3.44	1.78	1.78	1.78	6.66	-	12.00 [3.4-14.2]	13.2	2930 [390-4190]	4.10
	16+16+16+71	1.34	1.34	1.34	5.98	-	10.00 [2.3-10.6]	13.1	2850 [380-3240]	3.51	1.61	1.61	1.61	7.17	-	12.00 [3.4-14.2]	13.1	2920 [400-4170]	4.11
	16+16+20+20	1.60	1.60	2.00	2.00	-	7.20 [2.3-10.6]	8.5	1850 [310-3600]	3.89	2.58	2.58	3.22	3.22	-	11.60 [3.4-14.2]	12.9	2870 [340-4370]	4.04
	16+16+20+25	1.60	1.60	2.00	2.50	-	7.70 [2.3-10.6]	9.4	2050 [310-3600]	3.76	2.49	2.49	3.12	3.90	-	12.00 [3.4-14.2]	13.6	3010 [340-4370]	3.99
	16+16+20+35	1.60	1.60	2.00	3.50	-	8.70 [2.3-10.6]	11.2	2450 [310-3530]	3.55	2.21	2.21	2.76	4.82	-	12.00 [3.4-14.2]	13.5	2990 [340-4340]	4.01
	16+16+20+42	1.60	1.60	2.00	4.20	-	9.40 [2.3-10.6]	12.6	2740 [310-3530]	3.43	2.04	2.04	2.56	5.36	-	12.00 [3.4-14.2]	13.4	2980 [340-4320]	4.03
	16+16+20+50	1.57	1.57	1.96	4.90	-	10.00 [2.3-10.6]	13.3	2910 [350-3310]	3.44	1.88	1.88	2.36	5.88	-	12.00 [3.4-14.2]	13.1	2920 [400-4170]	4.11
	16+16+20+60	1.43	1.43	1.79	5.35	-	10.00 [2.3-10.6]	13.3	2910 [350-3310]	3.44	1.71	1.71	2.15	6.43	-	12.00 [3.4-14.2]	13.1	2920 [400-4170]	4.11
	16+16+20+71	1.30	1.30	1.63	5.77	-	10.00 [2.3-10.8]	13.1	2850 [380-3380]	3.51	1.56	1.56	1.95	6.93	-	12.00 [3.4-14.2]	13.1	2910 [400-4160]	4.12
	16+16+25+25	1.60	1.60	2.50	2.50	-	8.20 [2.3-10.6]	10.2	2230 [310-3600]	3.68	2.34	2.34	3.66	3.66	-	12.00 [3.4-14.2]	13.6	3010 [340-4370]	3.99
	16+16+25+35	1.60	1.60	2.50	3.50	-	9.20 [2.3-10.6]	12.3	2680 [310-3530]	3.43	2.09	2.09	3.26	4.56	-	12.00 [3.4-14.2]	13.5	2990 [340-4340]	4.01
	16+16+25+42	1.60	1.60	2.50	4.20	-	9.90 [2.3-10.6]	13.9	3040 [310-3530]	3.26	1.94	1.94	3.03	5.09	-	12.00 [3.4-14.2]	13.4	2980 [340-4320]	4.03
	16+16+25+50	1.50	1.50	2.34	4.66	-	10.00 [2.3-10.6]	13.3	2910 [350-3310]	3.44	1.79	1.79	2.81	5.61	-	12.00 [3.4-14.2]	13.1	2920 [400-4170]	4.11
	16+16+25+60	1.37	1.37	2.14	5.12	-	10.00 [2.3-10.6]	13.3	2910 [350-3310]	3.44	1.64	1.64	2.57	6.15	-	12.00 [3.4-14.2]	13.1	2920 [400-4170]	4.11
	16+16+25+71	1.25	1.25	1.95	5.55	-	10.00 [2.3-10.8]	13.1	2850 [380-3380]	3.51	1.50	1.50	2.34	6.66	-	12.00 [3.4-14.4]	13.1	2910 [400-4220]	4.12
	16+16+35+35	1.57	1.57	3.43	3.43	-	10.00 [2.3-10.6]	13.9	3040 [320-3530]	3.29	1.88	1.88	4.12	4.12	-	12.00 [3.4-14.2]	13.3	2960 [360-4300]	4.05
	16+16+35+42	1.47	1.47	3.21	3.85	-	10.00 [2.3-10.6]	13.9	3040 [320-3450]	3.29	1.76	1.76	3.86	4.62	-	12.00 [3.4-14.2]	13.3	2950 [360-4220]	4.07
	16+16+35+50	1.37	1.37	2.99	4.27	-	10.00 [2.3-10.6]	13.1	2850 [380-3240]	3.51	1.64	1.64	3.59	5.13	-	12.00 [3.4-14.2]	13.1	2900 [420-4140]	4.14
	16+16+35+60	1.26	1.26	2.76	4.72	-	10.00 [2.3-10.8]	13.1	2850 [380-3380]	3.51	1.51	1.51	3.31	5.67	-	12.00 [3.4-14.2]	13.1	2900 [420-4140]	4.14
	16+16+35+71	1.16	1.16	2.54	5.14	-	10.00 [2.3-10.8]	13.1	2850 [390-3310]	3.51	1.39	1.39	3.05	6.17	-	12.00 [3.4-14.4]	13.0	2890 [420-4180]	4.15
	16+16+42+42	1.38	1.38	3.62	3.62	-	10.00 [2.3-10.6]	13.9	3040 [320-3450]	3.29	1.66	1.66	4.34	4.34	-	12.00 [3.4-14.2]	13.2	2940 [370-4210]	4.08
	16+16+42+50	1.29	1.29	3.39	4.03	-	10.00 [2.3-10.8]	13.1	2850 [380-3380]	3.51	1.55	1.55	4.06	4.84	-	12.00 [3.4-14.2]	13.0	2890 [420-4130]	4.15
	16+16+42+60	1.19	1.19	3.14	4.48	-	10.00 [2.3-10.8]	13.1	2850 [380-3380]	3.51	1.43	1.43	3.77	5.37	-	12.00 [3.4-14.4]	13.0	2890 [420-4190]	4.15
	16+16+42+71	1.10	1.10	2.90	4.90	-	10.00 [2.3-11.0]	13.1	2850 [390-3460]	3.51	1.32	1.32	3.48	5.88	-	12.00 [3.4-14.4]	13.0	2880 [430-4170]	4.17
	16+16+50+50	1.21	1.21	3.79	3.79	-	10.00 [2.3-10.8]	12.5	2730 [430-3180]	3.66	1.45	1.45	4.55	4.55	-	12.00 [3.4-14.4]	12.8	2850 [490-4110]	4.21
	16+16+50+60	1.13	1.13	3.52	4.22	-	10.00 [2.3-11.0]	12.5	2730 [430-3320]	3.66	1.35	1.35	4.23	5.07	-	12.00 [3.4-14.4]	12.8	2850 [490-4110]	4.21
	16+16+50+71	1.05	1.05	3.27	4.63	-	10.00 [2.3-11.0]	12.5	2730 [460-3320]	3.66	1.25	1.25	3.93	5.57	-	12.00 [3.4-14.4]	13.0	2890 [510-4100]	4.15
	16+16+60+60	1.05	1.05	3.95	3.95	-	10.00 [2.3-11.0]	12.5	2730 [430-3320]	3.66	1.26	1.26	4.74	4.74	-	12.00 [3.4-14.4]	12.8	2850 [490-4110]	4.21
	16+16+60+71	0.98	0.98	3.68	4.36	-	10.00 [2.3-11.2]	12.5	2730 [460-3400]	3.66	1.18	1.18	4.42	5.22	-	12.00 [3.4-14.4]	13.0	2890 [510-4100]	4.15
	16+16+71+71	0.92	0.92	4.08	4.08	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.10	1.10	4.90	4.90	-	12.00 [3.4-14.4]	13.0	2880 [510-4140]	4.17
	16+20+20+20	1.60	2.00	2.00	2.00	-	7.60 [2.3-10.6]	9.3	2020 [310-3600]	3.76	2.52	3.16	3.16	3.16	-	12.00 [3.4-14.2]	13.5	3000 [340-4360]	4.00
	16+20+20+25	1.60	2.00	2.00	2.50	-	8.10 [2.3-10.6]	10.0	2170 [310-3600]	3.73	2.38	2.96	2.96	3.70	-	12.00 [3.4-14.2]	13.5	3000 [340-4360]	4.00
	16+20+20+35	1.60	2.00	2.00	3.50	-	9.10 [2.3-10.6]	12.0	2610 [310-3530]	3.49	2.11	2.64	2.64	4.61	-	12.00 [3.4-14.2]	13.4	2980 [340-4320]	4.03
	16+20+20+42	1.60	2.00	2.00	4.20	-	9.80 [2.3-10.6]	13.3	2910 [310-3530]	3.37	1.96	2.45	2.45	5.14	-	12.00 [3.4-14.2]	13.4	2970 [350-4310]	4.04
16+20+20+50	1.51	1.89	1.89	4.71	-	10.00 [2.3-10.6]	13.1	2850 [360-3240]	3.51	1.82	2.26	2.26	5.66	-	12.00 [3.4-14.2]	13.1	2910 [400-4160]	4.12	
16+20+20+60	1.39	1.72	1.72	5.17	-	10.00 [2.3-10.6]	13.1	2850 [360-3240]	3.51	1.66	2.07	2.07	6.20	-	12.00 [3.4-14.2]	13.1	2910 [400-4160]	4.12	
16+20+20+71	1.27	1.57	1.57	5.59	-	10.00 [2.3-10.8]	13.1	2850 [390-3310]	3.51	1.51	1.89	1.89	6.71	-	12.00 [3.4-14.2]	13.1	2900 [420-4140]	4.14	
16+20+25+25	1.60	2.00	2.50	2.50	-	8.60 [2.3-10.6]	11.1	2410 [310-3600]	3.57	2.23	2.79	3.49	3.49	-	12.00 [3.4-14.2]	13.5	3000 [340-4360]	4.00	
16+20+25+35	1.60	2.00	2.50	3.50	-	9.60 [2.3-10.6]	13.0	2840 [310-3530]	3.38	2.00	2.50	3.13	4.37	-	12.00 [3.4-14.2]	13.4	2980 [340-4320]	4.03	
16+20+25+42	1.55	1.94	2.43	4.08	-	10.00 [2.3-10.6]	13.9	3040 [310-3530]	3.29	1.87	2.33	2.91	4.89	-	12.00 [3.4-14.2]	13.4	2970 [350-4310]	4.04	
16+20+25+50	1.45	1.80	2.25	4.50	-	10.00 [2.3-10.6]	13.1	2850 [360-3240]	3.51	1.73	2.16	2.70	5.41	-	12.00 [3.4-14.2]	13.1	2910 [400-4160]	4.12	
16+20+25+60	1.32	1.65	2.07	4.96	-	10.00 [2.3-10.8]	13.1	2850 [360-3380]	3.51	1.59	1.98	2.48	5.95	-	12.00 [				

CU-5Z100VBR: Free Multi Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
4 rooms	16+20+71+71	0.90	1.12	3.99	3.99	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.08	1.34	4.79	4.79	-	12.00 [3.4-14.4]	12.9	2870 [520-4130]	4.18
	16+25+25+25	1.60	2.50	2.50	2.50	-	9.10 [2.3-10.6]	12.0	2610 [310-3600]	3.49	2.10	3.30	3.30	3.30	-	12.00 [3.4-14.2]	13.5	3000 [340-4360]	4.00
	16+25+25+35	1.58	2.48	2.48	3.46	-	10.00 [2.3-10.6]	13.9	3040 [310-3530]	3.29	1.90	2.97	2.97	4.16	-	12.00 [3.4-14.2]	13.4	2980 [340-4320]	4.03
	16+25+25+42	1.49	2.31	2.31	3.89	-	10.00 [2.3-10.6]	13.9	3040 [310-3530]	3.29	1.78	2.78	2.78	4.66	-	12.00 [3.4-14.2]	13.4	2970 [350-4310]	4.04
	16+25+25+50	1.38	2.16	2.16	4.30	-	10.00 [2.3-10.6]	13.1	2850 [360-3240]	3.51	1.66	2.59	2.59	5.16	-	12.00 [3.4-14.2]	13.1	2910 [400-4160]	4.12
	16+25+25+60	1.28	1.98	1.98	4.76	-	10.00 [2.3-10.8]	13.1	2850 [360-3380]	3.51	1.53	2.38	2.38	5.71	-	12.00 [3.4-14.2]	13.1	2910 [400-4160]	4.12
	16+25+25+71	1.18	1.82	1.82	5.18	-	10.00 [2.3-10.8]	13.1	2850 [390-3310]	3.51	1.40	2.19	2.19						

CU-5Z100VBR: Free Multi Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION								HEATING OPERATION									
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	Total
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
4 rooms	20+20+35+71	1.37	1.37	2.40	4.86	-	10.00 [2.3-11.0]	12.8	2780 [390-3390]	3.60	1.64	1.64	2.88	5.84	-	12.00 [3.4-14.4]	12.9	2870 [430-4160]	4.18
	20+20+42+42	1.61	1.61	3.39	3.39	-	10.00 [2.3-10.8]	13.7	2980 [340-3600]	3.36	1.94	1.94	4.06	4.06	-	12.00 [3.4-14.2]	13.1	2920 [370-4190]	4.11
	20+20+42+50	1.52	1.52	3.18	3.78	-	10.00 [2.3-10.8]	13.1	2850 [390-3310]	3.51	1.82	1.82	3.82	4.54	-	12.00 [3.4-14.4]	12.9	2870 [430-4160]	4.18
	20+20+42+60	1.41	1.41	2.96	4.22	-	10.00 [2.3-11.0]	13.1	2850 [390-3460]	3.51	1.69	1.69	3.55	5.07	-	12.00 [3.4-14.4]	12.9	2870 [430-4160]	4.18
	20+20+42+71	1.31	1.31	2.75	4.63	-	10.00 [2.3-11.0]	12.8	2780 [390-3390]	3.60	1.57	1.57	3.29	5.57	-	12.00 [3.4-14.4]	12.9	2860 [440-4200]	4.20
	20+20+50+50	1.43	1.43	3.57	3.57	-	10.00 [2.3-10.8]	12.5	2730 [440-3180]	3.66	1.71								

CU-5Z100VBR: Free Multi Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	Total
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
4 rooms	25+25+35+60	1.72	1.72	2.42	4.14	-	10.00 [2.3-11.0]	13.1	2850 [390-3460]	3.51	2.07	2.07	2.90	4.96	-	12.00 [3.4-14.4]	13.0	2880 [420-4170]	4.17
	25+25+35+71	1.60	1.60	2.25	4.55	-	10.00 [2.3-11.0]	12.8	2780 [390-3390]	3.60	1.92	1.92	2.70	5.46	-	12.00 [3.4-14.4]	12.9	2870 [430-4160]	4.18
	25+25+42+42	1.87	1.87	3.13	3.13	-	10.00 [2.3-10.8]	13.7	2980 [340-3600]	3.36	2.24	2.24	3.76	3.76	-	12.00 [3.4-14.4]	13.1	2920 [370-4310]	4.11
	25+25+42+50	1.76	1.76	2.96	3.52	-	10.00 [2.3-11.0]	13.1	2850 [390-3460]	3.51	2.11	2.11	3.55	4.23	-	12.00 [3.4-14.4]	12.9	2870 [430-4160]	4.18
	25+25+42+60	1.64	1.64	2.77	3.95	-	10.00 [2.3-11.0]	13.1	2850 [390-3460]	3.51	1.97	1.97	3.32	4.74	-	12.00 [3.4-14.4]	12.9	2870 [430-4160]	4.18
	25+25+42+71	1.53	1.53	2.58	4.36	-	10.00 [2.3-11.2]	12.8	2780 [390-3530]	3.60	1.84	1.84	3.09	5.23	-	12.00 [3.4-14.4]	12.9	2860 [440-4200]	4.20
	25+25+50+50	1.67	1.67	3.33	3.33	-	10.00 [2.3-11.0]	12.5	2730 [440-3320]	3.66	2.00	2.00	4.00	4.00	-	12.00 [3.4-14.4]	13.0	2880 [510-4150]	4.17
	25+25+50+60	1.56	1.56	3.13	3.75	-	10.00 [2.3-11.2]	12.5	2730 [440-3390]	3.66	1.88	1.88	3.75	4.49	-	12.00 [3.4-14.4]	13.0	2880 [510-4150]	4.17
	25+25+50+71	1.46	1.46	2.93	4.15	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.75	1.75	3.52	4.98	-	12.00 [3.4-14.4]	12.9	2870 [520-4130]	4.18
	25+25+60+60	1.47	1.47	3.53	3.53	-	10.00 [2.3-11.2]	12.5	2730 [440-3390]	3.66	1.76	1.76	4.24	4.24	-	12.00 [3.4-14.4]	13.0	2880 [510-4150]	4.17
	25+25+60+71	1.38	1.38	3.32	3.92	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.66	1.66	3.98	4.70	-	12.00 [3.4-14.4]	12.9	2870 [520-4130]	4.18
	25+35+35+35	1.93	2.69	2.69	2.6														

CU-5Z100VBR: Free Multi Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION								HEATING OPERATION									
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
5 rooms	16+16+16+16+16	1.60	1.60	1.60	1.60	1.60	8.00 [2.3-11.5]	9.0	1990 [390-3810]	4.02	2.40	2.40	2.40	2.40	2.40	12.00 [3.4-14.5]	13.4	3050 [540-4320]	3.93
	16+16+16+16+20	1.60	1.60	1.60	1.60	2.00	8.40 [2.3-11.5]	9.5	2100 [390-3810]	4.00	2.29	2.29	2.29	2.29	2.84	12.00 [3.4-14.5]	13.3	3040 [560-4310]	3.95
	16+16+16+16+25	1.60	1.60	1.60	1.60	2.50	8.90 [2.3-11.5]	10.3	2270 [390-3810]	3.92	2.16	2.16	2.16	2.16	3.36	12.00 [3.4-14.5]	13.3	3040 [560-4310]	3.95
	16+16+16+16+35	1.60	1.60	1.60	1.60	3.50	9.90 [2.3-11.5]	12.2	2690 [420-3740]	3.68	1.94	1.94	1.94	1.94	4.24	12.00 [3.4-14.5]	13.4	3070 [570-4270]	3.91
	16+16+16+16+42	1.51	1.51	1.51	1.51	3.96	10.00 [2.3-11.5]	12.5	2750 [430-3740]	3.64	1.81	1.81	1.81	1.81	4.76	12.00 [3.4-14.5]	13.4	3060 [580-4320]	3.92
	16+16+16+16+50	1.40	1.40	1.40	1.40	4.40	10.00 [2.3												

CU-5Z100VBR: Free Multi Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION								HEATING OPERATION									
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
5 rooms	16+16+25+25+35	1.37	1.37	2.14	2.14	2.98	10.00 [2.3-11.5]	12.5	2750 [430-3740]	3.64	1.64	1.64	2.56	2.56	3.60	12.00 [3.4-14.5]	13.4	3050 [600-4310]	3.93
	16+16+25+25+42	1.29	1.29	2.02	2.02	3.38	10.00 [2.3-11.5]	12.5	2750 [430-3660]	3.64	1.55	1.55	2.42	2.42	4.06	12.00 [3.4-14.5]	13.4	3050 [600-4300]	3.93
	16+16+25+25+50	1.21	1.21	1.89	1.89	3.80	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.45	1.45	2.27	2.27	4.56	12.00 [3.4-14.5]	13.4	3070 [710-4230]	3.91
	16+16+25+25+60	1.13	1.13	1.76	1.76	4.22	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.35	1.35	2.11	2.11	5.08	12.00 [3.4-14.5]	13.4	3070 [710-4230]	3.91
	16+16+25+25+71	1.05	1.05	1.63	1.63	4.64	10.00 [2.3-11.5]	12.3	2710 [520-3530]	3.69	1.25	1.25	1.96	1.96	5.58	12.00 [3.4-14.5]	13.4	3060 [720-4220]	3.92
	16+16+25+35+35	1.26	1.26	1.96	2.76	2.76	10.00 [2												

CU-5Z100VBR: Free Multi Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION								HEATING OPERATION									
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
5 rooms	16+20+25+25+50	1.18	1.47	1.84	1.84	3.67	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.41	1.76							

CU-5Z100VBR: Free Multi Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION								HEATING OPERATION									
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
5 rooms	16+35+35+42+42	0.94	2.06	2.06	2.47	2.47	10.00 [2.3-11.5]	12.3	2700 [480-3600]	3.70	1.14	2.47	2.47	2					

CU-5Z100VBR: Free Multi Indoor Capacity Tables

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
		Room A	Room B	Room C	Room D	Room E				Total	Room A	Room B	Room C	Room D				Room E	
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
5 rooms	20+25+25+25+71	1.20	1.51	1.51	1.51	4.27	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.45								