



B62AWY-9L6

Ducted System - High Static  
18kW (Cooling)

Zone Control of up to 8 zones with the LG  
premium controller

Wi-Fi Compatible (Dongle module sold separately)

Quiet Mode

5 Year Parts and Labour Warranty

PERFORMANCE

Rated Capacity - Cooling	18.0 kW	Rated Capacity - Heating	20.6 kW
Capacity Range - Cooling (Min - Max)	7.2 ~ 19.8 kW	Capacity Range - Heating (Min - Max)	8.2 ~ 22.7 kW
Rated Power Input - Cooling	5.47 kW	Rated Power Input - Heating	5.49 kW
EER/COP (Cooling/Heating)	3.29 / 3.75	Rated Current (Cooling/Heating)	9.3 / 9.6 A
Air Flow Rate (Min ~ Max L/s)	550 ~ 1600		

INDOOR

Sound Level at 1.5m (H/M/L)	43 / 41 / 40 Pressure dB(A)	Dimensions (W x H x D)	1,563 x 458 x 791 mm
Weight	89 kg		

OUTDOOR

Sound Level at 1m (Cooling/Heating)	59 / 60 Pressure dB(A)	Sound Power Level	71 dB(A)
Dimensions (W x H x D)	1,090 x 1,625 x 380 mm	Weight	144 kg

TECHNICAL

Rated Power Input - Indoor	220-240, 1, 50 V / Phase / Hz	Rated Power Input - Outdoor	380-415, 3, 50 V / Phase / Hz
----------------------------	-------------------------------	-----------------------------	-------------------------------

4/21/22, 10:23 AM

Ducted System - High Static 18kW (Cooling)

Circuit Breaker	30 A	Compressor Type	Hermetically Sealed Scroll
Refrigerant Type	R410A	Refrigerant Precharged Length	15 m
Pipe Sizes (Liquid)	Ø 12.7 (1/2) mm/inch	Pipe Sizes (Gas)	Ø 22.8 (7/8) mm/inch
Pipe Sizes (Drain OD/ID)	Ø 32 / 25 mm	Max. Piping Length	75 m
Max. Height Difference (ODU - IDU)	30 m	Supply Air Opening (Hx W, Flange)	286 x 1,044 mm
Return Air Opening (Oval)	392 x 1,368 mm	Continuous Operating Range - Cooling	-20 ~ 48 °C DB
Continuous Operating Range - Heating	-18 ~ 18 °C WB		