



B30AWY-7G6

Ducted System - High Static
8.8kW (Cooling)

- Zone Control of up to 8 zones with the LG premium controller
- Wi-Fi Compatible (Dongle module sold separately)
- Quiet Mode
- Compact indoor unit helps make it easy to install in small spaces
- 5 Year Parts and Labour Warranty

PERFORMANCE

Rated Capacity - Cooling	8.8 kW	Rated Capacity - Heating	9.4 kW
Capacity Range - Cooling (Min - Max)	2.5 ~ 9.6 kW	Capacity Range - Heating (Min - Max)	2.7 ~ 11.1 kW
Rated Power Input - Cooling	2.58 kW	Rated Power Input - Heating	2.32 kW
AEER/ACOP (Cooling/Heating)	3.39 / 4.0	EER/COP (Cooling/Heating)	3.41 / 4.05
Rated Current (Cooling/Heating)	11.4 / 10.3 A	Max. Current (Full Load Amps)	17 A
Air Flow Rate (Min ~ Max L/s)	132 ~ 771		

INDOOR

Sound Level at 1.5m (H/M/L)	41 / 40 / 39 Pressure dB(A)	Dimensions (W x H x D)	1,320 x 400 x 534 mm
Weight	48 kg		

OUTDOOR

Sound Level at 1m (Cooling/Heating)	51 / 52 Pressure dB(A)	Sound Power Level	64 dB(A)
Dimensions (W x H x D)	950 x 834 x 330 mm	Weight	58.5 kg

TECHNICAL

Power Supply	220-240, 1, 50 V / Phase / Hz	Circuit Breaker	25 A
Compressor Type	Inverter Twin Rotary	Refrigerant Type	R410A
Refrigerant Precharged Length	10 m	Pipe Sizes (Liquid)	Ø 9.52 (3/8) mm/inch
Pipe Sizes (Gas)	Ø 15.88 (5/8) mm/inch	Pipe Sizes (Drain OD/ID)	Ø 32 / 25 mm
Max. Piping Length	30 m	Max. Height Difference (ODU - IDU)	30 m
Supply Air Opening (Hx W, Flange)	287 x 840 mm	Return Air Opening (Oval)	317 x 1,172 mm
Continuous Operating Range - Cooling	-15 ~ 48 °C DB	Continuous Operating Range - Heating	-18 ~ 18 °C WB
Demand Response	Capable		